

## CTVF-0 Series

From 1.0  $\mu\text{H}$  to 390  $\mu\text{H}$



### SPECIFICATIONS

Part numbers indicate inductance tolerance available.

K =  $\pm 10\%$ , L =  $\pm 15\%$

Part Number	Inductance ( $\mu\text{H}$ )	Rated Current (A)	DCR Max. ( $\Omega$ )	Physical Dimensions (in/mm)			
				A Max.	B Max.	C $\pm 0.015/0.38$	D $\pm 0.015/0.38$
CTVF-0-1R0L-25	1.0	21.8	0.002	0.60/15.2	0.68/17.3	0.42/10.7	0.068/1.73
CTVF-0-1R0L-10	1.0	16.7	0.003	0.50/12.7	0.75/19.1	0.42/10.7	0.054/1.37
CTVF-0-3R3L-10	3.3	12.7	0.005	0.50/12.7	1.0/25.4	0.42/10.7	0.054/1.37
CTVF-0-4R7L-03	4.7	7.4	0.021	0.51/13.0	0.75/19.1	0.42/10.7	0.035/0.89
CTVF-0-4R7L-05	4.7	8.9	0.012	0.50/12.7	0.75/19.1	0.42/10.7	0.042/1.07
CTVF-0-4R7L-10	4.7	11.9	0.012	0.50/12.7	1.0/25.4	0.42/10.7	0.054/1.37
CTVF-0-4R7L-20	4.7	16.4	0.004	0.53/13.5	1.2/30.5	0.42/10.7	0.068/1.73
CTVF-0-100K-03	10	5.9	0.023	0.50/12.7	0.75/19.1	0.42/10.7	0.035/0.89
CTVF-0-100K-05	10	7.1	0.017	0.50/12.7	0.75/19.1	0.42/10.7	0.042/1.07
CTVF-0-100K-10	10	11.8	0.015	0.52/13.2	1.0/25.4	0.42/10.7	0.054/1.37
CTVF-0-100K-20	10	17	0.006	0.75/19.1	1.8/45.7	0.60/15.2	0.075/1.91
CTVF-0-150K-03	15	6.8	0.025	0.50/12.7	1.0/25.4	0.42/10.7	0.035/0.89
CTVF-0-150K-10	15	9.8	0.02	0.52/13.2	1.0/25.4	0.42/10.7	0.054/1.37
CTVF-0-220K-03	22	7.4	0.035	0.50/12.7	1.0/25.4	0.42/10.7	0.035/0.89
CTVF-0-220K-05	22	8.9	0.023	0.50/12.7	1.0/25.4	0.42/10.7	0.042/1.07
CTVF-0-220K-10	22	13	0.015	0.66/16.8	1.3/33.0	0.42/10.7	0.060/1.52
CTVF-0-270K-05	27	7.1	0.024	0.50/12.7	1.0/25.4	0.49/12.5	0.042/1.07
CTVF-0-330K-12	33	11.3	0.017	0.70/17.8	1.3/33.0	0.55/14.0	0.060/1.52
CTVF-0-470K-03	47	4.3	0.05	0.55/14.0	1.0/25.4	0.42/10.7	0.035/0.89
CTVF-0-470K-05	47	6.0	0.035	0.65/16.5	1.1/28.0	0.70/17.8	0.042/1.07
CTVF-0-470K-10	47	8.7	0.022	0.85/21.6	1.3/33.0	0.70/17.8	0.060/1.52
CTVF-0-820K-03	82	2.8	0.11	0.50/12.7	0.65/16.5	0.375/9.5	0.028/0.71
CTVF-0-101K-01	100	1.8	0.19	0.40/10.2	0.90/22.9	0.30/7.6	0.020/0.51
CTVF-0-101K-03	100	3.8	0.072	0.55/14.0	1.2/30.5	0.70/17.8	0.035/0.89
CTVF-0-101K-05	100	5.5	0.055	0.65/16.5	1.3/33.0	0.70/17.8	0.042/1.07
CTVF-0-151K-03	150	2.8	0.14	0.60/15.2	1.2/30.5	0.43/10.9	0.028/0.71
CTVF-0-151K-05	150	5.2	0.065	0.65/16.5	1.3/33.0	0.70/17.8	0.042/1.07
CTVF-0-181K-05	180	3.3	0.11	0.60/15.2	1.2/30.5	0.43/10.9	0.035/0.89
CTVF-0-221K-03	220	2.1	0.21	0.55/14.0	1.2/30.5	0.42/10.7	0.025/0.64
CTVF-0-271K-04	270	2.1	0.25	0.95/24.0	0.72/18.3	0.71/18.0	0.030/0.76
CTVF-0-271K-10	270	3.6	0.16	1.1/28.0	1.0/25.4	0.72/18.3	0.038/0.97
CTVF-0-391K-03	390	3.0	0.25	1.1/28.0	1.0/25.4	0.72/18.3	0.035/0.89
CTVF-0-391K-05	390	3.1	0.19	1.1/28.0	1.0/25.4	0.72/18.3	0.038/0.97

### CHARACTERISTICS

**Description:** Radial leaded power inductor.

**Applications:** Used in switching regulators, power amplifiers, power supplies, SCR and Triac controls, speaker crossover networks, RFI suppression and filters.

**Inductance Tolerance:**  $\pm 10\%$ ,  $\pm 15\%$

**Operating Temperature:**  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$

**Rated Current:** Based on the inductance change within 10% of initial value.

**Testing:** Inductance is tested on an HP4284A at 15.75KHz.

**Sleeving:** Poly-Olefin shrink tube.

**Packaging:** Bulk.

**Marking:** Parts are marked with inductance code.

**Miscellaneous:** **RoHS Compliant.**

**Additional Information:** Additional electrical & physical information available upon request.

**Samples available. See website for ordering information.**

