

EasyView™ Light Meters


Choice of models for high intensity measurements
Up to 400,000 Lux and 40,000 Foot candles

Features:

- Compact and rugged design features large display
- Multiple wide measuring ranges:
Model EA30 - 40,000Fc in 4 ranges and 400,000Lux in 5 Ranges
Model EA31 - 20,000Fc in 4 ranges and 20,000Lux in 4 ranges
- Data hold freezes reading on display
- MIN/MAX readings
- Zero function
- Cosine and color corrected measurements
- Low battery and overrange indication
- Auto power off to save battery life
- Utilizes precision silicon photodiode sensor with 3ft coiled cable for easy storage
- Complete with built-in stand, remote sensor with protective cover, protective rubber holster, and 6 AAA batteries

Additional features for Model EA30:

- Large display with bargraph
- Peak hold captures short light pulses to 100µSec
- Relative function for zero or difference from reference value



High resolution for low level measurements in places like parking lots, stairwells, and ATM machines

Specifications	Range	Resolution	Basic Accuracy
Light Intensity			
EA30	Lux	40, 400, 4000, 40000, 400000Lux	0.01 ±3%rdg + 0.5%FS
	Foot candles	40, 400, 4000, 40000Fc	
EA31	Lux	20, 200, 2000, 20000Lux	0.01 ±3%rdg + 0.5%FS
	Foot candles	20, 200, 2000, 20000Fc	
Dimensions			
5.9 x 2.8 x 1.4" (150 x 72 x 33mm)			
Weight			
8.3oz (235g)			

Ordering Information:

- EA30.....EasyView™ High Intensity Light Meter
EA30-NISTEA30 with NIST Certificate
EA31.....EasyView™ Light Meter
EA31-NISTEA30 with NIST Certificate

