

## Features

- Low output noise = 4.0nA/rt-Hz
- High-performance laser diode driver
- Pin compatible with EL6257
- Voltage-controlled output current source to 150 mA per channel, requiring one external set resistor per channel
- Current-controlled output current source to 150 mA per channel
- Rise time = 1.0 ns
- Fall time = 1.1 ns
- On chip oscillator with frequency and amplitude control by use of external resistors to ground
- Oscillator to 500 MHz
- Oscillator to 100 mA pk/pk
- Single +5V supply ( $\pm 10\%$ )
- Disable feature for power-up protection and power savings
- TTL/CMOS control signals

## Applications

- DVD-RAM high speed drives
- CD-RW applications
- Writable optical drives
- Laser diode current switching

## Ordering Information

Part No	Temp. Range	Package	Outline #
EL6259CU	0°C to +70°C	QSOP-24	MDP0040

## Complete Product Specifications Elantec Technical Support:

North America: 1-888-352-6832 X 311  
Asia: +85-45-682-5820  
Europe: +44-18-977-6020

## General Description


The EL6259C is a low noise four channel laser diode current amplifier that provides controlled current to a grounded laser diode. The four amplifiers can provide up to 150 mA per channel of DC or pulsed current. Channels 2, 3, and 4 must be used as the write channels, with switching speeds of approximately one nanosecond rise/fall time. All four channels are summed together at the I<sub>OUT</sub> output, allowing the user to create multilevel waveforms in order to optimize laser diode performance. The level of the output current is set by an analog voltage applied to an external resistor which converts the voltage into a current at the I<sub>IN</sub> pin. The current seen at this pin is then amplified by 100X to become a current source at pin I<sub>OUT</sub>.

An on-chip 500 MHz oscillator is provided to allow current modulation when in the read mode. This is turned on when the EOSC pin is held high (floating not recommended). Complete control of amplitude and frequency is set by two external resistors connected to ground at pins RFREQ and RAMP (see graphs in this data sheet for further explanation).

Output current pulses are enabled when an 'L' signal is applied to the  $\overline{\text{OE}}$  pin. No output current flows when  $\overline{\text{OE}}$  is 'H', and additional laser diode protection is provided since the  $\overline{\text{OE}}$  input will float high when open. Complete I<sub>OUT</sub> shut-off is also achieved by holding the CE pin low, which will override the  $\overline{\text{OE}}$  control pins.

The external resistors allow the user to accurately and independently set each amplifier transconductance by applying a voltage to each resistor, without restriction on the voltage range, thus ensuring broad voltage DAC compatibility. Alternatively, the I<sub>IN</sub> pin can be biased from a current DAC or other current source.

## Connection Diagram



# ***EL6259C - Product Brief***

***Low Noise 4-Channel Laser Diode Driver + Oscillator***

## **General Disclaimer**

Specifications contained in this product brief are in effect as of the publication date shown. Elantec Semiconductor, Inc. reserves the right to make changes in the circuitry or specifications contained herein at any time without notice. Elantec Semiconductor, Inc. assumes no responsibility for the use of any circuits described herein and makes no representations that they are free from patent infringement.

# ***élantec***

HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

## **Elantec Semiconductor, Inc.**

675 Trade Zone Blvd.  
Milpitas, CA 95035

Telephone: (408) 945-1323  
(888) 352-6832 (toll free)

Fax: (408) 945-9305  
European Office: 44-18-977-6020  
Japan Office: 85-45-682-5820

## **WARNING - Life Support Policy**

Elantec Semiconductor, Inc. products are not authorized for and should not be used within Life Support Systems without the specific written consent of Elantec Semiconductor, Inc. Life Support systems are equipment intended to support or sustain life and whose failure to perform when properly used in accordance with instructions provided can be reasonably expected to result in significant personal injury or death. Users contemplating application of Elantec Semiconductor, Inc. Products in Life Support Systems are requested to contact Elantec Semiconductor, Inc. factory headquarters to establish suitable terms & conditions for these applications. Elantec Semiconductor, Inc.'s warranty is limited to replacement of defective components and does not cover injury to persons or property or other consequential damages.