


10/100Base-TX Module for Multi-Port Applications

EPF8049S





- Optimized for ICS 1890 & SSI 78Q2120 Chips
- Recommended for Broadcom BCM5208 10/100 Solution
- Complies with or exceeds IEEE 802.3, 10/100Base-TX Standards
- Significantly Improved Common Mode Attenuation
- Guaranteed to operate with 8 mA DC Bias at 70°C

Electrical Parameters @ 25° C


OCL (@ 70°C)	Insertion Loss (dB Max.)			Return Loss (dB Min.)			Common Mode Rejection (dB Min.)				Crosstalk (dB Min.)	
	0.1-80 MHz	100 MHz	150 MHz	1-30 MHz	60 MHz	100 MHz	30-100 MHz	200 MHz	300 MHz	500 MHz		
100 KHz, 0.1 Vrms 8 mA DC Bias												
Cable Side	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	
350 μ H	-1/-1	-1/-1	-3/-3	-18/-18	-12/-12	-10/-10	-30/-28	-25/-20	-20/-10	-15/---		-30

• Isolation : 1500 Vrms • Impedance : 100 Ω • Rise Time : 3.0 nS Max. •

Schematic



Package



Unless Otherwise Specified Dimensions are in Inches /mm \pm .010 / .25