Switchcraft

F SERIES RECEPTACLES WITH FERRITE

PRODUCT BULLETIN 5 2 4



Switchcraft now offers the F Series. Available in male and female, the receptacles can be mounted from the rear of the panel. Features include an all metal housing with a ferrite disk for added EMI/RMI shielding. Both male and female connectors can be mounted vertical or horizontal to the PC board. All connectors have a PC-board retention feature to hold the connectors firmly to the PC board prior to soldering. See the chart below for part numbers.

F SERIES FEATURES

- Replaces Cannon XLM-Series
- 3-pin contact; male and female types
- Both male and female fit in same panel cutout
- · Locking receptacles
- Silver-plated contacts
- Rugged metal shells; satin nickel finishes
- Through-the-shell ground connection and all-metal shells for greater shielding effectiveness
- Compatible with Switchcraft Q-G®, QGP and other connectors with similar configurations
- Added EMI/RFI ferrite shield

SPECIFICATIONS: ELECTRICAL

QC® PART NUMBERING SYSTEM

Each character (or absence thereof) in the part numbers listed denotes one specific feature.

Character	Description		
F	Series designator		
3	3 pins or contacts		
*	M Đ male connector; F Đ female connector		
RA	Right-angle PC terminals		
ST	Straight PC terminals		
F	Ferrite		

Switchcraft

TERMINALS

Two terminations are available on F-Series receptacles:

1. Straight PC-terminals - direct termination to PC-board. Housing

Part Number	Terminals	Contacts	Housing	Туре
F3MSTF	Straight	Silver	Satin Nickel	М
F3FSTF				F
F3MRAF	Right Angle			М
F3FRAF				F