

**1A SURFACE MOUNT GLASS PASSIVATED BRIDGE**

**RECTIFIER Reverse Voltage - 100 to 1000 V**

**Forward Current - 1A**


**FEATURES**

- ◆High current capability
- ◆Low forward voltage drop
- ◆Glass Passivated Chip Junction
- ◆Low power loss, high efficiency
- ◆Lead free in comply with EU RoHS 2011/65/EU directives



**MECHANICAL DATA**

- ◆Case: MBF
- ◆Terminals: Solderable per MIL-STD-750, Method 2026
- ◆Approx. Weight: 75mg / 0.0026oz



**Maximum Ratings and Electrical characteristics**

Ratings at 25 °C ambient temperature unless otherwise specified.


Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

| Parameter   | Symbols                            | FMB1F      | FMB2F | FMB4F | FMB6F | FMB8F | FMB10F | Units              |
|---|------------------------------------|------------|-------|-------|-------|-------|--------|--------------------|
| Maximum Repetitive Peak Reverse Voltage   | $V_{RRM}$                          | 100        | 200   | 400   | 600   | 800   | 1000   | V                  |
| Maximum RMS voltage   | $V_{RMS}$                          | 70         | 140   | 280   | 420   | 560   | 700    | V                  |
| Maximum DC Blocking Voltage   | $V_{DC}$                           | 100        | 200   | 400   | 600   | 800   | 1000   | V                  |
| Average Rectified Output Current at $T_c = 125\text{ }^\circ\text{C}$   | $I_o$                              | 1          |       |       |       |       |        | A                  |
| Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC method)                             | $I_{FSM}$                          | 35         |       |       |       |       |        | A                  |
| Forward Voltage per element at 1.0A   | $V_F$                              | 1.3        |       |       |       |       |        | V                  |
| Maximum DC Reverse Current @ $T_A=25\text{ }^\circ\text{C}$<br>at Rated DC Blocking Voltage @ $T_A=125\text{ }^\circ\text{C}$ | $I_R$                              | 5<br>50    |       |       |       |       |        | $\mu\text{A}$      |
| Typical Junction Capacitance (Note1)  | $C_j$                              | 15         |       |       |       |       |        | pF                 |
| Maximum Reverse Recovery Time (Note2)   | $T_{rr}$<br>$T_{rr}(\text{typ})$   | 500<br>300 |       |       |       |       |        | nS                 |
| Typical Thermal Resistance (Note3)  | $R_{\theta JA}$<br>$R_{\theta JC}$ | 80<br>30   |       |       |       |       |        | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range   | $T_j, T_{stg}$                     | -55 ~ +150 |       |       |       |       |        | $^\circ\text{C}$   |


(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad.


**Fig.1 Average Rectified Output Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Instantaneous Forward Characteristics**



**Fig.4 Typical Junction Capacitance**




**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**



**Package Outline**


**MBF**

Plastic surface mounted package; 4 leads



| UNIT |     | A   | C    | D   | E   | H <sub>E</sub> | d   | e   | L   | L <sub>1</sub> | a   | ∠  |
|------|-----|-----|------|-----|-----|----------------|-----|-----|-----|----------------|-----|----|
| mm   | max | 1.6 | 0.22 | 5.0 | 4.1 | 7.0            | 2.7 | 0.8 | 1.7 | 1.1            | 0.2 | 7° |
|      | min | 1.2 | 0.15 | 4.5 | 3.6 | 6.4            | 2.3 | 0.5 | 1.3 | 0.5            | —   |    |
| mil  | max | 63  | 8.7  | 197 | 161 | 276            | 106 | 31  | 67  | 43             | 8   |    |
|      | min | 47  | 5.9  | 177 | 142 | 252            | 91  | 20  | 51  | 20             | —   |    |

**The recommended mounting pad size**



**Summary of Packing Options**

| Package | Packing Description | Packing Quantity | Industry Standard |
|---------|---------------------|------------------|-------------------|
| MBF     | Tape/Reel, 13" reel | 5000             | EIA-481-1         |