


■ Features

- Low Profile Compact Size
- High Contact Capacity
- High Sensitivity
200 mW nominal (98mW Pull-in)
- Easy Flow-Soldering
- Solvent Compatibility



UL E50288
CSA LR700402

■ Coil Rating (at 20°C)


Rated Voltage	Coil Resistance	Pull-in Voltage	Drop-out Voltage	Max. Allowable Voltage	Rated Power
3VDC	45 Ω	70%V Max. of rated voltage	10%V Min. of rated voltage	200%V of rated voltage	Approx. 0.2W
5VDC	125 Ω				
6VDC	180 Ω				
9VDC	405 Ω				
10VDC	500 Ω				
12VDC	720 Ω				
24VDC	2,880 Ω				

■ Specifications


Contact Arrangement	1 Form A	1 Form C
Contact Material	Standard : Silver alloy Low level : Gold-plated silver alloy	
Rated Load	250VAC • 10A(resistive) 30VDC • 10A(resistive)	250VAC • 7A(resistive) 30VDC • 7A(resistive)
Max. Switching Power	2,500VA/300W	
Max. Switching Current	10A	7A
Max. Switching Voltage	380VAC/125VDC	
Contact Resistance (Initial)	30m Ω Max. at 6VDC • 1A after throw	
Dielectric Strength	1000VAC for 1 minute between across contacts 2000VAC for 1 minute between coil and contacts	
Insulation Resistance	1000M Ω Min. at 500VDC	
Operate Time	10ms Max.	
Release Time	10ms Max.	
Shock	False Operation	Approx. 20G
	Endurance	Approx. 100G
Vibration	False Operation	10 to 55 Hz, amplitude 1.5mm
	Endurance	10 to 55 Hz, amplitude 1.5mm
Mechanical Life	50 X 10 ⁶ times (Switching frequency: 300 times/minute)	
Electrical Life	1 X 10 ⁵ times at rated load (Switching frequency: 30 times/minute)	
Ambient Temperature	-40 to + 70°C	
Weight	Approx. 5.5 grams.	

■ **Dimensions**

● **Flux Tight Type**



Standard Terminal




Kink Terminal




● **P.C. Board Drilling Design**


1 Form A




1 Form C



● **Sealed Type**




● **Internal Wiring Diagram (BOTTOM VIEW)**



Take notice of the polarity of coil shown above.

Taiko Brand

■ **How to order**



- Model
- Coil Voltages: 3, 5, 6, 9, 10, 12, 24 VDC
- Blank: 1 Form C (SPDT)
- M: 1 Form A (SPST-NO)
- Blank: Standard Contact
- G: Low level contact
- Blank: Standard terminal type
- C: Kink terminal type