

## Features

- 10A, 400V and 500V
- $V_{CE(ON)}$  2.5V Max.
- $T_{FALL} \leq 1.4\mu s$
- Low On-State Voltage
- Fast Switching Speeds
- High Input Impedance

## Applications

- Power Supplies
- Motor Drives
- Protective Circuits

## Description

The HGTD10N40F1, HGTD10N40F1S, HGTD10N50F1, and HGTD10N50F1S are n-channel enhancement-mode insulated gate bipolar transistors (IGBTs) designed for high voltage, low on-dissipation applications such as switching regulators and motor drivers. These types can be operated directly from low power integrated circuits.


### PACKAGING AVAILABILITY

PART NUMBER	PACKAGE	BRAND
HGTD10N40F1	TO-251AA	G10N40
HGTD10N50F1	TO-251AA	G10N50
HGTD10N40F1S	TO-252AA	G10N40
HGTD10N50F1S	TO-252AA	G10N50


NOTE: When ordering, use the entire part number. Add the suffix 9A to obtain the TO-252AA variant in the tape and reel, i.e., HGTD10N40F19A.

## Packages

HGTD10N40F1, HGTD10N50F1  
JEDEC TO-251AA




HGTD10N40F1S, HGTD10N50F1S  
JEDEC TO-252AA



## Terminal Diagram

### N-CHANNEL ENHANCEMENT MODE



## Absolute Maximum Ratings $T_C = +25^\circ C$ , Unless Otherwise Specified

	HGTD10N40F1 HGTD10N40F1S	HGTD10N50F1 HGTD10N50F1S	UNITS
Collector-Emitter Voltage	400	500	V
Collector-Gate Voltage $R_{GE} = 1M\Omega$	400	500	V
Gate-Emitter Voltage	$\pm 20$	$\pm 20$	V
Collector Current Continuous at $T_C = +25^\circ C$	12	12	A
at $T_C = +90^\circ C$	10	10	A
Power Dissipation Total at $T_C = +25^\circ C$	75	75	W
Power Dissipation Derating $T_C > +25^\circ C$	0.6	0.6	W/ $^\circ C$
Operating and Storage Junction Temperature Range	-55 to +150	-55 to +150	$^\circ C$

### INTERSIL CORPORATION IGBT PRODUCT IS COVERED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS:



4,364,073	4,417,385	4,430,792	4,443,931	4,466,176	4,516,143	4,532,534	4,567,641
4,587,713	4,598,461	4,605,948	4,618,872	4,620,211	4,631,564	4,639,754	4,639,762
4,641,162	4,644,637	4,682,195	4,684,413	4,694,313	4,717,679	4,743,952	4,783,690
4,794,432	4,801,986	4,803,533	4,809,045	4,809,047	4,810,665	4,823,176	4,837,606
4,860,080	4,883,767	4,888,627	4,890,143	4,901,127	4,904,609	4,933,740	4,963,951
4,969,027							

# Specifications HGTD10N40F1, HGTD10N40F1S, HGTD10N50F1, HGTD10N50F1S

## Electrical Specifications $T_C = +25^\circ\text{C}$ , Unless Otherwise Specified

PARAMETERS	SYMBOL	TEST CONDITIONS	LIMITS				UNITS	
			HGTD10N40F1 HGTD10N40F1S		HGTD10N50F1 HGTD10N50F1S			
			MIN	MAX	MIN	MAX		
Collector-Emitter Breakdown Voltage	$BV_{CES}$	$I_C = 250\mu\text{A}, V_{GE} = 0\text{V}$	400	-	500	-	V	
Gate Threshold Voltage	$V_{GE(TH)}$	$V_{GE} = V_{CE}, I_C = 1\text{mA}$	2.0	4.5	2.0	4.5	V	
Zero Gate Voltage Collector Current	$I_{CES}$	$T_J = +150^\circ\text{C}, V_{CE} = 400\text{V}$	-	250	-	-	$\mu\text{A}$	
		$T_J = +150^\circ\text{C}, V_{CE} = 500\text{V}$	-	-	-	250	$\mu\text{A}$	
Gate-Emitter Leakage Current	$I_{GES}$	$V_{GE} = \pm 20\text{V}, V_{CE} = 0\text{V}$	-	100	-	100	nA	
Collector-Emitter On-Voltage	$V_{CE(ON)}$	$T_J = +150^\circ\text{C}, I_C = 5\text{A}, V_{GE} = 10\text{V}$	-	2.5	-	2.5	V	
		$T_J = +150^\circ\text{C}, I_C = 5\text{A}, V_{GE} = 15\text{V}$	-	2.2	-	2.2	V	
		$T_J = +25^\circ\text{C}, I_C = 5\text{A}, V_{GE} = 10\text{V}$	-	2.5	-	2.5	V	
		$T_J = +25^\circ\text{C}, I_C = 5\text{A}, V_{GE} = 15\text{V}$	-	2.2	-	2.2	V	
Gate-Emitter Plateau Voltage	$V_{GEP}$	$I_C = 5\text{A}, V_{CE} = 10\text{V}$	5.3 (Typ)				V	
On-State Gate Charge	$Q_{G(ON)}$	$I_C = 5\text{A}, V_{CE} = 10\text{V}$	13.4 (Typ)				nC	
Turn-On Delay Time	$t_{D(ON)}$	Resistive Load, $I_C = 5\text{A}, V_{CE} = 400\text{V}, R_L = 80\Omega, T_J = +150^\circ\text{C}, V_{GE} = 10\text{V}, R_G = 25\Omega$	45 (Typ)				ns	
Rise Time	$t_{RI}$		35 (Typ)				ns	
Turn-Off Delay Time	$t_{D(OFF)}$		130 (Typ)				ns	
Fall Time	$t_{FI}$		1400 (Typ)				ns	
Turn-Off Energy Loss Per Cycle (Off Switching Dissipation = $W_{OFF} \times$ Frequency)	$W_{OFF}$		0.64 (Typ)				mJ	
Turn-Off Delay Time	$t_{D(OFF)}$		Inductive Load (See Figure 11), $I_C = 5\text{A}, V_{CE(CLIP)} = 400\text{V}, R_L = 80\Omega, L = 50\mu\text{H}, T_J = +150^\circ\text{C}, V_{GE} = 10\text{V}, R_G = 25\Omega$	-	375	-	375	ns
Fall Time	$t_{FI}$			-	1200	-	1200	ns
Turn-Off Energy Loss Per Cycle (Off Switching Dissipation = $W_{OFF} \times$ Frequency)	$W_{OFF}$	-		1.2	-	1.2	mJ	
Thermal Resistance Junction-to-Case (IGBT)	$R_{\theta JC}$		-	1.67	-	1.67	$^\circ\text{C/W}$	

## Typical Performance Curves



Typical Performance Curves (Continued)




FIGURE 3. SATURATION VOLTAGE vs COLLECTOR-EMITTER CURRENT (TYPICAL)




FIGURE 4. DC COLLECTOR CURRENT vs CASE TEMPERATURE




FIGURE 5. CAPACITANCE vs COLLECTOR-TO-EMITTER VOLTAGE (TYPICAL)




FIGURE 6. TURN-OFF DELAY vs COLLECTOR-TO-EMITTER CURRENT (TYPICAL)




FIGURE 7. FALL TIME vs COLLECTOR-TO-EMITTER CURRENT (TYPICAL)





FIGURE 8. TURN-OFF SWITCHING LOSS vs COLLECTOR-EMITTER CURRENT (TYPICAL)

Typical Performance Curves (Continued)



NOTE:  
 $P_D$  = ALLOWABLE DISSIPATION  $P_C$  = CONDUCTION DISSIPATION

FIGURE 9. MAXIMUM OPERATING FREQUENCY vs COLLECTOR CURRENT AND VOLTAGE (TYPICAL)




FIGURE 10. NORMALIZED SWITCHING WAVEFORMS AT CONSTANT GATE CURRENT

Test Circuit




FIGURE 11. INDUCTIVE SWITCHING TEST CIRCUIT

All Intersil semiconductor products are manufactured, assembled and tested under ISO9000 quality systems certification.

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see web site <http://www.intersil.com>

Sales Office Headquarters

**NORTH AMERICA**  
 Intersil Corporation  
 P. O. Box 883, Mail Stop 53-204  
 Melbourne, FL 32902  
 TEL: (407) 724-7000  
 FAX: (407) 724-7240

**EUROPE**  
 Intersil SA  
 Mercure Center  
 100, Rue de la Fusee  
 1130 Brussels, Belgium  
 TEL: (32) 2.724.2111  
 FAX: (32) 2.724.22.05

**ASIA**  
 Intersil (Taiwan) Ltd.  
 Taiwan Limited  
 7F-6, No. 101 Fu Hsing North Road  
 Taipei, Taiwan  
 Republic of China  
 TEL: (886) 2 2716 9310  
 FAX: (886) 2 2715 3029