



GBC846

NPN EPITAXIAL PLANAR TRANSISTOR

Description

The GBC846 is designed for switching and AF amplifier application, suitable for automatic insertion in thick and thin-film circuits.

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0 C	10 C

Absolute Maximum Ratings at Ta = 25

Parameter	Symbol	Ratings	Unit
Junction Temperature	Tj	+150	
Storage Temperature	Tstg	-55 ~ +150	
Collector to Base Voltage	VCBO	80	V
Collector to Emitter Voltage	VCEO	65	V
Emitter to Base Voltage	VEBO	6	V
Collector Current	IC	100	mA
Total Power Dissipation	PD	250	mW


Characteristics at Ta = 25

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	80	-	-	V	IC=100uA
BVCEO	65	-	-	V	IC=1mA
BVEBO	6	-	-	V	IE=10uA
ICBO	-	-	15	nA	VCB=30V
VCE(sat)1	-	90	250	mV	IC=10mA, IB=0.5mA
VCE(sat)2	-	200	600	mV	IC=100mA, IB=5mA
VBE(sat)1	-	700	-	mV	IC=10mA, IB=0.5mA
VBE(sat)2	-	900	-	mV	IC=100mA, IB=5mA
VBE(on)1	580	-	700	mV	VCE=5V, IC=2mA
VBE(on)2	-	-	770	mV	VCE=5V, IC=10mA
hFE	110	-	800		VCE=5V, IC=2mA
fT	-	300	-	MHz	VCE=5V, IC=10mA
Cob	-	3.5	6	pF	VCB=10V, f=1MHz, IE=0A

Classification Of hFE

Rank	A	B	C
hFE	110-220	200-450	420-800

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165