



H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Features

- High isolation 5000 VRMS
- DC input with Schmitt Trigger output
- 1MHz(NRZ) data rate
- Temperature range - 55 °C to 100 °C


Applications

- Line Receiver
- Logic to Logic Isolator
- Microprocessor system interface
- AC to TTL conversion

Description


The H11L1, H11L2 and H11L3 series consist of a Schmitt Trigger optically coupled to a gallium arsenide Infrared-emitting diode in a 6-lead DIP package with different lead forming options.

Package Outline



Note: Different lead forming options available. See package dimension.

Schematic





H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
V _{ISO}	Isolation voltage	5000	V _{RMS}	
T _{OPR}	Operating temperature	-55 ~ +100	°C	
T _{STG}	Storage temperature	-55 ~ +150	°C	
T _{SOL}	Soldering temperature	260	°C	
Emitter				
I _F	Forward current	60	mA	
I _{F(TRANS)}	Peak transient current (≤1μs P.W,300pps)	1	A	
V _R	Reverse voltage	6	V	
P _D	Power dissipation	100	mW	
Detector				
P _D	Power dissipation	150	mW	
V _o	Output Voltage	0 to 16	V	
V _{CC}	Supply Voltage	3 to 16	V	
I _o	Output Current	50	mA	



H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Emitter Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V_F	Forward voltage	$I_F = 10\text{mA}$		1.24	1.4	V	
I_R	Reverse Current	$V_R = 6\text{V}$	-	-	5	μA	
C_{IN}	Input Capacitance	$f = 1\text{MHz}$	-	45	-	pF	

Detector Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V_{CC}	Supply Voltage		3	-	15	V	
I_{CCH}	Logic High Supply Current	$I_F = 0\text{mA}$, $V_{CC} = 5\text{V}$		1.5	5	mA	
I_{OH}	Logic High Output Current	$I_F = 0\text{mA}$, $V_{CC} = V_O = 15\text{V}$			100	μA	

Transfer Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I_{CCL}	Logic Low Supply Current	$I_F = 10\text{mA}$, $V_{CC} = 5\text{V}$		1.5	5	mA	
$I_{F(ON)}$	Input Threshold Current	H11L1	$V_{CC} = 5\text{V}$, $R_L = 270\ \Omega$		1.6	mA	
		H11L2		10	mA		
		H11L3		5	mA		
$I_{F(OFF)}$	Off Threshold Current	$V_{CC} = 5\text{V}$, $R_L = 270\ \Omega$	0.3	1		mA	
$I_{F(ON)}/I_{F(OFF)}$	Hysteresis Ratio		0.5		0.9		
V_{OL}	Logic Low Output Voltage	$I_F = I_{F(ON)} \text{ Max}$, $V_{CC} = 5\text{V}$, $R_L = 270\ \Omega$			0.4	V	
R_{IO}	Isolation Resistance	$V_{IO} = 500\text{V}_{DC}$	1×10^{11}			Ω	
C_{IO}	Isolation Capacitance	$f = 1\text{MHz}$		0.25		pF	

Switching Characteristics







Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
t_{ON}	Turn On Time	$I_F = I_{F(ON)}$, $V_{CC} = 5\text{V}$, $R_L = 270\ \Omega$	-	-	3.8	μs	
t_r	Rise Time		-	0.1	-		
t_{OFF}	Turn Off Time		-	-	3.8		
t_f	Fall Time		-	0.1	-		
	Data Rate		-	1	-	MHz	



H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Typical Characteristic Curves






H11L1, H11L2, H11L3


Schmitt Trigger Output 6-Pin Optocoupler

Package Dimension *Dimensions in mm unless otherwise stated*

Standard DIP – Through Hole



Wide Lead Forming – Through Hole (M Type)







H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Surface Mount Forming (S Type)



Surface Mount Forming (Low Profile) (SL Type)







H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Recommended Solder Mask *Dimensions in mm unless otherwise stated*



Marking Information



Note:

- CT : Denotes "CT Micro"
- H11L1 : Part Number
- Y : Fiscal Year
- WW : Work Week
- K : Manufacturing Code



H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Ordering Information

H11LX(Y)(Z)-G

X = Part No. (X=1,2,3)

Y = Lead form option (S, SL, M or none)

Z = Tape and reel option (T1, T2 or none)

G= Material option (G: Green, None: Non-green)

Option	Description	Quantity
None	Standard 6 Pin Dip	65Units/Tube
M	Gullwing (400mil) Lead Forming	65Units/Tube
S(T1)	Surface Mount Lead Forming – With Option 1 Taping	1000 Units/Reel
S(T2)	Surface Mount Lead Forming – With Option 2 Taping	1000 Units/Reel
SL(T1)	Surface Mount (Low Profile) Lead Forming– With Option 1 Taping	1000 Units/Reel
SL(T2)	Surface Mount (Low Profile) Lead Forming – With Option 2 Taping	1000 Units/Reel




H11L1, H11L2, H11L3


Schmitt Trigger Output 6-Pin Optocoupler

Carrier Tape Specifications *Dimensions in mm unless otherwise stated*

Option S(T1) & SL(T1)



Option S(T2) & SL(T2)






H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T_{smin})	150 °C
Temperature Max. (T_{smax})	200 °C
Time (t_s) from (T_{smin} to T_{smax})	60-120 seconds
Ramp-up Rate (t_L to t_P)	3°C/second max.
Liquidous Temperature (T_L)	217 °C
Time (t_L) Maintained Above (T_L)	60 – 150 seconds
Peak Body Package Temperature	260 °C +0 °C / -5 °C
Time (t_P) within 5 °C of 260 °C	30 seconds
Ramp-down Rate (T_P to T_L)	6°C/second max
Time 25 °C to Peak Temperature	8 minutes max.



H11L1, H11L2, H11L3

Schmitt Trigger Output 6-Pin Optocoupler

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

DISCOLORATION MIGHT OCCUR ON THE PACKAGE SURFACE AFTER SOLDERING, REFLOW OR LONG TERM USE. THIS DOES NOT IMPACT THE PRODUCT PERFORMANCE NOR THE PRODUCT RELIABILITY.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*