

### GLASS PASSIVATED RECTIFIER

VOLTAGE RANGE: 50 — 1000 V

CURRENT: 1.0 A


#### FEATURES

- ◇ Low cost
- ◇ Glass passivated junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

#### MECHANICAL DATA

- ◇ Case: JEDEC DO-41, molded plastic
- ◇ Terminals: Axial lead, solderable per ML-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.34 grams
- ◇ Mounting position: Any

#### DO - 41



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		HER 101G	HER 102G	HER 103G	HER 104G	HER 105G	HER 106G	HER 107G	HER 108G	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	50	100	200	300	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	210	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	300	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ C$	$I_{F(AV)}$	1.0								A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	$I_{FSM}$	30.0								A
Maximum instantaneous forward voltage @1.0 A	$V_F$	1.0		1.3		1.7			V	
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	$I_R$	5.0 100.0								$\mu A$
Maximum reverse capacitance (Note1)	$t_{rr}$	50					75			ns
Typical junction capacitance (Note2)	$C_J$	20					15			pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	60.0								$^\circ C/W$
Operating junction temperature range	$T_J$	-55----+175								$^\circ C$
Storage temperature range	$T_{STG}$	-55----+175								$^\circ C$


NOTE: 1. Measured with  $I_F=0.5A$ ,  $I_R=1A$ ,  $I_{rr}=0.25A$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

www.galaxycn.com


**FIG.1 –FORWARD DERATING CURVE**




**FIG.2 –TYPICAL REVERSE CHARACTERISTICS**



**FIG.3 –TYPICAL FORWARD CHARACTERISTICS**



**FIG.4—PEAK FORWARD SURGE CURRENT**



**FIG.5—TYPICAL JUNCTION CAPACITANCE**

