

IL1084T2
CHIP LOW DROPOUT POSITIVE REGULATOR 5A
Features

- ◆ Output Current - 5A
- ◆ Maximum Input Voltage – 12V
- ◆ Adjustable Output Voltage or Fixed
1.5V, 1.8V, 2.5V, 2.85V, 3.3V, 3.6V, 5V
- ◆ Current Limiting and Thermal Protection
- ◆ Standard 3-Pin Power Packages


Applications

- ◆ Post Regulator for Switching DC/DC Converter
- ◆ High Efficiency Linear Regulators
- ◆ Battery Charger

Physical Characteristics:

- Chip size.....1.9 x 2.2 mm
- ◆ Wafer Diameter 100 ± 0.5 mm
- ◆ Wafer thickness 280 ± 20 μm
- ◆ Scribe width 100 μm
- ◆ Metallization bottom... Ti-Ni-Ag
Ti-Ni – 0.5-0.7μm
Ag – 0.6-0.1μm

- ◆ Passivation PSG


Pad Location Coordinates

N	Pad names	Pad size	X(μm)	Y(μm)
1	NC	130x130	251	88
2	INPUT	150x340	1961	780
3	OUTPUT	600x150	1251	875
4	INPUT	150x340	991	780
5	GND	130x130	88	311

Absolute Maximum Ratings (Note 1)

Power Dissipation (Note 2) Internally Limited
 Junction Temperature (Note 3) 150°C
 Storage Temperature Range -65°C to 150°C
 Storage Temperature Range -65°C to 150°C

Operating Ratings

Junction Temperature Range (Note 3) -10°C to 125°C

ELECTRICAL CHARACTERISTICS

Typicals and limits appearing in normal type apply for T_j= +25°C.

Limits appearing in **Boldface** type apply over the entire junction temperature range for operation.

Symbol	Parameter	Conditions	Min (Note 5)	Typ (Note 4)	Max (Note 5)	Units
V _{OUT}	Output Voltage (Note 6) IL1084-Adj BT2	I _{OUT} =10mA, V _{IN} =4.25V	1.237	1.250	1.263	V
		0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 2.75V ≤ V _{IN} ≤ 10V	1.232	1.250	1.268	
			1.225	1.250	1.275	
	IL1084-1.5 BT2	I _{OUT} =10mA, V _{IN} =4.5V	1.485	1.500	1.515	
		0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 3.0V ≤ V _{IN} ≤ 10V	1.478	1.500	1.522	
			1.470	1.500	1.530	
	IL1084-1.8 BT2	I _{OUT} =10mA, V _{IN} =4.8V	1.782	1.800	1.818	
		0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 3.3V ≤ V _{IN} ≤ 10V	1.773	1.800	1.827	
			1.764	1.800	1.836	
IL1084-2.5 BT2	I _{OUT} =10mA, V _{IN} =5.5V	2.475	2.500	2.525		
	0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 4.0V ≤ V _{IN} ≤ 10V	2.463	2.500	2.537		
		2.450	2.500	2.550		
IL1084-2.85 BT2	I _{OUT} =10mA, V _{IN} =5.85V	2.820	2.850	2.880		
	0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 4.35V ≤ V _{IN} ≤ 10V	2.805	2.850	2.895		
		2.790	2.850	2.910		
IL1084-3.3 BT2	I _{OUT} =10mA, V _{IN} =6.3V	3.270	3.300	3.330		
	0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 4.8V ≤ V _{IN} ≤ 10V	3.250	3.300	3.350		
		3.235	3.300	3.365		
IL1084-3.6 BT2	I _{OUT} =10mA, V _{IN} =6.6V	3.564	3.600	3.636		
	0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 5.1V ≤ V _{IN} ≤ 10V	3.546	3.600	3.654		
		3.528	3.600	3.672		
IL1084-5.0 BT2	I _{OUT} =10mA, V _{IN} =8.0V	4.950	5.000	5.050		
	0 ≤ I _{OUT} ≤ I _{FULL LOAD} , 6.5V ≤ V _{IN} ≤ 10V	4.925	5.000	5.075		
		4.900	5.000	5.100		

IL1084 BT2	CHIP LOW DROPOUT POSITIVE REGULATOR 5A
-------------------	---

ELECTRICAL CHARACTERISTICS

Typicals and limits appearing in normal type apply for T_j= +25°C.

Limits appearing in **Boldface** type apply over the entire junction temperature range for operation.

ΔV_{OUT}	Line Regulation (Note 7)		-	-	0.3	%
	IL1084-Adj BT2	$I_{OUT}=10mA, 2.75V \leq V_{IN} \leq 10V$	-	-	0.4	
	IL1084-1.5 BT2	$I_{OUT}=10mA, 3.0V \leq V_{IN} \leq 10V$	-	-	6	mV
	IL1084-1.8 BT2	$I_{OUT}=10mA, 3.3V \leq V_{IN} \leq 10V$	-	-	6	
	IL1084-2.5 BT2	$I_{OUT}=10mA, 4.0V \leq V_{IN} \leq 10V$	-	-	6	
	IL1084-2.85 BT2	$I_{OUT}=10mA, 4.35V \leq V_{IN} \leq 10V$	-	-	6	
	IL1084-3.3 BT2	$I_{OUT}=10mA, 4.8V \leq V_{IN} \leq 10V$	-	-	6	
	IL1084-3.6 BT2	$I_{OUT}=10mA, 5.1V \leq V_{IN} \leq 10V$	-	-	6	
	IL1084-5.0 BT2	$I_{OUT}=10mA, 6.5V \leq V_{IN} \leq 10V$	-	-	6	
ΔV_{OUT}	Load Regulation (Note 7)		-	-	0.3	%
	IL1084-Adj BT2	$V_{IN}=4.25V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	0.4	
	IL1084-1.5 BT2	$V_{IN}=5.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	12	mV
	IL1084-1.8 BT2	$V_{IN}=5.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	20	
	IL1084-2.5 BT2	$V_{IN}=5.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	15	
	IL1084-2.85 BT2	$V_{IN}=5.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	20	
ΔV	IL1084-3.3 BT2	$V_{IN}=5.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	15	
	IL1084-3.6 BT2	$V_{IN}=5.3V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	25	
ΔV	IL1084-5.0 BT2	$V_{IN}=8.0V, 0 \leq I_{OUT} \leq I_{FULL\ LOAD}$	-	-	20	
	Dropout Voltage (Note 8)	$\Delta V_{REF}=1\%, I_{OUT}=5A$	-	-	1.5	V
$I_{O(MIN)}$	Minimum Load Current	$V_{IN}=10V$	-	-	10	mA
I_{LIMIT}	Current Limit	$V_{IN}=6.25V$	5.5	-	-	A
I_{ADJ}	Adjust Pin Current	$V_{IN}=2.75 \div 10V, I_{OUT}=10mA$	-	-	120	μA
ΔI_{ADJ}	Adjust Pin Current Change	$I_{OUT}=10mA \div 5A, V_{IN}=2.75 \div 10V$	-	-	5	μA
RR	Ripple Rejection	$f_{RIPPLE} = 120Hz, C_{OUT}=25\mu F$ Tantalum, $I_{out}=5A; V_{IN}=4.25V$	60	-	-	dB
S	Temperature Stability		-	0.5	-	%

NOTES 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Rating indicate conditions for which the device is intended to be functional, but specific performance is not guaranteed. For guaranteed specifications and the test conditions, see the Electrical Characteristics.

NOTES 2: Power Dissipation is kept in a safe range by current limiting circuitry. Refer to Overload Recovery in Application Notes.

NOTES 3: The maximum power dissipation is a function of T_{j(MAX)}, Θ_{jA} and T_A. The maximum allowable power dissipation at any ambient temperature is $P_D = (T_{j(MAX)} - T_A) \Theta_{jA}$.

NOTES 4: Typical Values represent the most likely parametric norm

NOTES 5: All limits are guaranteed by testing or statistical analysis

NOTES 6: I_{FULL LOAD} is defined in the current limit curves. The I_{FULL LOAD} curve defines the current limit as a function of input-to-output voltage.

NOTES 7: Load and Line regulation are measured at constant junction temperature, and are guaranteed up to the maximum power dissipation of 30W. Power dissipation is determined by the input/output differential and the output current. Guaranteed maximum power dissipation will not be available over the full input/output range.

NOTES 8: Dropout voltage is specified over the full output current range of the device.