IS61SF25632T/D IS61LF25632T/D
IS61SF25636T/D IS61LF25636T/D
IS61SF51218T/D IS61LF51218T/D

ISSI®

256K x 32, 256K x 36, 512K x 18 SYNCHRONOUS FLOW-THROUGH STATIC RAM

PRELIMINARY INFORMATION
NOVEMBER 2000

FEATURES

- Internal self-timed write cycle
- Individual Byte Write Control and Global Write
- Clock controlled, registered address, data and control
- Pentium™ or linear burst sequence control using MODE input
- Three chip enable option for simple depth expansion and address pipelining
- Common data inputs and data outputs
- JEDEC 100-Pin TQFP and 119-pin PBGA package
- Single +3.3V, +10%, –5% power supply
- Power-down snooze mode
- 3.3V I/O for SF
- 2.5V I/O for LF
- Snooze MODE for reduced-power standby
- T version (three chip selects)
- D version (two chip selects)

DESCRIPTION

The *ISSI* IS61SF25632, IS61SF25636, IS61SF51218, IS61LF25632, IS61LF25636, and IS61LF51218 are high-speed, low-power synchronous static RAMs designed to provide a burstable, high-performance, secondary cache for the Pentium™, 680X0™, and PowerPC™ microprocessors. The IS61SF25632 and IS61LF25632 are organized as 262,144 words by 32 bits and the IS61SF25636 and IS61LF25636 are organized as 262,144 words by 36 bits. The IS61SF51218 and IS61LF51218 are organized as 524,288 words by 18 bits. Fabricated with *ISSI*'s advanced CMOS technology, the device integrates a 2-bit burst counter, high-speed SRAM core, and high-drive capability outputs into a single monolithic circuit. All synchronous inputs pass through registers that are controlled by a positive-edge-triggered single clock input.

Write cycles are internally self-timed and are initiated by the rising edge of the clock input. Write cycles can be from one to four bytes wide as controlled by the write control inputs.

Separate byte enables allow individual bytes to be written. Byte write operation is performed by using byte write enable ($\overline{BWE}$).input combined with one or more individual byte write signals ($\overline{BWx}$). In addition, Global Write ($\overline{GW}$) is available for writing all bytes at one time, regardless of the byte write controls.

Bursts can be initiated with either $\overline{ADSP}$ (Address Status Processor) or $\overline{ADSC}$ (Address Status Cache Controller) input pins. Subsequent burst addresses can be generated internally and controlled by the $\overline{ADV}$ (burst address advance) input pin.

The mode pin is used to select the burst sequence order, Linear burst is achieved when this pin is tied LOW. Interleave burst is achieved when this pin is tied HIGH or left floating.

FAST ACCESS TIME

Symbol	Parameter	-8*	-8.5	-9	-10	Units
t_{KQ}	Clock Access Time	8	8.5	9	10	ns
t_{KC}	Cycle Time	10	11	15	15	ns
	Frequency	100	90	66	66	MHz

*This speed available only in SF version

This document contains PRELIMINARY INFORMATION data. ISSI reserves the right to make changes to its products at any time without notice in order to improve design and supply the best possible product. We assume no responsibility for any errors which may appear in this publication. © Copyright 2001, Integrated Silicon Solution, Inc.

BLOCK DIAGRAM



PIN CONFIGURATION

119-pin PBGA (Top View)

	1	2	3	4	5	6	7
A	VCCQ	A6	A4	$\overline{ADSP}$	A8	A16	VCCQ
B	NC	CE2	A3	$\overline{ADSC}$	A9	A17	NC
C	NC	A7	A2	VCC	A12	A15	NC
D	DQc1	NC	GND	NC	GND	NC	DQb8
E	DQc2	DQc3	GND	$\overline{CE}$	GND	DQb6	DQb7
F	VCCQ	DQc4	GND	$\overline{OE}$	GND	DQb5	VCCQ
G	DQc5	DQc6	$\overline{BWc}$	ADV	$\overline{BWb}$	DQb4	DQb3
H	DQc7	DQc8	GND	$\overline{GW}$	GND	DQb2	Dqb1
J	VCCQ	VCC	NC	VCC	NC	VCC	VCCQ
K	DQd1	DQd2	GND	CLK	GND	DQa7	DQa8
L	DQd4	DQd3	$\overline{BWd}$	NC	$\overline{BWa}$	DQa5	DQa6
M	VCCQ	DQd5	GND	$\overline{BWE}$	GND	DQa4	VCCQ
N	DQd6	DQd7	GND	A1	GND	DQa3	DQa2
P	DQd8	NC	GND	A0	GND	NC	DQa1
R	NC	A5	MODE	VCC	GND	A13	NC
T	NC	NC	A10	A11	A14	NC	ZZ
U	VCCQ	NC	NC	NC	NC	NC	VCCQ

100-Pin TQFP (D Version)



256K x 32

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A17	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWd}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable

$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, CE2	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQd	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: +3.3V or 2.5V
ZZ	Snooze Enable

PIN CONFIGURATION

100-Pin TQFP (T Version)



256K x 32

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A17	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWd}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable

$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, $\overline{CE2}$, CE2	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQd	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: +3.3V or 2.5V
ZZ	Snooze Enable

PIN CONFIGURATION

119-pin PBGA (Top View)

	1	2	3	4	5	6	7
A	VCCQ	A6	A4	$\overline{ADSP}$	A8	A16	VCCQ
B	NC	CE2	A3	$\overline{ADSC}$	A9	A17	NC
C	NC	A7	A2	VCC	A12	A15	NC
D	DQc1	DQPc	GND	NC	GND	DQPb	DQb8
E	DQc2	DQc3	GND	$\overline{CE}$	GND	DQb6	DQb7
F	VCCQ	DQc4	GND	$\overline{OE}$	GND	DQb5	VCCQ
G	DQc5	DQc6	$\overline{BWc}$	ADV	$\overline{BWb}$	DQb4	DQb3
H	DQc7	DQc8	GND	$\overline{GW}$	GND	DQb2	Dqb1
J	VCCQ	VCC	NC	VCC	NC	VCC	VCCQ
K	DQd1	DQd2	GND	CLK	GND	DQa7	DQa8
L	DQd4	DQd3	$\overline{BWd}$	NC	$\overline{BWa}$	DQa5	DQa6
M	VCCQ	DQd5	GND	$\overline{BWE}$	GND	DQa4	VCCQ
N	DQd6	DQd7	GND	A1	GND	DQa3	DQa2
P	DQd8	DQPd	GND	A0	GND	DQPa	DQa1
R	NC	A5	MODE	VCC	GND	A13	NC
T	NC	NC	A10	A11	A14	NC	ZZ
U	VCCQ	NC	NC	NC	NC	NC	VCCQ

100-Pin TQFP (D Version)



256K x 36

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A17	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWd}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable
$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, CE2	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQd	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: +3.3V or 2.5V
ZZ	Snooze Enable
DQPa-DQPd	Parity Data I/O

PIN CONFIGURATION

100-Pin TQFP (T Version)



256K x 36

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A17	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWd}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable

$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, $\overline{CE2}$, CE2	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQd	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: +3.3V or 2.5V
ZZ	Snooze Enable
DQPa-DQPd	Parity Data I/O

PIN CONFIGURATION

119-pin PBGA (Top View)

	1	2	3	4	5	6	7
A	VCCQ	A6	A4	$\overline{ADSP}$	A8	A16	VCCQ
B	NC	CE2	A3	$\overline{ADSC}$	A9	$\overline{CE2}$	NC
C	NC	A7	A2	VCC	A12	A15	NC
D	DQb1	NC	GND	NC	GND	DQPa	NC
E	NC	DQb2	GND	$\overline{CE}$	GND	NC	DQa8
F	VCCQ	NC	GND	$\overline{OE}$	GND	DQa7	VCCQ
G	NC	DQb3	$\overline{BWb}$	$\overline{ADV}$	GND	NC	DQa6
H	DQb4	NC	GND	$\overline{GW}$	GND	DQa5	NC
J	VCCQ	VCC	NC	VCC	NC	VCC	VCCQ
K	NC	DQb5	GND	CLK	GND	NC	DQa4
L	DQb6	NC	GND	NC	$\overline{BWa}$	DQa3	NC
M	VCCQ	DQb7	GND	$\overline{BWE}$	GND	NC	VCCQ
N	DQb8	NC	GND	A1	GND	DQa2	NC
P	NC	DQPb	GND	A0	GND	NC	DQa1
R	NC	A5	MODE	VCC	GND	A13	NC
T	NC	A11	A10	NC	A14	A17	ZZ
U	VCCQ	NC	NC	NC	NC	NC	VCCQ

100-Pin TQFP (D Version)



512K x 18

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A18	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWb}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable

$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, CE2	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQb	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: 3.3V or 2.5V
ZZ	Snooze Enable
DQPa-DQPb	Parity Data I/O DQPa is parity for DQa1-a8; DQPb is parity for DQb1-b8

PIN CONFIGURATION

100-Pin TQFP (T Version)



512K x 18

PIN DESCRIPTIONS

A0, A1	Synchronous Address Inputs. These pins must tied to the two LSBs of the address bus.
A2-A18	Synchronous Address Inputs
CLK	Synchronous Clock
$\overline{ADSP}$	Synchronous Processor Address Status
$\overline{ADSC}$	Synchronous Controller Address Status
$\overline{ADV}$	Synchronous Burst Address Advance
$\overline{BWa}$-$\overline{BWb}$	Synchronous Byte Write Enable
$\overline{BWE}$	Synchronous Byte Write Enable

$\overline{GW}$	Synchronous Global Write Enable
$\overline{CE}$, CE2, $\overline{CE2}$	Synchronous Chip Enable
$\overline{OE}$	Output Enable
DQa-DQb	Synchronous Data Input/Output
MODE	Burst Sequence Mode Selection
V_{CC}	+3.3V Power Supply
GND	Ground
V_{CCQ}	Isolated Output Buffer Supply: 3.3V or 2.5V
ZZ	Snooze Enable
DQPa-DQPb	Parity Data I/O DQPa is parity for DQa1-a8; DQPb is parity for DQb1-b8

TRUTH TABLE

Operation	Address Used	$\overline{CE}$	CE2	$\overline{CE2}$	$\overline{ADSP}$	$\overline{ADSC}$	$\overline{ADV}$	$\overline{WRITE}$	$\overline{OE}$	DQ
Deselected, Power-down	None	H	X	X	X	L	X	X	X	High-Z
Deselected, Power-down	None	L	X	H	L	X	X	X	X	High-Z
Deselected, Power-down	None	L	L	X	L	X	X	X	X	High-Z
Deselected, Power-down	None	L	X	H	H	L	X	X	X	High-Z
Deselected, Power-down	None	L	L	X	H	L	X	X	X	High-Z
Read Cycle, Begin Burst	External	L	H	L	L	X	X	X	X	Q
Read Cycle, Begin Burst	External	L	H	L	H	L	X	Read	X	Q
Write Cycle, Begin Burst	External	L	H	L	H	L	X	Write	X	D
Read Cycle, Continue Burst	Next	X	X	X	H	H	L	Read	L	Q
Read Cycle, Continue Burst	Next	X	X	X	H	H	L	Read	H	High-Z
Read Cycle, Continue Burst	Next	H	X	X	X	H	L	Read	L	Q
Read Cycle, Continue Burst	Next	H	X	X	X	H	L	Read	H	High-Z
Write Cycle, Continue Burst	Next	X	X	X	H	H	L	Write	X	D
Write Cycle, Continue Burst	Next	H	X	X	X	H	L	Write	X	D
Read Cycle, Suspend Burst	Current	X	X	X	H	H	H	Read	L	Q
Read Cycle, Suspend Burst	Current	X	X	X	H	H	H	Read	H	High-Z
Read Cycle, Suspend Burst	Current	H	X	X	X	H	H	Read	L	Q
Read Cycle, Suspend Burst	Current	H	X	X	X	H	H	Read	H	High-Z
Write Cycle, Suspend Burst	Current	X	X	X	H	H	H	Write	X	D
Write Cycle, Suspend Burst	Current	H	X	X	X	H	H	Write	X	D

PARTIAL TRUTH TABLE

Function	$\overline{GW}$	$\overline{BWE}$	$\overline{BWa}$	$\overline{BWb}$	$\overline{BWc}$	$\overline{BWd}$
Read	H	H	X	X	X	X
Read	H	L	H	H	H	H
Write Byte 1	H	L	L	H	H	H
Write All Bytes	H	L	L	L	L	L
Write All Bytes	L	X	X	X	X	X

INTERLEAVED BURST ADDRESS TABLE (MODE = V_{CCQ} or No Connect)

External Address A1 A0	1st Burst Address A1 A0	2nd Burst Address A1 A0	3rd Burst Address A1 A0
00	01	10	11
01	00	11	10
10	11	00	01
11	10	01	00

LINEAR BURST ADDRESS TABLE (MODE = GND_Q)



ABSOLUTE MAXIMUM RATINGS[1]

Symbol	Parameter	Value	Unit
T_{BIAS}	Temperature Under Bias	–40 to +85	°C
T_{STG}	Storage Temperature	–55 to +150	°C
P_D	Power Dissipation	1.6	W
I_{OUT}	Output Current (per I/O)	100	mA
V_{IN}, V_{OUT}	Voltage Relative to GND for I/O Pins	–0.5 to V_{CCQ} + 0.3	V
V_{IN}	Voltage Relative to GND for for Address and Control Inputs	–0.5 to V_{CC} + 0.5	V
V_{CC}	Voltage on Vcc Supply Relatiive to GND	–0.5 to 4.6	V

Notes:

1. Stress greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
2. This device contains circuity to protect the inputs against damage due to high static voltages or electric fields; however, precautions may be taken to avoid application of any voltage higher than maximum rated voltages to this high-impedance circuit.
3. This device contains circuitry that will ensure the output devices are in High-Z at power up.

OPERATING RANGE

Range	Ambient Temperature	Vcc	VccQ
Commercial	0°C to +70°C	3.3V, +10%, –5%	2.375–3.6V
Industrial	–40°C to +85°C	3.3V, +10%, –5%	2.375–3.6V

DC ELECTRICAL CHARACTERISTICS(1) (Over Operating Range)

Symbol	Parameter	Test Conditions		Min.	Max.	Unit
V_{OH}	Output HIGH Voltage	I_{OH} = –2.0 mA, V_{CCQ} = 2.5V		1.7	—	V
		I_{OH} = –4.0 mA, V_{CCQ} = 3.3V		2.4	—	V
V_{OL}	Output LOW Voltage	I_{OL} = 2.0 mA, V_{CCQ} = 2.5V		—	0.7	V
		I_{OL} = 8.0 mA, V_{CCQ} = 3.3V		—	0.4	V
V_{IH}	Input HIGH Voltage	V_{CCQ} = 2.5V		1.7	V_{CCQ} + 0.3	V
		V_{CCQ} = 3.3V		2.0	V_{CCQ} + 0.3	V
V_{IL}	Input LOW Voltage	V_{CCQ} = 2.5V		–0.3	0.7	V
		V_{CCQ} = 3.3V		–0.3	0.8	V
I_{LI}	Input Leakage Current	GND ≤ V_{IN} ≤ V_{CCQ}(2)	Com.	–2	2	µA
			Ind.	–5	5	
I_{LO}	Output Leakage Current	GND ≤ V_{OUT} ≤ V_{CCQ}, $\overline{OE}$ = V_{IH}	Com.	–2	2	µA
			Ind.	–5	5	

POWER SUPPLY CHARACTERISTICS (Over Operating Range)

Symbol	Parameter	Test Conditions		-8* Max.	-8.5 Max.	-9 Max.	-10 Max.	Unit
I_{CC}	AC Operating Supply Current	Device Selected, All Inputs = V_{IL} or V_{IH} $\overline{OE}$ = V_{IH}, Vcc = Max. Cycle Time ≥ t_{KC} min.	Com.	400	370	350	300	mA
			Ind.	—	400	380	330	mA
I_{SB}	Standby Current	Device Deselected, Vcc = Max., All Inputs = V_{IH} or V_{IL} CLK Cycle Time ≥ t_{KC} min.	Com.	110	105	90	80	mA
			Ind.	—	110	95	85	mA

*This speed available only in SF version

Notes:
1. The MODE pin has an internal pullup. This pin may be a No Connect, tied to GND, or tied to Vcc.
2. The MODE pin should be tied to Vcc or GND. It exhibits ±10 µA maximum leakage current when tied to - GND + 0.2V or ≥ Vcc – 0.2V.

CAPACITANCE[1,2]

Symbol	Parameter	Conditions	Max.	Unit
C_{IN}	Input Capacitance	V_{IN} = 0V	6	pF
C_{OUT}	Input/Output Capacitance	V_{OUT} = 0V	8	pF

Notes:
1. Tested initially and after any design or process changes that may affect these parameters.
2. Test conditions: T_A = 25°C, f = 1 MHz, Vcc = 3.3V.

AC TEST CONDITIONS

Parameter	Unit
Input Pulse Level	0V to 3.0V
Input Rise and Fall Times	1.5 ns
Input and Output Timing and Reference Level	1.5V for 3.3V I/O V_{CCQ}/2 for 2.5V I/O
Output Load	See Figures 1 and 2

AC TEST LOADS



Figure 1



Figure 2

READ/WRITE CYCLE SWITCHING CHARACTERISTICS (Over Operating Range)

Symbol	Parameter	-8*		-8.5		-9		-10		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
f_{MAX}	Clock Frequency	—	100	—	90	—	66	—	66	MHz
t_{KC}	Cycle Time	9.5	—	10	—	15	—	15	—	ns
t_{KH}	Clock High Pulse Width	3.0	—	3.0	—	4.0	—	4.0	—	ns
t_{KL}	Clock Low Pulse Width	3.0	—	3.0	—	4.0	—	4.0	—	ns
t_{KQ}	Clock Access Time	—	8	—	8.5	—	9	—	10	ns
t_{KQX}(1)	Clock High to Output Invalid	2	—	2	—	2	—	2	—	ns
t_{KQLZ}(1,2)	Clock High to Output Low-Z	0	—	0	—	0	—	0	—	ns
t_{KQHZ}(1,2)	Clock High to Output High-Z	2	3.5	2	3.8	2	4	1.5	4.2	ns
t_{OEQ}	Output Enable to Output Valid	—	3.5	—	3.8	—	4	—	5	ns
t_{OELZ}(1,2)	Output Enable to Output Low-Z	0	—	0	—	0	—	0	—	ns
t_{OEHZ}(1,2)	Output Enable to Output High-Z	—	3.2	—	3.8	—	4	—	5	ns
t_{AS}	Address Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{SS}	Address Status Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{WS}	Write Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{CES}	Chip Enable Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{AVS}	Address Advance Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{AH}	Address Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{SH}	Address Status Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{WH}	Write Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{CEH}	Chip Enable Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{AVH}	Address Advance Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns

*This speed available only in SF version

Note:

1. Guaranteed but not 100% tested. This parameter is periodically sampled.
2. Tested with load in Figure 2.

READ/WRITE CYCLE TIMING



WRITE CYCLE SWITCHING CHARACTERISTICS (Over Operating Range)

Symbol	Parameter	-8* Min.	-8* Max.	-8.5 Min.	-8.5 Max.	-9 Min.	-9 Max.	-10 Min.	-10 Max.	Unit
t_{KC}	Cycle Time	9.5	—	10	—	15	—	15	—	ns
t_{KH}	Clock High Pulse Width	3.0	—	3.0	—	4.0	—	4.0	—	ns
t_{KL}	Clock Low Pulse Width	3.0	—	3.0	—	4.0	—	4.0	—	ns
t_{AS}	Address Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{SS}	Address Status Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{WS}	Write Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{DS}	Data In Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{CES}	Chip Enable Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{AVS}	Address Advance Setup Time	1.8	—	1.8	—	2	—	2	—	ns
t_{AH}	Address Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{SH}	Address Status Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{DH}	Data In Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{WH}	Write Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{CEH}	Chip Enable Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns
t_{AVH}	Address Advance Hold Time	0.5	—	0.5	—	0.5	—	0.5	—	ns

*This speed available only in SF version

WRITE CYCLE TIMING



SLEEP MODE ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	Min.	Max.	Unit
I_{SB2}	Current during SLEEP MODE	ZZ ≥ Vih	—	30	mA
t_{PDS}	ZZ active to input ignored		2	—	cycle
t_{PUS}	ZZ inactive to input sampled		2	—	cycle
t_{ZZI}	ZZ active to SLEEP current		2	—	cycle
t_{RZZI}	ZZ inactive to exit SLEEP current		0	—	ns

SLEEP MODE TIMING



ORDERING INFORMATION

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8 ns	IS61SF25632T-8TQ	TQFP
	IS61SF25632D-8TQ	TQFP
	IS61SF25632D-8B	PBGA
8.5 ns	IS61SF25632T-8.5TQ	TQFP
	IS61SF25632D-8.5TQ	TQFP
	IS61SF25632D-8.5B	PBGA
9 ns	IS61SF25632T-9TQ	TQFP
	IS61SF25632D-9TQ	TQFP
	IS61SF25632D-9B	PBGA
10 ns	IS61SF25632T-10TQ	TQFP
	IS61SF25632D-10TQ	TQFP
	IS61SF25632D-10B	PBGA

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8 ns	IS61SF25636T-8TQ	TQFP
	IS61SF25636D-8TQ	TQFP
	IS61SF25636D-8B	PBGA
8.5 ns	IS61SF25636T-8.5TQ	TQFP
	IS61SF25636D-8.5TQ	TQFP
	IS61SF25636D-8.5B	PBGA
9 ns	IS61SF25636T-9TQ	TQFP
	IS61SF25636D-9TQ	TQFP
	IS61SF25636D-9B	PBGA
10 ns	IS61SF25636T-10TQ	TQFP
	IS61SF25636D-10TQ	TQFP
	IS61SF25636D-10B	PBGA

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61SF25632T-8.5TQI	TQFP
	IS61SF25632D-8.5TQI	TQFP
9 ns	IS61SF25632T-9TQI	TQFP
	IS61SF25632D-9TQI	TQFP
10 ns	IS61SF25632T-10TQI	TQFP
	IS61SF25632D-10TQI	TQFP

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61SF25636T-8.5TQI	TQFP
	IS61SF25636D-8.5TQI	TQFP
9 ns	IS61SF25636T-9TQI	TQFP
	IS61SF25636D-9TQI	TQFP
10 ns	IS61SF25636T-10TQI	TQFP
	IS61SF25636D-10TQI	TQFP

ORDERING INFORMATION

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8 ns	IS61SF51218T-8TQ	TQFP
	IS61SF51218D-8TQ	TQFP
	IS61SF51218D-8B	PBGA
8.5 ns	IS61SF51218T-8.5TQ	TQFP
	IS61SF51218D-8.5TQ	TQFP
	IS61SF51218D-8.5B	PBGA
9 ns	IS61SF51218T-9TQ	TQFP
	IS61SF51218D-9TQ	TQFP
	IS61SF51218D-9B	PBGA
10 ns	IS61SF51218T-10TQ	TQFP
	IS61SF51218D-10TQ	TQFP
	IS61SF51218D-10B	PBGA

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61SF51218T-8.5TQI	TQFP
	IS61SF51218D-8.5TQI	TQFP
9 ns	IS61SF51218T-9TQI	TQFP
	IS61SF51218D-9TQI	TQFP
10 ns	IS61SF51218T-10TQI	TQFP
	IS61SF51218D-10TQI	TQFP

ORDERING INFORMATION

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8.5 ns	IS61LF25632T-8.5TQ	TQFP
	IS61LF25632D-8.5TQ	TQFP
	IS61LF25632D-8.5B	PBGA
9 ns	IS61LF25632T-9TQ	TQFP
	IS61LF25632D-9TQ	TQFP
	IS61LF25632D-9B	PBGA
10 ns	IS61LF25632T-10TQ	TQFP
	IS61LF25632D-10TQ	TQFP
	IS61LF25632D-10B	PBGA

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8.5 ns	IS61LF25636T-8.5TQ	TQFP
	IS61LF25636D-8.5TQ	TQFP
	IS61LF25636D-8.5B	PBGA
9 ns	IS61LF25636T-9TQ	TQFP
	IS61LF25636D-9TQ	TQFP
	IS61LF25636D-9B	PBGA
10 ns	IS61LF25636T-10TQ	TQFP
	IS61LF25636D-10TQ	TQFP
	IS61LF25636D-10B	PBGA

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61LF25632T-8.5TQI	TQFP
	IS61LF25632D-8.5TQI	TQFP
9 ns	IS61LF25632T-9TQI	TQFP
	IS61LF25632D-9TQI	TQFP
10 ns	IS61LF25632T-10TQI	TQFP
	IS61LF25632D-10TQI	TQFP

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61LF25636T-8.5TQI	TQFP
	IS61LF25636D-8.5TQI	TQFP
9 ns	IS61LF25636T-9TQI	TQFP
	IS61LF25636D-9TQI	TQFP
10 ns	IS61LF25636T-10TQI	TQFP
	IS61LF25636D-10TQI	TQFP

ORDERING INFORMATION

Commercial Range: 0°C to +70°C

Speed	Order Part Number	Package
8.5 ns	IS61LF51218T-8.5TQ	TQFP
	IS61LF51218D-8.5TQ	TQFP
	IS61LF51218D-8.5B	PBGA
9 ns	IS61LF51218T-9TQ	TQFP
	IS61LF51218D-9TQ	TQFP
	IS61LF51218D-9B	PBGA
10 ns	IS61LF51218T-10TQ	TQFP
	IS61LF51218D-10TQ	TQFP
	IS61LF51218D-10B	PBGA

Industrial Range: –40°C to +85°C

Speed	Order Part Number	Package
8.5 ns	IS61LF51218T-8.5TQI	TQFP
	IS61LF51218D-8.5TQI	TQFP
9 ns	IS61LF51218T-9TQI	TQFP
	IS61LF51218D-9TQI	TQFP
10 ns	IS61LF51218T-10TQI	TQFP
	IS61LF51218D-10TQI	TQFP

Integrated Silicon Solution, Inc.
2231 Lawson Lane
Santa Clara, CA 95054
Tel: 1-800-379-4774
Fax: (408) 588-0806
E-mail: sales@issi.com
www.issi.com