


ISQ204-77




**OPTICALLY COUPLED ISOLATOR
TRANSISTOR OUTPUT**

SCHEMATIC



PACKAGE DIMENSIONS INCHES (MM)



DESCRIPTION

The ISQ204-77 are optically coupled isolators consisting of Gallium Arsenide infrared emitting diodes and NPN silicon phototransistors mounted in a standard 16-pin dual-in-line package with four channels per unit.

OUTPUT TRANSISTOR

Collector Emitter Voltage BV_{CEO} _____ 30V
 Emitter Collector Voltage BV_{ECO} _____ 7V
 Power Dissipation _____ 150mW
 (derate linearly 2.00mW/°C above 25°C)

ABSOLUTE MAXIMUM RATINGS

(25 °C unless otherwise noted)

Storage Temperature _____ -55°C to +125°C
 Operating Temperature _____ -55°C to +100°C
 Lead Soldering Temperature
 (2mm from case for 10 secs) _____ 260°C
 Input to Output Isolation Voltage _____ 5000Vrms

PACKAGE

Total Power Dissipation _____ 500mW
 (derate linearly 6.67mW/°C above 25°C)

INPUT DIODE

Forward D.C.Current _____ 50mA
 Reverse D.C.Voltage _____ 3V
 Peak Forward Current
 (pw ≤100µs, duty ratio 0.001) _____ 1A
 Power Dissipation
 (derate linearly 1.33W/°C above 25°C) _____ 100mW

ISOCOM COMPONENTS LTD

Unit 25B, Park Road West,
 Park View Industrial Estate, Brenda Road
 Hartlepool, Cleveland, TS25 1YD
 Tel: (01429) 863609 Fax :(01429) 863581

ISOCOM INC

720 E., Park Boulevard, Suite 104,
 Plano, TX 75074 USA
 Tel: (214) 423-5521
 Fax: (214) 422-4549

ELECTRICAL CHARACTERISTICS (25°C unless otherwise noted)

Parameter		Min.	Typ	Max.	Units	Test Condition
Input	Forward Voltage (V_F)		1.2	1.5	Volt	$I_F = 20 \text{ mA}$
	Forward Voltage (V_F)		1.0	1.2	Volt	$I_F = 1 \text{ mA}$
	Reverse Current (I_R)			10	μA	$V_R = 3 \text{ V}$
Output	Collector-emitter Voltage (BV_{CEO})	30	50		Volt	$I_C = 1 \text{ mA}$
	Emitter-collector Voltage (BV_{ECO})	7	9		Volt	$I_E = 0.1 \text{ mA}$
	Collector-emitter Dark Current (I_{CEO})			50	nA	$V_{CE} = 10 \text{ V}$
Coupled	DC Current Transfer Ratio (CTR)	80			%	$I_F = 1 \text{ mA}, V_{CE} = 10 \text{ V}$
	Collector-emitter Saturation Voltage $V_{CE}(\text{Sat})$				Volt	$I_F = 10 \text{ mA}, I_C = 2 \text{ mA}$
	Floating Capacitance (C_F)				pF	$V = 0 \text{ f} = 1 \text{ MHz}$
	Input-to-Output Isolation Resistance Riso	10^{12}		0.4	ohm	$V_{IO} = 500 \text{ V}$ (see note 1)
	Input to Output Isolation Voltage	5000		10	Vrms	(note 1)
	Output Rise Time (t_r)				μS	$I_F = 10 \text{ mA}, V_{CC} = 5 \text{ V}$
	Output Turn - on Time (t_{on})				μS	$R_L = 75 \text{ R},$
	Output Fall Time (t_f)		0.2		μS	Fig 1
Output Turn - off Time (t_{off})		0.6				
			2.0			
			3.0			
			2.0			
			2.5			

Note 1. Measured with input leads shorted together and output leads shorted together.




FIG 1