

DESCRIPTION:


Non-independent Standby refrigeration units KBL20B/30B/40B/50B/60B/70B/80B/90B have two compressors. The main compressor is driven by vehicle engine directly when its running. The standby compressor is driven by electric power when vehicle stopped. Our products can meet the long-distance transportation refrigeration requirement for vehicle 6-13m³/12-19m³/16-26m³/24-40m³/90-50m³/36-55m³ separately. The condenser adopts streamlines design and delicate appearance. The evaporator uses super-thin design. We use refrigerant R404A for low temperature and R134a for high temperature, free of fluorin.

信心, 源于品质!
CONFIDENCE STEMS FROM QUALITY


KBL20B/30B/40B/50B/60B/70B/80B/90B 技术参数 TECHNICAL DATA

备电机组图片
BACKUP ELECTRICITY POWER TECHNOLOGY DESCRIPTION:
外型尺寸: 620×425×552mm
KBL20B/KBL30B/KBL40B/KBL50B/KBL60B

KBL40B/KBL60B



名称: 控制面板 型号: WD-02L
CONTROL PANEL MODEL: WD-02L



机组型号/UNIT MODEL	KBL20B	KBL30B	KBL40B	KBL50B	KBL60B	KBL70B	KBL80B	KBL90B
使用温度/APPLICABLE TEMPERATURE(°C)	-18/20	-18/20	-18/20	-18/20	-18/20	-18/20	-18/20	-18/20
适用箱体容积/APPLICABLE VOLUME (M ³)	6/13	12/19	16/26	20/31	24/40	30/50	36/55	42/60
制冷量/制冷 (W)	0°C	2000/1818	2800/2545	4200/3810	4700/4272	5200/4727	5800/5272	6500/5909
	-18°C	1200/1334	1600/1776	2200/2445	2560/2840	2950/3278	3300/3667	3800/4222
制冷剂/充注量/REFRIGERANT CHARGE AMOUNT (kg)	A404A/1.2	R404A/1.3	R404A/2.3	R404A/2.8	R404A/3.3	R404A/3.3	R404A/4.0	R404A/4.3
压缩机 COMPRESSOR	冷态压缩机型号/Model	SD7L15	SD7L15	TM19HDUPH170	TM19HDUPH170	TM21HDUPP200	TM21HDUPP200	DKS32
	备电压缩机型号/Model	ZB15KQE	ZB15KQE	ZB19KQE	ZB19KQE	ZB21KQE	MLZ026	MLZ026
	备电压缩机电压/相数 (V)	220/1、380/3	220/1、380/3	220/1、380/3	220/1、330/3	220/1、380/3	220/1、380/3	220/1、380/3
	润滑油/LUBRICATION OIL	RL68H	RL68H	RL68H	RL68H	RL68H	RL68H	RL68H
冷凝器总成 CONDENSER ASSEMBLY	冷凝器形式/CONDENSER TYPE	管片式/Gilled tubed type						
	风机形式/FAN TYPE	轴流式/Axial						
	风机数量/NUMBER	1	1	1	1	1	2	2
	电压/VOLTAGE (V)	12/24						
蒸发器总成 EVAPORATOR ASSEMBLY	蒸发器形式/EVAPORATOR TYPE	管片式/Gilled tubed type						
	风机形式/FAN TYPE	离心式/Centrifugal			轴流式/Axial			
	风机数量/NUMBER	1	1	2	3	3	3	3
	电压/VOLTAGE (V)	12/24						
外形尺寸 (mm) DIMENSIONS	蒸发器总成 EVAPORATOR ASSEMBLY	853×608×171	1254×649×150	1556×649×150	1556×649×150	1223×550×280	1223×652×330	1223×652×330
	冷凝器总成 CONDENSER ASSEMBLY	895×500×235	1125×505×238	1367×514×468	1367×514×456	1367×514×458	1367×514×458	1367×514×456
	备电机组	620×425×552	620×425×552			620×425×552	620×425×552	
重量/Weight(kg)	蒸发器总成 EVAPORATOR ASSEMBLY	16	18	22	28	28	34	38
	冷凝器总成 CONDENSER ASSEMBLY	32	38	88	92	92	60	63
	备电机组	65	65				70	70

注: 1. 环境温度35℃NOTE: environment temperature is 35°C
2. 以上冷冻机组为非独立备电机组。
3. KBL20B/30B/70B/80B/90B冷凝器总成和备电机组为分体式。
KBL40B/50B/60B冷凝器总成和备电机组为整体式。
NOTE: environment temperature is 35°C
1. Ambience temperature 35°C
2. All above refrigeration units are non-independent standby refrigeration unit.
3. KBL20B/30B/70B/80B/90B has split condenser assembly and standby system. KBL40B/50B/60B has integrated condenser assembly and standby system.

广州精博制冷设备有限公司
GUANGZHOU JINGBO REFRIGERATION EQUIPMENT CO., LTD.

地址: 广州市花都区花山镇坪山工业区5号 邮编: 510880 总机: 020-86789018
电话: 020-86788612 86788613 国际营销: 020-86789036 86788631
传真: 020-86789023 免费热线: 400-830-5668