

## APPLICATIONS

- ✓ Cellular Phones
- ✓ Personal Digital Assistant (PDA)
- ✓ Notebook Computers
- ✓ SMART Cards

## IEC COMPATIBILITY (EN61000-4)

- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns

## FEATURES


- ✓ ESD Protection > 25 kilovolts
- ✓ Available in Voltages Ranging From 3.3V to 36V
- ✓ 200 Watts Peak Pulse Power per Line (tp = 8/20µs)
- ✓ Low Clamping Voltage
- ✓ Bidirectional Configuration & Monolithic Structure
- ✓ Protects 4 to 7 Lines
- ✓ Low Capacitance
- ✓ Low Leakage Current
- ✓ RoHS Compliant

## MECHANICAL CHARACTERISTICS

- ✓ Standard EIA Chip Size: 0408
- ✓ Weight 0.73 milligrams (Approximate)
- ✓ Available in Lead-Free Plating
- ✓ Solder Reflow Temperature:  
Lead-Free - Sn/Ag/Cu, 96/3.5/0.5: 260-270°C
- ✓ Consult Factory for Leaded Device Availability
- ✓ Flammability Rating UL 94V-0
- ✓ 8mm Plastic & Paper Tape and Reel Per EIA Standard 481
- ✓ Device Marking On Reel
- ✓ Top Contacts: Solder Bump 0.004" in Height (Nominal)



## PIN CONFIGURATION



# LC0408FC3.3C thru LC0408FC36C

## DEVICE CHARACTERISTICS

### MAXIMUM RATINGS @ 25°C Unless Otherwise Specified

PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (tp = 8/20µs) - See Figure 1	P <sub>PP</sub>	200	Watts
Operating Temperature	T <sub>A</sub>	-55 to 150	°C
Storage Temperature	T <sub>STG</sub>	-55 to 150	°C


### ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER (See Note 1)	RATED STAND-OFF VOLTAGE  V <sub>WM</sub> VOLTS	MINIMUM BREAKDOWN VOLTAGE	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM LEAKAGE CURRENT (See Note 2)	TYPICAL CAPACITANCE
		@ 1mA V <sub>(BR)</sub> VOLTS	@ I <sub>p</sub> = 1A V <sub>C</sub> VOLTS	@ 8/20µs V <sub>C</sub> @ I <sub>PP</sub>	@ V <sub>WM</sub> I <sub>D</sub> µA	@ 0V, 1 MHz C pF
LC0408FC3.3C	3.3	4.0	7.0	12.5V @ 16A	75*	70
LC0408FC05C	5.9	6.0	11.0	13V @ 15A	10**	35
LC0408FC08C	8.0	8.5	13.2	18V @ 11A	1	32
LC0408FC12C	12.0	13.3	19.8	26.9V @ 7.4A	1	30
LC0408FC15C	15.0	16.7	25.4	34.5V @ 5.8A	1	25
LC0408FC24C	24.0	26.7	37.2	50.6V @ 4A	1	20
LC0408FC36C	36.0	40.0	70.0	80.0V @ 2.5A	1	18


**Note 1:** All devices are bidirectional. Electrical characteristics apply in both directions.

**Note 2:** \*Maximum leakage current < 5µA @ 2.8V. \*\*Maximum leakage current < 500nA @ 3.3V.

**FIGURE 1  
PEAK PULSE POWER VS PULSE TIME**




**FIGURE 2  
PULSE WAVE FORM**




GRAPHS


**FIGURE 3  
 POWER DERATING CURVE**



**FIGURE 4  
 OVERSHOOT & CLAMPING VOLTAGE FOR LC0408FC05C**



**FIGURE 5  
 TYPICAL CLAMPING VOLTAGE VS PEAK PULSE CURRENT FOR LC0408FC05C**





**APPLICATION INFORMATION**

PRINTED CIRCUIT BOARD RECOMMENDATIONS	
PARAMETER	VALUE
Pad Size on PCB	0.275mm
Pad Shape	Round
Pad Definition	Non-Solder Mask Defined Pads
Solder Mask Opening	0.325mm Round
Solder Stencil Thickness	0.150mm
Solder Stencil Aperture Opening (laser cut, 5% tapered walls)	0.330mm Round
Solder Paste Type	No Clean
Pad Protective Finish	OSP (Entek Cu Plus 106A)
Tolerance - Edge To Corner Ball	±50µm
Solder Ball Side Coplanarity	±20µm
Maximum Dwell Time Above Liquidous (183°C)	60 Seconds
Soldering Maximum Temperature	270°C


REQUIREMENTS
Temperature: $T_p$ for Lead-Free (SnAgCu): 260-270°C $T_p$ for Tin-Lead: 240-245°C Preheat time and temperature depends on solder paste and flux activation temperature, component size, weight, surface area & plating.

**RECOMMENDED NON-SOLDER MASK DEFINED PAD ILLUSTRATION**



# LC0408FC3.3C thru LC0408FC36C


## 0408 PACKAGE OUTLINE & DIMENSIONS



# LC0408FC3.3C thru LC0408FC36C

## 0408 PACKAGE OUTLINE & DIMENSIONS

### MOUNTING PAD LAYOUT - Option 2




### PACKAGE DIMENSIONS

DIM	MILLIMETERS	INCHES
A	0.51	0.020
F	0.15 SQ	0.006 SQ
G	0.71	0.028
H	0.99	0.039
I	0.51	0.020

#### NOTES:

- Controlling dimensions in inches.
- Decimal tolerances for mounting pad and outline: .xxx ± 0.05mm (± 0.002").
- Preferred: Using 0.1mm (0.004") stencil.

### TAPE & REEL ORIENTATION



#### NOTE:

- Top view of tape. Solder bumps are face down in tape package.

### TAPE & REEL ORDERING NOMENCLATURE

- Surface mount product is taped and reeled in accordance with EIA 481.
- 8mm Plastic Tape: 7 Inch Reels - 5,000 pieces per reel. Ordering Suffix: -T75-1, i.e., LC0408FC05C-T75-1.
- 8mm Paper Tape: 7 Inch Reels - 5,000 pieces per reel. Ordering Suffix: -T75-2, i.e., LC0408FC05C-T75-2.
- Suffix - LF = Lead-Free, i.e., LC0408FC05C-LF-T75-1.

Outline & Dimensions: Rev 4 - 2/04, 06021

COPYRIGHT © ProTek Devices 2007

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

**ProTek Devices**

2929 South Fair Lane, Tempe, AZ 85282

Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: [sales@protekdevices.com](mailto:sales@protekdevices.com)

Web Site: [www.protekdevices.com](http://www.protekdevices.com)