

LD2541U/V Series - 0.25 inch dual Digit 7 Segment LED Display



ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DISCHARGE
SENSITIVE
DEVICES




Features

- 6.20 mm (0.25inch) digit high
- Excellent digit appearance
- Wide viewing angle
- Range of emitted colors
- I.C. compatible
- Low power consumption
- White segment
- RoHS compliant

Available options

- Alternative emitting luminosity:
Standard or high brightness version
- Alternative emitted color
- Alternative segment color
- Alternative font
- Common Cathode is available
- Cropped terminal pins

Package Dimensions




Notes:


1. All dimensions are in millimeters(inches), Tolerance is $\pm 0.25\text{mm}(0.01\text{inch})$ unless other wise noted.
2. Specifications are subject to change without notice.
3. The gap between the reflector and PCB shall not exceed 0.25mm

Internal Circuit Diagram

LD2541U (Common Cathode)



LD2541V (Common Anode)



Selection Guide

Four Digits 7 Segment LED Display, Digit Height: 6.20mm(0.25inch), External Dimensions: 36.00x11.00x5.10mm (Lx W x H)

Part No.		Chip			Iv@IF=20mA		Iv@IF=20mA	
Common Cathode	Common Anode	Material	Color	WLD	One Seg		One DP	
					Min.	Typ.	Min.	Typ.
LD2541UR	LD2541VR	GaAlAs	Super Red	640	8	10	8	10
LD2541UD	LD2541VD	GaAlAs	Hi-Red	640	18	25	18	25
LD2541UO	LD2541VO	GaAsP	Orange	625	7	9	7	9
LD2541UY	LD2541VY	GaAsP	Yellow	588	8	10	8	10
LD2541UG	LD2541VG	GaP	Green	568	7	9	7	9
LD2541UUR	LD2541VUR	AlGaInP	Ultra Red	640	30	45	30	45
LD2541UUO	LD2541VUO	AlGaInP	Ultra Orange	625	45	60	45	60
LD2541UUA	LD2541VUA	AlGaInP	Ultra Amber	65	30	45	30	45
LD2541UUY	LD2541VUY	AlGaInP	Ultra Yellow	595	30	45	30	45
LD2541UUG	LD2541VUG	AlGaInP	Ultra Green	573	30	45	30	45
LD2541UPG	LD2541VPG	InGaN	Pure Green	525	120	300	120	300
LD2541UUB	LD2541VUB	InGaN	Ultra Blue	470	30	45	30	45
LD2541UUW	LD2541VUW	InGaN	Ultra White	\	100	120	100	120
Unit:	\	\	\	nm	mcd	mcd	mcd	mcd

Electrical Characteristics & Absolute Maximum Ratings

Color		Electrical Characteristics ^[1]			Absolute Maximum Ratings ^[1]		
		Forward Voltage@ IF=20mA		Reverse Current VR=5V	Power Dissipation	DC Forward Current	Peak Forward Current ^[2]
		Typ.	Max.				
Super Red	Per Seg.	1.8	2.2	30	60	25	100
	Per DP	1.8	2.2	30	60	25	100
Hi-Red	Per Seg.	1.8	2.2	30	60	25	100
	Per DP	1.8	2.2	30	60	25	100
Orange	Per Seg.	2.1	2.5	30	80	30	100
	Per DP	2.1	2.5	30	80	30	100
Yellow	Per Seg.	2.1	2.5	30	80	30	100
	Per DP	2.1	2.5	30	80	30	100
Green	Per Seg.	2.2	2.5	30	80	30	100
	Per DP	2.2	2.5	30	80	30	100
Ultra Red	Per Seg.	1.9	2.6	30	60	30	100
	Per DP	1.9	2.6	30	60	30	100
Ultra Orange	Per Seg.	2	2.6	30	65	30	100
	Per DP	2	2.6	30	65	30	100
Ultra Amber	Per Seg.	2	2.6	30	65	30	100
	Per DP	2	2.6	30	65	30	100
Ultra Yellow	Per Seg.	2	2.6	30	65	30	100
	Per DP	2	2.6	30	65	30	100
Ultra Green	Per Seg.	2.1	2.6	30	75	30	100
	Per DP	2.1	2.6	30	75	30	100
Pure Green	Per Seg.	3.5	4	30	110	30	100
	Per DP	3.5	4	30	110	30	100
Ultra Blue	Per Seg.	3.5	4	30	120	30	100
	Per DP	3.5	4	30	120	30	100
Ultra White	Per Seg.	3.5	4	30	120	30	100
	Per DP	3.5	4	30	120	30	100
Unit:	\	V	V	uA	mW	mA	mA

Notes:

1. At Ta=25 °C.

2. Peak forward current at 1/10 Duty Cycle, 0.1ms Pulse.