

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- Ultra Low Forward Voltage Drop
- High Current Capability
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


Maximum Ratings

- Operating Temperature:-55°C to +150°C
- Storage Temperature:-55°C to +150°C

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBR1545PS	1545	45V	31.5V	45V

MBR1545PS

15 Amp Schottky Barrier Rectifier 45 Volts



Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}		15A		T _L = 90°0	C
Peak Forward Surge Current	I _{FSM}		280A		8.3ms, h	alf sine
		Min.	Тур.	Max.		
Forward Voltage	V_{F}		0.43V 0.50V	 0.55V	l⊧=8A l⊧=15A	TJ=25°C
Reverse Current	I _R		50uA 	1mA 120mA	V _R =45V V _R =45V	Tյ=25°C Tյ=125°C
Maximum thermal Resistance	R _{θJC}		8.0 ℃	/W		

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

INCHES мм DIM NOTE MA MIN MAX 030 047 1.00 1.20 A A2 .008 .012 0.30 0.20 b1 .039 .047 1.00 1.20 .075 .165 .083 .173 b2 D 1.90 2.10 4.40 4.20 D2 .138 150 3.50 6.30 3.80 .256 Ε .248 6.50 .079 .083 2.00 2.10 е E1 240 5.90 6.10 .232 E2 149 .157 3.79 3.99 .027 .031 0.68 0.78 L W .025 .029 0.63 0.73 0.55 0.65 F .022 .177 .026 .185

•PIN 2

-oPIN 1

2

PIN 3 0-14 HEAT SINK

Revision: B

www.mccsemi.com



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com