

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# MBRD5200CT

# **Features**

- Low Leakage Current.
- High Current Capability, High Efficiency.
- High Junction Temperature Capability.
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

# **Maximum Ratings**


- Operating Temperature:- 55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance (Per Leg): 3°C/W Junction To Case

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximu m RMS Voltage	Maximum DC Blocking Voltage
MBRD5200CT	MBRD5200CT	200V	140V	200V

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Rectified Forward Current (Rated VR-20Khz Square Wave) - 50% duty cycle	I <sub>F(AV)</sub>	5.0A			
Peak Forward Surge Current	I <sub>FSM</sub>	140A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage	V <sub>F</sub>	0.78V(typ) 0.84V 0.70V	$I_F = 2.5A; T_J = 25^{\circ}C$ $I_F = 2.5A; T_J = 25^{\circ}C$ $I_F = 2.5A; T_J = 125^{\circ}C$		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	5uA 1.5mA	$T_J = 25^{\circ}\mathbb{C}$ $T_J = 125^{\circ}\mathbb{C}$		

# 5 Amp Schottky Barrier Rectifier 200 Volts




DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	0.087	0.094	2.20	2.40	
В	0.000	0.005	0.00	0.13	
С	0.026	0.034	0.66	0.86	
D	0.018	0.023	0.46	0.58	
Е	0.256	0.264	6.50	6.70	
F	0.201	0.215	5.10	5.46	
G	0.190		4.83		
Н	0.236	0.244	6.00	6.20	
ı	0.086	0.094	2.18	2.39	
J	0.386	0.409	9.80	10.40	
K	0.114		2.90		
L	0.055	0.067	1.40	1.70	
М	0.063		1.60		,
0	0.043	0.051	1.10	1.30	,
Q	0.000	0.012	0.00	0.30	
V	V 0.211		5.	35	




# **Characteristic Curves**

## The forward voltage and forward current curve



### The reverse leak current and the reverse voltage (single-device) curve.





## **Ordering Information:**

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.