




MBRF5100 - MBRF5200

Isolated 5.0 AMPS. Schottky Barrier Rectifiers

ITO-220AC

Features

- ✧ Plastic material used carries Underwriters Laboratory Classifications 94V-0
- ✧ Metal silicon rectifier, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ Guardring for overvoltage protection
- ✧ High temperature soldering guaranteed: 260°C/10 seconds, 0.25"(6.35mm) from case
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



Dimensions in inches and (millimeters)
Marking Diagram



- MBRF5XXX = Specific Device Code
- G = Green Compound
- Y = Year
- WW = Work Week

Mechanical Data

- ✧ Cases: JEDEC ITO-220AC molded plastic body
- ✧ Terminals: Lead solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in. - lbs. max
- ✧ Weight: 1.61 grams

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%

| Type Number | Symbol | MBRF 5100 | MBRF 5150 | MBRF 5200 | Units |
|---|-----------------|--------------|--------------|-----------|---------------------------|
| Maximum Recurrent Peak Reverse Voltage | V_{RRM} | 100 | 150 | 200 | V |
| Maximum RMS Voltage | V_{RMS} | 70 | 105 | 140 | V |
| Maximum DC Blocking Voltage | V_{DC} | 100 | 150 | 200 | V |
| Maximum Average Forward Rectified Current | $I_{F(AV)}$ | 5 | | | A |
| Peak Repetitive Forward Current (Square Wave, 20KHz) at $T_c=105^\circ\text{C}$ | I_{FRM} | 10 | | | A |
| Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | I_{FSM} | 120 | | | A |
| Peak Repetitive Reverse Surge Current (Note 2) | I_{RRM} | 0.5 | | | A |
| Maximum Instantaneous Forward Voltage at $I_F=5A, T_A=25^\circ\text{C}$ $I_F=5A, T_A=125^\circ\text{C}$ | V_F | 0.90 0.80 | 1.02 0.92 | | V |
| Maximum Instantaneous Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage (Note 1) @ $T_A=125^\circ\text{C}$ | I_R | 0.1 5.0 | | | mA mA |
| Voltage Rate of Change (Rated V_R) | dV/dt | 10,000 | | | V/ μS |
| Typical Junction capacitance | C_j | 310 | | | pF |
| Maximum Thermal Resistance, (Note 3) | $R_{\theta JC}$ | 3.0 | | | $^\circ\text{C}/\text{W}$ |
| Operating Junction Temperature Range | T_J | -65 to +150 | | | $^\circ\text{C}$ |
| Storage Temperature Range | T_{STG} | -65 to +175 | | | $^\circ\text{C}$ |

Notes: 1. Pulse Test: 300us Pulse Width, 1% Duty Cycle
2. 2.0us Pulse Width, f=1.0 KHz
3. Mounted on Heatsink Size of 2 in x 3 in x 0.25 in Al-Plate.

RATINGS AND CHARACTERISTIC CURVES (MBRF5100 THRU MBRF5200)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

