

### Features

- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-0
- ✧ Metal silicon rectifier, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ Guard-ring for overvoltage protection
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.25", (6.35mm) from case
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



### Mechanical Data

- ✧ Case: ITO-220AC molded plastic body
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in. - lbs, max
- ✧ Weight: 1.61 grams

### Ordering Information(example)

Part No.	Package	Packing	Packing code	Packing code (Green)
MBRF5100	ITO-220AC	50 / TUBE	C0	C0G

### Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbol	MBRF 5100	MBRF 5150	MBRF 5200	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	100	150	200	V
Maximum RMS Voltage	$V_{RMS}$	70	105	140	V
Maximum DC Blocking Voltage	$V_{DC}$	100	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	5			A
Peak Repetitive Surge Current (Rated $V_R$ , Square Wave, 20KHz)	$I_{FRM}$	10			A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	$I_{FSM}$	120			A
Peak Repetitive Reverse Surge Current (Note 1)	$I_{RRM}$	0.5			A
Maximum Instantaneous Forward Voltage (Note 2) IF=5A, $T_A=25^{\circ}C$ IF=5A, $T_A=125^{\circ}C$	$V_F$	0.90 0.80	1.02 0.92		V
Maximum Reverse Current @ Rated $V_R$ $T_A=25^{\circ}C$ $T_A=125^{\circ}C$	$I_R$	0.1 5			mA
Voltage Rate of Change,(Rated $V_R$ )	dV/dt	10000			V/us
Typical Junction capacitance	$C_j$	310			pF
Typical Thermal Resistance	$R_{\theta JC}$	3			$^{\circ}C/W$
Operating Temperature Range	$T_J$	- 65 to + 150			$^{\circ}C$
Storage Temperature Range	$T_{STG}$	- 65 to + 175			$^{\circ}C$

Note 1: 2.0uS Pulse Width, f=1.0KHz

Note 2: Pulse Test : 300uS Pulse Width, 1% Duty Cycle

RATINGS AND CHARACTERISTIC CURVES (MBRF5100 THRU MBRF5200)

FIG. 1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE





FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE




### Ordering information

Part No.	Package	BULK Packing	Packing code	Packing code (Green)
MBRF5xxx	ITO-220AC	50 / TUBE	C0	C0G

Note: "xxx" is Device Code from "100" thru "200".

### Dimensions



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	4.30	4.70	0.169	0.185
B	2.50	3.10	0.098	0.122
C	2.30	2.90	0.091	0.114
D	0.46	0.76	0.018	0.030
E	6.30	6.90	0.248	0.272
F	9.60	10.30	0.378	0.406
G	3.00	3.40	0.118	0.134
H	-	1.60	-	0.063
I	0.95	1.45	0.037	0.057
J	0.50	0.90	0.020	0.035
K	2.40	3.20	0.094	0.126
L	14.80	15.50	0.583	0.610
M	-	4.10	-	0.161
N	-	1.80	-	0.071
O	12.60	13.80	0.496	0.543
P	4.95	5.20	0.195	0.205

### Marking Diagram



P/N = Specific Device Code  
 G = Green Compound  
 YWW = Date Code