



## 2.5V PRECISION SERIAL VOLTAGE REFERENCE

- OUTPUT VOLTAGE : 2.5V  $\pm$ 1%
- INPUT VOLTAGE RANGE : 4.5V to 40V
- QUIESCENT CURRENT : 1.2mA typ.
- OUTPUT CURRENT : 10mA


### DESCRIPTION

The MC1403 is a serial 2.5V bandgap voltage reference. The major advantages are the 1% precision, the wide input voltage range (4.5V to 40V) and the low quiescent current (1.5mA max.)


### ORDER CODE

| Part Number | Temperature Range | Package |
|-------------|-------------------|---------|
|             |                   | D       |
| MC1403      | 0°C, +70°C        | •       |

D = Small Outline Package (SO) - also available in Tape & Reel (DT)



### PIN CONNECTIONS (top view)



**ABSOLUTE MAXIMUM RATINGS**

| Symbol    | Parameter                 | Value       | Unit |
|-----------|---------------------------|-------------|------|
| $V_{IN}$  | Input Voltage             | 40          | V    |
| $T_{stg}$ | Storage Temperature Range | -65 to +150 | °C   |

**OPERATING CONDITIONS**


| Symbol     | Parameter                            | Value     | Unit |
|------------|--------------------------------------|-----------|------|
| $V_{IN}$   | Input Voltage ( $I_{OUT} = 0mA$ )    | 4.5 to 40 | V    |
| $T_{oper}$ | Operating Free Air Temperature Range | 0 to +70  | °C   |

**ELECTRICAL CHARACTERISTICS**

$T_{amb} = 25^{\circ}C$ ,  $V_{IN} = 15V$  (unless otherwise specified)

| Symbol                            | Parameter  | Min.  | Typ. | Max.     | Unit   |
|-----------------------------------|--|-------|------|----------|--------|
| $V_{OUT}$                         | Output Voltage<br>$I_{OUT} = 0mA$  | 2.475 | 2.5  | 2.525    | V      |
| $\frac{\Delta V_{out}}{\Delta T}$ | Temperature Coefficient of Output Voltage<br>$I_{OUT} = 0mA$   |       | 10   | 40       | ppm/°C |
| $\Delta V_{OUT}$                  | Output Voltage change Over the Full Temperature Range<br>$I_{OUT} = 0mA$                                   |       | 2    | 7        | mV     |
| $Reg_{line}$                      | Line regulation<br>$I_{OUT} = 0mA$ , $4.5V \leq V_i \leq 15V$<br>$I_{OUT} = 0mA$ , $15V \leq V_i \leq 40V$ |       |      | 3<br>4.5 | mV     |
| $Reg_{load}$                      | Load Regulation<br>$0 \leq I_{OUT} \leq 10mA$  |       |      | 10       | mV     |
| $I_Q$                             | Quiescent Current<br>$I_{OUT} = 0mA$   |       | 1.2  | 1.5      | mA     |

**PACKAGE MECHANICAL DATA**  
8 PINS - PLASTIC MICROPACKAGE (SO)



| Dimensions | Millimeters |      |      | Inches |       |       |
|------------|-------------|------|------|--------|-------|-------|
|            | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A          |             |      | 1.75 |        |       | 0.069 |
| a1         | 0.1         |      | 0.25 | 0.004  |       | 0.010 |
| a2         |             |      | 1.65 |        |       | 0.065 |
| a3         | 0.65        |      | 0.85 | 0.026  |       | 0.033 |
| b          | 0.35        |      | 0.48 | 0.014  |       | 0.019 |
| b1         | 0.19        |      | 0.25 | 0.007  |       | 0.010 |
| C          | 0.25        |      | 0.5  | 0.010  |       | 0.020 |
| c1         | 45° (typ.)  |      |      |        |       |       |
| D          | 4.8         |      | 5.0  | 0.189  |       | 0.197 |
| E          | 5.8         |      | 6.2  | 0.228  |       | 0.244 |
| e          |             | 1.27 |      |        | 0.050 |       |
| e3         |             | 3.81 |      |        | 0.150 |       |
| F          | 3.8         |      | 4.0  | 0.150  |       | 0.157 |
| L          | 0.4         |      | 1.27 | 0.016  |       | 0.050 |
| M          |             |      | 0.6  |        |       | 0.024 |
| S          | 8° (max.)   |      |      |        |       |       |

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All Rights Reserved  
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia  
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States

© <http://www.st.com>