

SWITCHMODE™ Series

NPN Silicon Power Transistors

These transistors are designed for high-voltage, high-speed, power switching in inductive circuits where fall time is critical. They are particularly suited for line-operated switchmode applications. The MJ16022 is a selected high-gain version of the MJ16020 for applications where drive current is limited.

Features:

- Fast Switching Times:
 - 30 ns (Typ) Inductive Fall Time
 - 50 ns (Typ) Inductive Crossover Time
 - 800 ns (Typ) Inductive Storage Time
- 100°C Performance Specified for:
 - Reverse-Biased SOA with Inductive Loads
 - Switching Times with Inductive Loads
 - Saturation Voltages

Typical Applications:

- Switching Regulators
- Inverters
- Solenoids and Relay Drivers
- Motor Controls
- Deflection Circuits

MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	Max	Unit
Collector-Emitter Sustaining Voltage	V _{CEO}	450	Vdc
Collector-Emitter Breakdown Voltage	V _{CEV}	850	Vdc
Emitter-Base Voltage	V _{EB}	6	Vdc
Collector Current — Continuous — Peak (1)	I _C I _{CM}	30 40	Adc
Base Current — Continuous — Peak (1)	I _B I _{BM}	20 30	Adc
Total Power Dissipation @ T _C = 25°C Derate above 25°C	P _D	250 1.42	Watts W/°C
Operating and Storage Temperature	T _J , T _{stg}	-65 to 200	°C


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance — Junction to Case	R _{θJC}	0.7	°C/W
Maximum Lead Temperature for Soldering Purposes: 1/8" from Case for 5 Seconds	T _L	275	°C

(1) Pulse Test: Pulse Width = 5 ms, Duty Cycle < 10%.

MJ16020
MJ16022

**NPN SILICON POWER
TRANSISTOR
30 AMPERES
450 VOLTS**



**CASE 197A-05
TO-204AE**

MJ16020 MJ16022

ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS*

Collector–Emitter Sustaining Voltage ($I_C = 1\text{ mA}$, $I = 0$)	$V_{CEO(sus)}$	450	—	—	Vdc
Collector Cutoff Current ($V_{CE} = 850\text{ Vdc}$, $R_{BE} = 50\text{ Ohms}$, $T_C = 100^\circ\text{C}$)	I_{CER}	—	—	—	mAdc
Collector Cutoff Current ($V_{CE} = 850\text{ Vdc}$, $V_{EB(off)} = 1.5\text{ Vdc}$) ($V_{CE} = 850\text{ Vdc}$, $V_{EB(off)} = 1.5\text{ Vdc}$)	I_{CES}	— —	— —	0.5 5	nAdc
Emitter Cutoff Current ($V_{EB} = 6\text{ Vdc}$, $I_C = 0$)	I_{EBO}	—	—	2	nAdc

ON CHARACTERISTICS*

Base–Emitter Saturation Voltage ($I_C = 20\text{ Adc}$, $I_B = 2\text{ Adc}$) ($I_C = 20\text{ Adc}$, $I_B = 2\text{ Adc}$)	$V_{BE(sat)}$	— —	— —	1.5 1.5	Vdc
Collector–Emitter Saturation Voltage ($I_C = 20\text{ Adc}$, $I_B = 1.4\text{ Adc}$) ($I_C = 20\text{ Adc}$, $I_B = 2.6\text{ Adc}$) ($I_C = 20\text{ Adc}$, $I_B = 2.6\text{ Adc}$)	$V_{CE(sat)}$	— — —	— — —	2.5 3 3	Vdc
DC Current Gain ($I_C = 30\text{ Adc}$, $V_{CE} = 5\text{ Vdc}$)	h_{FE}	5 7	— —	— —	—
		MJ16020 MJ16022			

DYNAMIC CHARACTERISTICS

Output Capacitance ($V_{CB} = 10\text{ Vdc}$, $I_E = 0$, $f_{test} = 1\text{ MHz}$)	C_{ob}	—	—	800	pF
--	----------	---	---	-----	----

*Indicates Pulse Test: Pulse Width = 300 μs Max, Duty Cycle = 2%.

MJ16020 MJ16022


ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit			
SWITCHING CHARACTERISTICS: MJ16020								
Resistive Load								
Delay Time	$(V_{CC} = 250\text{ Vdc},$ $I_C = 20\text{ Adc},$ $I_{B1} = 2.6\text{ Adc},$ $t_p = 30\ \mu\text{s},$ Duty Cycle < 2%)	$I_{B2} = 5.2\text{ Adc}$ $R_B = 1.6\ \text{Ohm}$	t_d	—	20	—	ns	
Rise Time			t_r	—	200	—		
Storage Time			t_s	—	1200	—		
Fall Time			t_f	—	200	—		
Storage Time			$(V_{BE(off)} = 5\text{ Vdc})$	t_s	—	650		—
Fall Time				t_f	—	80		—
Inductive Load								
Storage Time	$(I_C = 20\text{ A}, I_{B1} = 2.6\text{ Adc},$ $V_{CE(pk)} = 400\text{ V},$ $V_{BE(off)} = 5\text{ Vdc})$	$(T_C = 100^\circ\text{C})$	t_{sv}	—	800	2000	ns	
Crossover Time			t_{fi}	—	50	200		
Fall Time			t_c	—	90	250		
Storage Time	$(I_C = 20\text{ A}, I_{B1} = 2.6\text{ Adc},$ $V_{CE(pk)} = 400\text{ V},$ $V_{BE(off)} = 5\text{ Vdc})$	$(T_C = 150^\circ\text{C})$	t_{sv}	—	1050	—	ns	
Crossover Time			t_{fi}	—	70	—		
Fall Time			t_c	—	120	—		
SWITCHING CHARACTERISTICS: MJ16022								
Resistive Load								
Delay Time	$(V_{CC} = 250\text{ Vdc},$ $I_C = 20\text{ Adc},$ $I_{B1} = 2.6\text{ Adc},$ $t_p = 30\ \mu\text{s},$ Duty Cycle < 2%)	$I_{B2} = 5.2\text{ Adc}$ $R_B = 1.6\ \text{Ohm}$	t_d	—	20	—	ns	
Rise Time			t_r	—	200	—		
Storage Time			t_s	—	900	—		
Fall Time			t_f	—	150	—		
Storage Time			$(V_{BE(off)} = 5\text{ Vdc})$	t_s	—	500		—
Fall Time				t_f	—	40		—
Inductive Load								
Storage Time	$(I_C = 20\text{ A}, I_{B1} = 2.6\text{ Adc},$ $V_{CE(pk)} = 400\text{ V},$ $V_{BE(off)} = 5\text{ Vdc})$	$(T_C = 100^\circ\text{C})$	t_{sv}	—	650	1700	ns	
Crossover Time			t_{fi}	—	30	150		
Fall Time			t_c	—	50	200		
Storage Time	$(I_C = 20\text{ A}, I_{B1} = 2.6\text{ Adc},$ $V_{CE(pk)} = 400\text{ V},$ $V_{BE(off)} = 5\text{ Vdc})$	$(T_C = 150^\circ\text{C})$	t_{sv}	—	850	—	ns	
Crossover Time			t_{fi}	—	30	—		
Fall Time			t_c	—	70	—		

MJ16020 MJ16022

PACKAGE DIMENSIONS

CASE 197A-05 TO-204AE ISSUE J




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.530 REF		38.86 REF	
B	0.990	1.050	25.15	26.67
C	0.250	0.335	6.35	8.51
D	0.057	0.063	1.45	1.60
E	0.060	0.070	1.53	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	0.760	0.830	19.31	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

STYLE 1:
PIN 1. BASE
2. EMITTER
CASE: COLLECTOR

SWITCHMODE is a trademark of Semiconductor Components Industries, LLC.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)
Email: ONlit@hibbertco.com

EUROPEAN TOLL-FREE ACCESS*: 00-800-4422-3781

*Available from Germany, France, Italy, UK, Ireland

CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)
Email: ONlit-spanish@hibbertco.com
Toll-Free from Mexico: Dial 01-800-288-2872 for Access –
then Dial 866-297-9322

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 1-303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001-800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.