


Features

Epitaxial Planar Die Construction
Complementary NPN Types Available
(MMBTA13 / MMBTA14)
Ideal for Medium Power Amplification and
Switching
High Current Gain

Mechanical Data

Case: SOT-23, Molded Plastic
Terminals: Solderable per MIL-STD-202,
Method 208
Terminal Connections: See Diagram
MMBTA63 Marking: K2E
MMBTA64 Marking: K3E
Weight: 0.008 grams (approx.)



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.19	1.40
C	2.10	2.50
D	0.89	1.05
E	0.45	0.61
G	1.78	2.05
H	2.65	3.05
J	0.013	0.15
K	0.89	1.10
L	0.45	0.61
M	0.076	0.178
All Dimensions in mm		

Maximum Ratings @ T_A = 25 C unless otherwise specified

Characteristic	Symbol	MMBTA63	MMBTA64	Unit
Collector-Base Voltage	V _{CB0}		-30	V
Collector-Emitter Voltage	V _{CEO}		-30	V
Emitter-Base Voltage	V _{EBO}		-10	V
Collector Current - Continuous (Note 1)	I _C		-500	mA
Power Dissipation (Note 1)	P _d		350	mW
Thermal Resistance, Junction to Ambient (Note 1)	R _{JA}		357	K/W
Operating and Storage and Temperature Range	T _J , T _{STG}		-55 to +150	C

Electrical Characteristics @ T_A = 25 C unless otherwise specified

Characteristic	Symbol	Min	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 2)					
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	-30		V	I _C = -100 A, V _{BE} = 0V
Collector Cutoff Current	I _{CB0}		-100	nA	V _{CB} = -30V, I _E = 0
Emitter Cutoff Current	I _{EBO}		-100	nA	V _{EB} = -10V, I _C = 0
ON CHARACTERISTICS (Note 2)					
DC Current Gain	MMBTA63 MMBTA64 MMBTA63 MMBTA64 h _{FE}	5,000 10,000 10,000 20,000			I _C = -10mA, V _{CE} = -5.0V I _C = -10mA, V _{CE} = -5.0V I _C = -100mA, V _{CE} = -5.0V I _C = -100mA, V _{CE} = -5.0V
Collector-Emitter Saturation Voltage	V _{CE(SAT)}		-1.5	V	I _C = -100mA, I _B = -100 A
Base- Emitter Saturation Voltage	V _{BE(SAT)}		-2.0	V	I _C = -100mA, V _{CE} = -5.0V
SMALL SIGNAL CHARACTERISTICS					
Current Gain-Bandwidth Product	f _T	125		MHz	V _{CE} = -5.0V, I _C = -10mA, f = 100MHz

- Notes: 1. Valid provided that terminals are kept at ambient temperature.
2. Pulse test: Pulse width 300 s, duty cycle 2%.