



MMDT3946

NPN/PNP Small Signal Surface Mount Transistors


Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Complementary Pair: NPN(3904), PNP(3906)
- Ideal for Low Power Amplification and Switching
- Ultra-small Surface Mount Package
- Epitaxial Planar Die Construction
- Marking:K46
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings @ 25°C Unless Otherwise Specified


Symbol	Rating	Rating(NPN)	Unit
V _{CEO}	Collector-Emitter Voltage	40	V
V _{CBO}	Collector-Base Voltage	60	V
V _{EBO}	Emitter-Base Voltage	6	V
I _C	Collector Current-Continuous	0.2	A
P _C	Collector Dissipation	0.2	W
R _{θJA}	Thermal Resistance Junction to Ambient	625	°C/W
T _J	Operating Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	°C

Symbol	Rating	Rating(PNP)	Unit
V _{CEO}	Collector-Emitter Voltage	-40	V
V _{CBO}	Collector-Base Voltage	-40	V
V _{EBO}	Emitter-Base Voltage	-5	V
I _C	Collector Current-Continuous	-0.2	A
P _C	Collector Dissipation	0.2	W
R _{θJA}	Thermal Resistance Junction to Ambient	625	°C/W
T _J	Operating Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	°C



E₁, B₁, C₁ = PNP3906 Section
 E₂, B₂, C₂ = NPN3904 Section

SOT-363



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.006	.014	0.15	0.35	
B	.045	.053	1.15	1.35	
C	.085	.096	2.15	2.45	
D	.026		0.65Nominal		
G	.047	.055	1.20	1.40	
H	.071	.087	1.80	2.20	
J	---	.004	---	0.10	
K	.035	.043	0.90	1.10	
L	.010	.018	0.26	0.46	
M	.003	.006	0.08	0.15	


NPN 3904 Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=1\text{mA}$, $I_B=0$)	40	---	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=10\mu\text{A}$, $I_E=0$)	60	---	---	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ($I_E=10\mu\text{A}$, $I_C=0$)	5	---	---	Vdc
I_{CBO}	Collector Cutoff Current ($V_{CB}=30\text{Vdc}$, $I_E=0$)	---	---	50	nAdc
I_{CEO}	Collector Cutoff Current ($V_{CE}=30\text{Vdc}$, $I_B=0$)	---	---	500	nAdc
I_{EBO}	Emitter Cutoff Current ($V_{EB}=5\text{Vdc}$, $I_C=0$)	---	---	50	nAdc
h_{FE}	DC Current Gain ($I_C=0.1\text{mA}$, $V_{CE}=1\text{Vdc}$) ($I_C=1\text{mA}$, $V_{CE}=1\text{Vdc}$) ($I_C=10\text{mA}$, $V_{CE}=1\text{Vdc}$) ($I_C=50\text{mA}$, $V_{CE}=1\text{Vdc}$) ($I_C=100\text{mA}$, $V_{CE}=1\text{Vdc}$)	40 70 100 60 30	---	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=10\text{mA}$, $I_B=1\text{mA}$) ($I_C=50\text{mA}$, $I_B=5\text{mA}$)	---	---	0.2 0.3	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=10\text{mA}$, $I_B=1\text{mA}$) ($I_C=50\text{mA}$, $I_B=5\text{mA}$)	0.65 ---	---	0.85 0.95	Vdc
f_T	Current Gain-Bandwidth Product ($V_{CE}=20\text{Vdc}$, $I_C=20\text{mA}$, $f=100\text{MHz}$)	300	---	---	MHz
C_{ob}	Output Capacitance ($V_{CB}=5\text{Vdc}$, $f=1.0\text{MHz}$, $I_E=0$)	---	---	4	pF
NF	Noise Figure ($V_{CE}=5\text{V}$, $I_C=0.1\text{mA}$, $f=1\text{KHz}$, $R_S=1\text{k}\Omega$)	---	---	5	dB
t_d	Delay Time	$V_{CC}=3\text{V}$, $I_C=10\text{mA}$, $V_{BE}=0.5\text{V}$, $I_{B1}=1\text{mA}$		35	ns
t_r	Rise Time			35	ns
t_s	Storage Time			200	ns
t_f	Fall Time			50	ns


PNP 3906 Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=-1\text{mA}$, $I_B=0$)	-40	---	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=-10\mu\text{A}$, $I_E=0$)	-40	---	---	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ($I_E=-10\mu\text{A}$, $I_C=0$)	-5	---	---	Vdc
I_{CBO}	Collector Cutoff Current ($V_{CB}=-30\text{Vdc}$, $I_E=0$)	---	---	-50	nAdc
I_{EBO}	Emitter Cutoff Current ($V_{EB}=-5\text{Vdc}$, $I_C=0$)	---	---	-50	nAdc
h_{FE}	DC Current Gain ($I_C=-0.1\text{mA}$, $V_{CE}=-1\text{Vdc}$)	40	---	---	---
	($I_C=-1\text{mA}$, $V_{CE}=-1\text{Vdc}$)	70	---	---	
	($I_C=-10\text{mA}$, $V_{CE}=-1\text{Vdc}$)	100	---	300	
	($I_C=-50\text{mA}$, $V_{CE}=-1\text{Vdc}$)	60	---	---	
	($I_C=-100\text{mA}$, $V_{CE}=-1\text{Vdc}$)	30	---	---	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=-10\text{mA}$, $I_B=-1\text{mA}$) ($I_C=-50\text{mA}$, $I_B=-5\text{mA}$)	---	---	-0.25	Vdc
		---	---	-0.4	
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=-10\text{mA}$, $I_B=-1\text{mA}$) ($I_C=-50\text{mA}$, $I_B=-5\text{mA}$)	-0.65	---	-0.85	Vdc
		---	---	-0.95	
f_T	Current Gain-Bandwidth Product ($V_{CE}=-20\text{Vdc}$, $I_C=-10\text{mA}$, $f=100\text{MHz}$)	250	---	---	MHz
C_{ob}	Output Capacitance ($V_{CB}=-5\text{Vdc}$, $f=1.0\text{MHz}$, $I_E=0$)	---	---	4.5	pF
NF	Noise Figure ($V_{CE}=-5\text{V}$, $I_C=-0.1\text{mA}$, $f=1\text{KHz}$, $R_S=1\text{k}\Omega$)	---	---	4	dB
t_d	Delay Time	---	---	35	ns
t_r	Rise Time			35	ns
t_s	Storage Time	---	---	225	ns
t_f	Fall Time			75	ns


MMDT3946




T_A , AMBIENT TEMPERATURE (°C)
Fig. 1, Max Power Dissipation vs Ambient Temperature (Total Device)




V_{CB} , COLLECTOR-BASE VOLTAGE (V)
Fig. 2, Input and Output Capacitance vs. Collector-Base Voltage (NPN-3904)




I_C , COLLECTOR CURRENT (mA)
Fig. 3, Typical DC Current Gain vs Collector Current (NPN-3904)



I_C , COLLECTOR CURRENT (mA)
Fig. 4, Typical Collector-Emitter Saturation Voltage vs. Collector Current (NPN-3904)



I_C , COLLECTOR CURRENT (mA)
Fig. 5, Typical Base-Emitter Saturation Voltage vs. Collector Current (NPN-3904)



V_{CB} , COLLECTOR-BASE VOLTAGE (V)
Fig. 6, Input and Output Capacitance vs. Collector-Base Voltage (PNP-3906)




Fig. 7, Typical DC Current Gain vs Collector Current (PNP-3906)




Fig. 8, Typical Collector-Emitter Saturation Voltage vs. Collector Current (PNP-3906)




Fig. 9, Typical Base-Emitter Saturation Voltage vs. Collector Current (PNP-3906)



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 3Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.