

# 0.36" Single Digit Display

## FEATURES


- 0.36" digit height
- Right hand decimal point
- Additional colors/materials available

## OPTO-ELECTRICAL CHARACTERISTICS (Ta = 25°C)

PART NO.	PEAK WAVE LENGTH (nm)	EMITTED COLOR	FACE COLORS		MAXIMUM RATINGS			OPTO-ELECTRICAL CHARACTERISTICS						PIN-OUT	
			SURFACE COLOR	EPOXY COLOR	IF (mA)	VR (V)	PD (mW)	VF(V)			IR(μA)		IV(μcd)		
								typ.	max.	@mA	max.	@VR	typ. per seg.		@mA
MTN2136-AG	567	Green	Grey	White	30	5	85	2.1	3.0	20	100	5	2300	10	1
MTN4136-AO	635	Orange	Grey	White	30	5	85	2.1	3.0	20	100	5	2600	10	1
MTN4136-AHR	635	Hi-Eff Red	Red	Red	30	5	85	2.1	3.0	20	100	5	2600	10	1
MTN7136M-11A	660	Ultra Red	Black	White	30	4	70	1.7	2.2	20	100	4	13700	20	1
MTN2136-CG	567	Green	Grey	White	30	5	85	2.1	3.0	20	100	5	2300	10	2
MTN4136-CO	635	Orange	Grey	White	30	5	85	2.1	3.0	20	100	5	2600	10	2
MTN4136-CHR	635	Hi-Eff Red	Red	Red	30	5	85	2.1	3.0	20	100	5	2600	10	2
MTN7136M-11C	660	Ultra Red	Black	White	30	4	70	1.7	2.2	20	100	4	13700	20	2

Operating Temperature: -25~+85, Storage Temperature: -25~+100. Other face/epoxy colors are available.

## PACKAGE DIMENSIONS AND PIN FUNCTIONS



### PINOUT 1

COMMON ANODE  
PIN NO. FUNCTION

1. COMMON ANODE
2. CATHODE F
3. CATHODE G
4. CATHODE E
5. CATHODE D
6. COMMON ANODE
7. CATHODE DP
8. CATHODE C
9. CATHODE B
10. CATHODE A

### PINOUT 2

COMMON CATHODE  
PIN NO. FUNCTION

1. COMMON CATHODE
2. ANODE F
3. ANODE G
4. ANODE E
5. ANODE D
6. COMMON CATHODE
7. ANODE DP
8. ANODE C
9. ANODE B
10. ANODE A

1. ALL DIMENSIONS ARE IN mm, TOLERANCE IS  $\pm 0.25$ mm UNLESS OTHERWISE SPECIFIED.
2. THE SLOPE ANGLE OF ANY PIN MAY BE  $\pm 5.0^\circ$  MAX.



120 Broadway • Menands, New York 12204  
Toll Free: (800) 98-4LEDS • Fax: (518) 432-7454

For up-to-date product info visit our web site at [www.marktechopto.com](http://www.marktechopto.com)

All specifications subject to change.