

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.

TELEPHONE: (973) 376-2922
 (212) 227-6005
 FAX: (973) 376-8960

MUR105 MUR150
MUR110 MUR160
MUR115 MUR170
MUR120 MUR180
MUR130 MUR190
MUR140 MUR1100



SWITCHMODE POWER RECTIFIERS

... designed for use in switching power supplies, inverters and as free wheeling diodes, these state-of-the-art devices have the following features:

- Ultrafast 25, 50 and 75 Nanosecond Recovery Times
- 175°C Operating Junction Temperature
- Low Forward Voltage
- Low Leakage Current
- High Temperature Glass Passivated Junction
- Reverse Voltage to 1000 Volts

ULTRAFAST RECTIFIERS

1.0 AMPERE
50-1000 VOLTS



PLASTIC PACKAGE

MAXIMUM RATINGS

Rating	Symbol	MUR										Unit		
		105	110	115	120	130	140	150	160	170	180		190	1100
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V _{RRM} V _{RWM} V _R	50	100	150	200	300	400	500	600	700	800	900	1000	Volts
Average Rectified Forward Current (Square Wave Mounting Method #3 Per Note 1)	I _{F(AV)}	1.0 @ T _A = 130°C			1.0 @ T _A = 120°C				1.0 @ T _A = 95°C				Amps	
Nonrepetitive Peak Surge Current (Surge applied at rated load conditions, halfwave, single phase, 60 Hz)	I _{FSM}	35										Amps		
Operating Junction Temperature and Storage Temperature	T _J , T _{stg}	-65 to +175										°C		

THERMAL CHARACTERISTICS

Maximum Thermal Resistance, Junction to Ambient	R _{θJA}	See Note 1	°C/W
---	------------------	------------	------

ELECTRICAL CHARACTERISTICS

Maximum Instantaneous Forward Voltage (1) (I _F = 1.0 Amp, T _J = 150°C) (I _F = 1.0 Amp, T _J = 25°C)	V _F	0.710 0.875	1.05 1.25	1.50 1.75	Volts
Maximum Instantaneous Reverse Current (1) (Rated dc Voltage, T _J = 150°C) (Rated dc Voltage, T _J = 25°C)	I _R	50 2.0	150 5.0	600 10	µA
Maximum Reverse Recovery Time (I _F = 1.0 Amp, di/dt = 50 Amp/µs) (I _F = 0.5 Amp, I _R = 1.0 Amp, I _{REC} = 0.25 A)	t _{rr}	35 25	75 50	100 75	ns
Maximum Forward Recovery Time (I _F = 1.0 A, di/dt = 100 A/µs, I _{REC} to 1.0 V)	t _{fr}	25	50	75	ns