

Features:

- CMOS Technology
- TTL/CMOS compatible inputs
- Low switching noise
- 5nS typical true / complement output skew
- 5nS typical output rise and fall times
- Up to 20V output voltage
- Output high voltage programmable via V_{OPT}
- Output low voltage programmable via V_{EE}

Applications

- Digital control of analog circuits
- Level shifting and amplification
- Circuit applications requiring complementary signal generation with low skew
- Bias control for PIN diode drivers in a microwave switch

General Description

The MX856 and MX857 are high speed single channel level shifters with complimentary output drivers. The MX856 features a 5.0V V_{CC} positive supply, and the MX857 features a 3.3V V_{CC} positive supply.

The input buffers accept digital TTL or CMOS level signals, amplifies them to the V_{CC} and GND supply rails, and generates complementary outputs. The translator level shifts these output signals by amplifying them to the V_{CC} and V_{EE} supply rails.

The output drivers then buffer the signals to V_{OPT} and V_{EE} . V_{OPT} may be set within the range of V_{CC} and GND. The output drivers also adjust the complimentary signals for minimized skew error.

The MX856 and MX857 are designed to operate over a temperature range of -40°C to $+85^{\circ}\text{C}$, and are available as die in wafer form, die in waaffle pack, 8 lead SOIC package, and SOIC on Tape and Reel.


Ordering Information – MX856

Part No.	Description
19202	MX856 Die / Wafer Form
19201	MX856 Die / Waffle Pack
19200-00	MX856 8 Lead SOIC
19241-00	MX856 SOIC on Tape & Reel


Ordering Information – MX857

Part No.	Description
19302	MX857 Die / Wafer Form
19301	MX857 Die / Waffle Pack
19300-00	MX857 8 Lead SOIC
19341-00	MX857 SOIC on Tape & Reel

Functional Block Diagram



8 Lead SOIC Configuration



Absolute Maximum Ratings

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{CC}	Positive DC Supply Voltage	-0.4	+6.0	V
V _{EE}	Negative DC Supply Voltage	-17.0	+0.4	V
V _{OPT}	Output Positive DC Supply Voltage		+6.0	V
V _{OPT} - V _{EE}	Output Positive to Negative Supply Voltage	-0.4	+20.0	V
V _{CC} - V _{EE}	Positive to Negative Supply Voltage	-0.4	+14.0	V
V _{CC} - V _{OPT}	Positive to Output Supply Voltage	-0.4	V _{CC} +0.4	V
V _{IN}	DC Input Voltage	-0.4	V _{CC} +0.4	V
I _{IN}	DC Input Current	-10	+10	μA
T _A	Ambient Operating Temperature	-40	+85	°C
T _{STG}	Storage Temperature	-65	+150	°C
ESD	ESD sensitivity (human body model)	1.0		kV

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and affect its reliability.

Guaranteed Operating Range

MX856 5.0V version

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{CC}	Positive DC Supply Voltage	3.0	5.5	V
V _{EE}	Negative DC Supply Voltage	-15.0	-4.5	V
V _{OPT}	Output Positive DC Supply Voltage	0.0	5.5	V
V _{OPT} - V _{EE}	Output Positive to Negative Supply Voltage	7.5	20.0	V
V _{CC} - V _{EE}	Positive to Negative Supply Voltage	7.5	20.0	V
V _{CC} - V _{OPT}	Positive to Output Supply Voltage	0.0	V _{CC}	V
T _A	Ambient Operating Temperature	-40	+85	°C
T _R , T _F	Input Rise and Fall Time	0.0	500	nS

MX857B 3.3V version

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{CC}	Positive DC Supply Voltage	3.0	3.6	V
V _{EE}	Negative DC Supply Voltage	-17.0	-4.5	V
V _{OPT}	Output Positive DC Supply Voltage	0.0	3.6	V
V _{OPT} - V _{EE}	Output Positive to Negative Supply Voltage	7.5	20.0	V
V _{CC} - V _{EE}	Positive to Negative Supply Voltage	7.5	20.0	V
V _{CC} - V _{OPT}	Positive to Output Supply Voltage	0.0	V _{CC}	V
T _A	Ambient Operating Temperature	-40	+85	°C
T _R , T _F	Input Rise and Fall Time	0.0	500	nS

DC Characteristics - Over Guaranteed Operating Range

SYMBOL	PARAMETER	MIN	TYP	MAX	Units
V _{IH}	Input HIGH Voltage	2.0			V
V _{IL}	Input LOW Voltage			0.8	V
V _{OH}	Output HIGH Voltage (I _{OH} =-1mA)	V _{OPT} - 0.1			V
V _{OL}	Output LOW Voltage (I _{OL} =1mA)			V _{EE} + 0.1	V
I _{IN}	Input Current (V _{IN} =0.0 to V _{CC})	-10		+10	uA
I _{CC}	Supply Current (V _{IN} =0.0 or V _{CC})	V _{CC} = 3.3V	<1.0		uA
		V _{CC} = 5.0V	<1.0		uA
I _{EE}	Supply Current (V _{IN} =0.0 or V _{CC})	V _{CC} = 3.3V	<1.0		uA
		V _{CC} = 5.0V	<1.0		uA
I _{OPT}	Supply Current (V _{IN} =0.0 or V _{CC})	V _{CC} = 3.3V	<1.0		uA
		V _{CC} = 5.0V	<1.0		uA

ESD Warning


ESD (electrostatic discharge) sensitive device. Electrostatic charges can readily accumulate on test equipment and the human body in excess of 4000 Volts. This energy can discharge without detection. Although the MX856 / MX857 feature proprietary ESD protection circuitry, permanent damage may be sustained if subjected to high energy electrostatic discharges. Proper ESD precautions are recommended to avoid performance degradation or loss of functionality.

AC Characteristics

$V_{CC}=V_{OPT}=3.3V$, $V_{EE}=-16.7V$ or $-4.5V$, Input rise and fall time 6ns, $V_{IH}=3.1$, $V_{IL}=0.2V$, $T_A = -40^{\circ}C$ to $+85^{\circ}C$
 $V_{CC}=V_{OPT}=5.0V$, $V_{EE}=-15.0V$ or $-4.5V$, Input rise and fall time 6ns, $V_{IH}=4.8$, $V_{IL}=0.2V$, $T_A = -40^{\circ}C$ to $+85^{\circ}C$

SYMBOL	PARAMETER		Typ	Max	UNITS
T _{PLH}	Propagation Delay (low to high input)	V _{CC} = 3.3V	22	29	nS
		V _{CC} = 5.0V	24	29	nS
T _{PHL}	Propagation Delay (high to low input)	V _{CC} = 3.3V	20	29	nS
		V _{CC} = 5.0V	20	29	nS
T _{TLH}	Output Rise Time (C _{LD} =10pf)	V _{CC} = 3.3V	5	9	nS
		V _{CC} = 5.0V	4	9	nS
T _{THL}	Output Fall Time (C _{LD} =10pf)	V _{CC} = 3.3V	5	8	nS
		V _{CC} = 5.0V	4	8	nS
T _{SKREW}	Delay Skew (Output A to Output B)	V _{CC} = 3.3V	5	10	nS
		V _{CC} = 5.0V	5	10	nS
C _{IN}	Input Capacitance			15	pF


Note: Production Tested at 25°C



Pad Locations (in μm)

PAD NAME	X	Y
OUT	89.1	556.4
OUT_B	489.1	556.4
GND	579.1	306.3
V _{OPT}	579.3	126.8
V _{EE}	406	0
IN	165.4	0
V _{CC}	0	74.3
GND	49.9	306.3

Pad location is the pad center point in microns. The origin of the coordinates is located as shown.




Die Size: 1095 μm X 930 μm
(Not Drawn To Scale)

8 Lead SOIC – I/O Assignment

Pin No.	Pin Name	Description
1	OUT	Output Driver
2	GND	Ground
3	V _{CC}	Positive Supply for Input Buffer
4	IN	Input Buffer
5	V _{EE}	Negative Supply for Output Driver
6	V _{OPT}	Positive Supply for Output Driver
7	GND	Ground
8	OUT_B	Complimentary Output Driver

8-LEAD SOIC



DIM.	DIMENSIONS ①				NOTE
	INCH		MM.		
	MIN.	MAX.	MIN.	MAX.	
A	.0532	.0688	1.35	1.75	----
A1	.0040	.0098	.10	.25	----
B	.013	.020	.33	.51	----
C	.0075	.0098	.19	.25	----
D	.1890	.1968	4.80	5.00	②
E	.1497	.1574	3.80	4.00	②
F	.050	BSC	1.27	BSC	----
H	.2284	.2440	5.80	6.20	----
J	.0099	.0196	.25	.50	----
K	0°	8°	0°	8°	----
L	.016	.050	.40	1.27	----

3. MOLDED PACKAGE SHALL CONFORM TO JEDEC STANDARD CONFIGURATION MS-012 VARIATION AA.

② DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSIONS.

① CONTROLLING DIMENSIONS: MILLIMETERS.

NOTES: (UNLESS OTHERWISE SPECIFIED)

Micronix, Inc makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Micronix's Standard Terms and Conditions of Sale, Micronix, Inc. assumes no liability whatsoever, and disclaims any expressed or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

Micronix

145 Columbia
Aliso Viejo, CA 92656-1490
Tel: 1-949-831-4622
Fax: 1-949-831-4628

SALES OFFICES AMERICAS

Eastern Region

[Eastern North America, Mexico, South America]
IXYS Corporation
Beverly, MA
Tel: 508-528-6883
Fax: 508-528-4562
wgh@ixys.net

Central Region

[Central North America]
IXYS Corporation
Greensburg, PA
Tel: 724-836-8530
Fax: 724-836-8540
neil.lejeune@westcode.com

Western Region

[Western North America]
IXYS Coporation
Solana Beach, CA
Tel: 858-792-1101
slodor@ix.netcom.com

SALES OFFICES EUROPE

European Headquarters

IXYS Semiconductor GMBH
Edisonstrasse 15
D- 68623 Lampertheim
Germany
Tel : 49-6206-503203
Fax: 49-6206-503286
marcom@ixys.de

United Kingdom

IXYS Semiconductor Limited
Langley Park Way
Langley Park
Chippenham
Wiltshire SN 15 1GE - England
Tel: 0 1249-444524
Fax: 0044 0 1249-444524
sales@ixys.co.uk

Sales Offices ASIA / PACIFIC

Asian Headquarters

IXYS
Room 1016, Chia-Hsin, Bldg II,
10F, No. 96, Sec. 2
Chung Shan North Road
Taipei, Taiwan R.O.C.
Tel: 886-2-2523-6368
Fax: 886-2-2523-6368
bradley.green@ixys.co.uk
Jhong@clare.com

<http://www.claremicronix.com>

Micronix cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in this Micronix product. No circuit patent licenses nor indemnity are expressed or implied. Micronix reserves the right to change the specification and circuitry, without notice at any time. The products described in this document are not intended for use in medical implantation or other direct life support applications where malfunction may result in direct physical harm, injury or death to a person.

Specification: MX856 / MX857
©Copyright 2006, Micronix, Inc.
All rights reserved. Printed in USA.