

20Watts Single Output Power Supply

NAD-200X series

Feature:

- 90 to 264Vac universal input range.
- UL, CSA, TUV safety approval.
- EMI/RFI meet VDE & FCC limit B.
- Low cost & compact size.
- 20Watts in 110×60×25mm Size.
- 2 Year Warranty.

Specifications: typical at nominal line, full load at 25°C.

Input Specifications:	General Specifications:
Input voltage: 90 to 264Vac	Efficiency: 70% typical at full load
Input Frequency: 47 Hz to 440Hz	Hold-up time: 15ms @ 110Vac full load
Input inrush current: 10A at 115Vac 20A at 230Vac	EMI/RFI: VDE & FCC Class B limits
Earth leakage: 0.2mA max @ 110VAC 0.4mA max @ 230VAC	Dielectric Withstand: Input/output: 3000VAC Input/Ground: 1500VAC
Output Specifications:	Safety Approval: UL UL1950 CSA 22.2-234/950 TUV EN60950
Output Rating: See Rating Charts	
Line Regulation: ±1% max	Switching frequency: 20Khz
Load Regulation: ±1% max.	Weight: 150g(5.3Oz)
Transient Response: ±1% max dev. (Full to half load) 500uSec recovery	MTBF: 100,000hours(MIL-HDBK-217F)
	Environmental Specifications:
Temperature Coefficient: ±0.02% /°C	Operating temperature: 0 to +50°C
Ripple & Noise: 1% P-P max	Storage temperature: -40 to +85°C
Protections: a. Over current protection b. Over voltage protection c. Over power protection d. Short circuit protection	Humidity: 5 to 95 % RH non-condensing
	Vibration: 2.4G , 5 to 500Hz
	Cooling: Free air convection

Note:

1. Vibration test: Three orthogonal axes, random vibration, 10 minutes for each axis.

20Watts Single Output Power Supply


NAD-200X series

Model No.	Output Voltage	Output Current Minimum	Output Current Maximum	Max. Power
NAD-2001	5V	0mA	4000mA	20W
NAD-2002	12V	0mA	1600mA	20W
NAD-2003	15V	0mA	1300mA	20W
NAD-2004	24V	0mA	800mA	20W
NAD-2005	3.3V	0mA	6000mA	20W

Note:

Other output voltage versions available. Consult factory for details.

Dimensions: mm±0.5mm



PIN	Function	PIN	Function
1	Vo1	3	COM
2	Vo1	4	COM

- AC mating connector is :LEOCO p/n 3941P03
- DC mating connector is : LEOCO p/n 3986P04