



## Model Number

NCB5-18GM40-Z0-3G-3D

## Features

- Comfort series
- ATEX-approval for zone 2 and zone 22

## Accessories

### BF 18

Mounting flange, 18 mm

### EXG-18

Quick mounting bracket with dead stop

## Technical Data

### General specifications

Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	$s_n$	5 mm
Installation		flush
Output polarity		DC
Assured operating distance	$s_a$	0 ... 4.05 mm
Actual operating distance	$s_r$	4.5 ... 5.5 mm typ. 5 mm
Reduction factor $r_{AI}$		0.37
Reduction factor $r_{Cu}$		0.33
Reduction factor $r_{304}$		0.7
Output type		2-wire

### Nominal ratings

Operating voltage	$U_B$	5 ... 60 V
Switching frequency	$f$	0 ... 350 Hz
Hysteresis	$H$	1 ... 10 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 5$ V
Operating current	$I_L$	2 ... 100 mA
Lowest operating current	$I_m$	2 mA
Off-state current	$I_r$	0 ... 0.5 mA typ.
Switching state indicator		all direction LED, yellow

### Functional safety related parameters

MTTF <sub>d</sub>	1739 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

### Mechanical specifications

Connection type	cable PVC , 2 m
Cable version	PA
Core cross-section	0.34 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Degree of protection	IP66 / IP67
Cable	
Cable diameter	4.8 mm $\pm$ 0.2 mm
Bending radius	> 10 x cable diameter

### General information

Use in the hazardous area	see instruction manuals
Category	3G; 3D


### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012


### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Certified by China Compulsory Certification (CCC)

## Dimensions



## Electrical Connection



## Equipment protection level Gc (nA)

Certificate	PF 15CERT3754 X
CE marking	CE

ATEX marking	II 3G Ex nA IIC T6 Gc The Ex-related marking can also be printed on the enclosed label.
--------------	--

Standards	EN 60079-0:2012+A11:2013, EN 60079-15:2010 Ignition protection category "n" Use is restricted to the following stated conditions
-----------	--

## Special conditions

Maximum operating current $I_L$	The maximum permissible load current must be restricted to the values given in the following list. High load currents and load short-circuits are not permitted.
Maximum operating voltage $U_{Bmax}$	The maximum permissible operating voltage $U_{Bmax}$ is restricted to the values in the following list. Tolerances are not permissible.
Maximum permissible ambient temperature $T_{Umax}$	dependant of the load current $I_L$ and the max. operating voltage $U_{Bmax}$ Information can be taken from the following list.
at $U_{Bmax}=60\text{ V}$ , $I_L=100\text{ mA}$	50 °C (122 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=50\text{ mA}$	56 °C (132.8 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=25\text{ mA}$	60 °C (140 °F)

## Equipment protection level Dc (tc)

CE marking	CE
------------	----

ATEX marking	II 3D Ex tc IIIC T80°C Dc The Ex-related marking can also be printed on the enclosed label.
--------------	--

Standards	EN 60079-0:2012+A11:2013, EN 60079-31:2014 Protection by enclosure "tc" Some of the information in this instruction manual is more specific than the information provided in the datasheet.
-----------	--

General	The corresponding datasheets, declarations of conformity, EC-type examination certificates, certifications, and control drawings, where applicable (see datasheets), form an integral part of this document. These documents can be found at <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> . The maximum surface temperature of the device was determined without a layer of dust on the apparatus. Some of the information in this instruction manual is more specific than the information provided in the datasheet.
---------	--

## Special conditions

Maximum permissible ambient temperature $T_{Umax}$	dependant of the load current $I_L$ and the max. operating voltage $U_{Bmax}$ Information can be taken from the following list.
at $U_{Bmax}=60\text{ V}$ , $I_L=100\text{ mA}$	50 °C (122 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=50\text{ mA}$	56 °C (132.8 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=25\text{ mA}$	60 °C (140 °F)

## Equipment protection level Dc (tD)

General	The apparatus has to be operated according to the appropriate data in the data sheet and in this instruction manual. The maximum surface temperature has been determined in accordance with method A without a dust layer on the equipment. The data stated in the data sheet are restricted by this operating instruction! The special conditions must be adhered to!
---------	--

## Special conditions

Maximum permissible ambient temperature $T_{Umax}$	dependant of the load current $I_L$ and the max. operating voltage $U_{Bmax}$ Information can be taken from the following list.
at $U_{Bmax}=60\text{ V}$ , $I_L=100\text{ mA}$	50 °C (122 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=50\text{ mA}$	56 °C (132.8 °F)
at $U_{Bmax}=60\text{ V}$ , $I_L=25\text{ mA}$	60 °C (140 °F)