



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE7025 Integrated Circuit Module, Switching Regulator Power Supply

Features:

- Switching regulator power IC
- Single-package, selectorless regulated power supply applicable to a wide range of line voltages from 0 to 280VAC
- The oscillation circuit is of a self-oscillation type.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

AC Input Voltage, V_{AC}	0 to 280V _{rms}
Maximum Output Power (85 to 280VAC), P_{Omax}	80W
Operating Temperature Range, T_{opg}	-10° to +65°C
Storage Temperature Range, T_{stg}	-30° to +105°C
Operating Case Temperature, T_{Cmax}	+105°C
Thermal Resistance, Junction-to-Case, R_{thJC}	1.6°C/W
Maximum Junction Temperature, T_{Jmax}	+150°C

Operating Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Min	Typ	Max	Unit
Output Voltage Setting	$V_{AC} = 200V, I_O = 0.3A$	114	115	116	V
Line Regulation	$V_{AC} = 170 \text{ to } 280V, I_O = 0.5A$	-	0.4	1.0	V
Load Regulation	$V_{AC} = 200V, I_O = 0.3 \text{ to } 0.7A$	-	1.0	2.0	V
Input Power	$V_{AC} = 200V, I_O = 0.7A$	-	102	105	W
Output Ripple Voltage	$V_{AC} = 200V, I_O = 0.7A$	-	0.4	0.6	V _{p-p}
Temperature Coefficient	$V_{AC} = 200V, I_O = 0.7A$	-	7	-	mV/°C
Light Load Characteristic	$V_{AC} = 200V, R_L = 4.7k\Omega$	-	125	135	V

