


OPB703W/OPB704W/OPB705W

PACKAGE DIMENSIONS



FUNCTION	WIRE COLOR
(C) COLLECTOR	WHITE
(E) EMITTER	BLUE
(K) CATHODE	GREEN
(A) ANODE	ORANGE

NOTES

1. DIMENSIONS ARE IN INCHES (mm).
 2. TOLERANCE IS ± 0.10 (.25)
- OPB703W - IR TRANSPARENT DUST COVER
 OPB704W - IR TRANSPARENT DUST COVER
 OPB705W - OFFSET LENS

DESCRIPTION

The OPB703W, OPB704W, and OPB705W consist of an infrared emitting diode and an NPN silicon phototransistor mounted side by side on a converging optical axis in a black plastic housing. The phototransistor responds to radiation from the emitting diode only when a reflective object passes within its field of view. The area of the optimum response approximates a circle .200" in diameter. Leads are 26 AWG, PVC insulation, 4.5" (114.3 mm) minimum length, stripped and tinned.

FEATURES

- Phototransistor output.
- High Sensitivity.
- Low cost plastic housing.
- Pre wired with 4.5 inch, 26 gauge leads.
- OPB703W/OPB704W, dust cover; lens.
- OBP705W, offset lens.

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)	
Storage Temperature	-40°C to $+85^\circ\text{C}$
Operating Temperature	-40°C to $+85^\circ\text{C}$
Soldering:	
Lead Temperature (Iron)	240°C for 5 sec. ^(2,3,4)
Lead Temperature (Flow)	260°C for 10 sec. ^(2,3)
INPUT DIODE	
Continuous Forward Current	50 mA
Reverse Voltage	5.0 Volts
Power Dissipation	100 mW ⁽¹⁾
OUTPUT TRANSISTOR	
Collector-Emitter Voltage	30 Volts
Emitter-Collector Voltage	5.0 Volts
Collector Current	25 mA
Power Dissipation	100 mW ⁽¹⁾

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)					
PARAMETER	SYMBOL	MIN.	MAX.	UNITS	TEST CONDITIONS
INPUT DIODE					
Forward Voltage	V_F	—	1.70	V	$I_F = 40\text{ mA}$
Reverse Leakage Current	I_R	—	100	μA	$V_R = 2.0\text{ V}$
OUTPUT TRANSISTOR					
Emitter-Collector Breakdown	BV_{ECO}	5	—	V	$I_E = 100\ \mu\text{A}$, $E_e = 0$
Collector-Emitter Breakdown	BV_{CEO}	30	—	V	$I_C = 100\ \mu\text{A}$, $E_e = 0$
Collector-Emitter Leakage	I_{CEO}	—	100	nA	$V_{CE} = 10.0\text{ V}$, $E_e = 0$
COUPLED					
On-State Collector Current					
OPB703W	$I_{C(ON)}$	200	—	μA	$I_F = 40\text{ mA}$, $V_{CE} = 5\text{ V}$, $D = .150''$ ^(5,6)
OPB704W	$I_{C(ON)}$	200	—	μA	$I_F = 40\text{ mA}$, $V_{CE} = 5\text{ V}$, $D = .150''$ ^(5,6)
OPB705W	$I_{C(ON)}$	100	—	μA	$I_F = 40\text{ mA}$, $V_{CE} = 5\text{ V}$, $D = .150''$ ^(5,6)
Crosstalk	I_{CX}	—	20	μA	$I_F = 40\text{ mA}$, $V_{CE} = 5\text{ V}$ ⁽⁷⁾

NOTES
1. Derate power dissipation linearly 1.67 mW/ $^\circ\text{C}$ above 25°C .
2. RMA flux is recommended.
3. Methanol or Isopropyl alcohols are recommended as cleaning agents.
4. Soldering iron tip $1/16''$ (1.6 mm) from housing.
5. D is the distance from the assembly face to the reflective surface.
6. Measured using Eastman Kodak neutral test card with 90% diffused reflecting surface.
7. Cross talk is the photocurrent measured with current to the input diode and no reflective surface.



REFLECTIVE OBJECT SENSOR

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.