


RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free

FEATURES

- Low cost construction
- Low forward voltage drop
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
 250 °C/10 second, at terminals

R - 6



Dimensions in inches and (millimeters)

MECHANICAL DATA

- Case: transfer molded plastic
- Polarity: Color band denotes cathode end
- Mounting position: Any
- Weight: 0.07ounces, 2.0 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.
 Single phase half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOLS	P10A05	P10A1	P10A2	P10A4	P10A6	P10A8	P10A10	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current @ $T_L=75^\circ C$	$I_{(AV)}$	10.0							Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	400							Amps
Maximum Instantaneous Forward Voltage Drop per bridge element at 10A	V_F	1.0							Volts
Maximum DC Reverse Current at rated DC blocking voltage	$T_J=25^\circ C$	10							μA
	$T_J=100^\circ C$	100							
Typical Junction Capacitance (Note 2)	C_J	200							pF
Operating and Storage Temperature Range	T_J	-65 to +175							$^\circ C$
Storage Temperature Range	T_{STG}	-65 to +175							$^\circ C$

NOTES:

1. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts.

RATINGS AND CHARACTERISTIC CURVES (P10A05 THRU P10A10)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

