

## SWITCHING REGULATOR CONTROL CIRCUIT

### DESCRIPTION

The μPC494 is an inverter control unit which provides all the control circuitry for PWM type switching regulators. Included in this device is the voltage reference, dual error amplifiers, oscillator, pulse width modulator, pulse steering flip flop, dual alternating output switches and dead-time control.


### FEATURES

- Complete PWM power control circuit.
- Adjustable dead-time (0 to 100%).
- No double pulsing of same output during load transient condition.
- Dual error amplifiers have wide common mode input voltage capability (−0.3 V to  $V_{CC}-2$  V).
- Circuit architecture provides easy synchronization.
- Uncommitted outputs for 250-mA sink or source.
- With miss-operation prevention circuit for low level supply voltage.
- Full pin-compatible TL494C.

### ★ ORDERING INFORMATION


Part Number	Package
μPC494C	16-pin plastic DIP (7.62 mm (300))
μPC494G	16-pin plastic SOP (9.53 mm (375))
μPC494GS	16-pin plastic SOP (7.62 mm (300))

### ★ PIN CONFIGURATION (Top View)



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version. Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.

BLOCK DIAGRAM



★ **ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25°C, unless otherwise noted)**

Characteristics	Symbol	μPC494C	μPC494G	μPC494GS	Unit
Supply Voltage	V <sub>CC</sub>	-0.3 to +41	-0.3 to +41	-0.3 to +41	V
Error Amplifier Input Voltage	V <sub>ICM</sub>	-0.3 to V <sub>CC</sub> + 0.3	-0.3 to V <sub>CC</sub> + 0.3	-0.3 to V <sub>CC</sub> + 0.3	V
Output Voltage	V <sub>CER</sub>	-0.3 to +41	-0.3 to +41	-0.3 to +41	V
Output Current	I <sub>C</sub>	250	250	250	mA
Total Power Dissipation	P <sub>T</sub>	1000	780 <sup>Note</sup>	650 <sup>Note</sup>	mW
Operating Ambient Temperature	T <sub>A</sub>	-20 to +85	-20 to +85	-20 to +85	°C
Storage Temperature	T <sub>stg</sub>	-65 to +150	-65 to +150	-65 to +150	°C

**Note** With 25 cm<sup>2</sup> x 1.6 mm glass-epoxy substrate.

- ★ **Caution** Product quality may suffer if the absolute maximum rating is exceeded even momentarily for any parameter. That is, the absolute maximum ratings are rated values at which the product is on the verge of suffering physical damage, and therefore the product must be used under conditions that ensure that the absolute maximum ratings are not exceeded.

**RECOMMENDED OPERATING CONDITIONS**

Characteristics	Symbol	MIN.	TYP.	MAX.	Unit
Supply Voltage	V <sub>CC</sub>	7		40	V
Output Voltage	V <sub>CER</sub>	-0.3		40	V
Output Current	I <sub>C</sub>			200	mA
Error Amplifier Sink Current	I <sub>OAMP</sub>			-0.3	mA
Timing Capacitor	C <sub>T</sub>	0.47		10000	nF
Timing Resistance	R <sub>T</sub>	1.8		500	kΩ
Oscillation Frequency	f <sub>OSC</sub>	1		300	kHz
Operating Temperature	T <sub>opt</sub>	-20		+70	°C

- ★ **Caution** The recommended operating range may be exceeded without causing any problems provided that the absolute maximum ratings are not exceeded. However, if the device is operated in a way that exceeds the recommended operating conditions, the margin between the actual conditions of use and the absolute maximum ratings is small, and therefore thorough evaluation is necessary. The recommended operating conditions do not imply that the device can be used with all values at their maximum values.

★ ELECTRICAL SPECIFICATIONS (V<sub>CC</sub> = 15 V, f = 10 kHz, -20 ≤ T<sub>A</sub> ≤ +70°C, unless otherwise noted)

(1/2)

Block	Characteristics		Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Reference Section	Output Voltage		V <sub>REF</sub>	I <sub>REF</sub> = 1 mA, T <sub>A</sub> = 25°C	4.75	5	5.25	V
	Line Regulation		REG <sub>IN</sub>	7 V ≤ V <sub>CC</sub> ≤ 40 V, I <sub>REF</sub> = 1 mA, T <sub>A</sub> = 25°C		8	25	mV
	Load Regulation		REG <sub>L</sub>	1 mA ≤ I <sub>REF</sub> ≤ 10 mA, T <sub>A</sub> = 25°C		1	15	mV
	Temperature Coefficient		ΔV <sub>REF</sub> / ΔT	-20°C ≤ T <sub>A</sub> ≤ +85°C, I <sub>REF</sub> = 1 mA		0.01	0.03	%/°C
	Short Circuit Output Current <sup>Note1</sup>		I <sub>SHORT</sub>	V <sub>REF</sub> = 0 V		50		mA
Oscillator Section	Frequency		f <sub>OSC</sub>	C <sub>T</sub> = 0.01 μF, R <sub>T</sub> = 12 kΩ, T <sub>A</sub> = 25°C		10		kHz
	Standard Deviation of Frequency <sup>Note2</sup>			7 V ≤ V <sub>CC</sub> ≤ 40 V, T <sub>A</sub> = 25°C, C <sub>T</sub> , R <sub>T</sub> , const.		10		%
	Frequency Change with Temperature			0°C ≤ T <sub>A</sub> ≤ 70°C, C <sub>T</sub> = 0.01 μF, R <sub>T</sub> = 12 kΩ		1	2	%
	Frequency Change with Voltage			7 V ≤ V <sub>CC</sub> ≤ 40 V, T <sub>A</sub> = 25°C, C <sub>T</sub> = 0.01 μF, R <sub>T</sub> = 12 kΩ		1		%
Dead-Time Control Section	Input Bias Current			0 V ≤ V <sub>I</sub> ≤ 5.25 V		-2	-10	μA
	Maximum Duty Cycle (Each Output)			V <sub>I</sub> = 0 V	45	49		%
	Input Threshold Voltage 1		V <sub>TH1</sub>	Output pulse 0% duty cycle		3	3.3	V
	Input Threshold Voltage 2		V <sub>TH2</sub>	Output pulse maximum duty cycle	0			V
Error Amplifier Section	Input Offset Voltage		V <sub>IO</sub>	V <sub>OAMP</sub> = 2.5 V		2	10	mV
	Input Offset Current		I <sub>IO</sub>	V <sub>OAMP</sub> = 2.5 V		25	250	nA
	Input Bias Current			V <sub>OAMP</sub> = 2.5 V		0.2	1	μA
	Common Mode Input Voltage	Low	V <sub>ICM</sub>	7 V ≤ V <sub>CC</sub> ≤ 40 V	-0.3			V
		High			V <sub>CC</sub> -2			
	Open Loop Voltage Amplification		A <sub>V</sub>	V <sub>OAMP</sub> = 0.5 to 3.5 V, T <sub>A</sub> = 25°C	60	80		dB
	Unity Gain Bandwidth			T <sub>A</sub> = 25°C	500	830		kHz
	Common Mode Rejection Ratio		CMR	V <sub>CC</sub> = 40 V, T <sub>A</sub> = 25°C	65	80		dB
	Output Sink Current			V <sub>OAMP</sub> = 0.7 V	0.3	0.7		mA
Output Source Current			V <sub>OAMP</sub> = 3.5 V	-2	-10		mA	
PWM Section	Input Threshold Voltage (3-pin)			Output pulse 0% duty cycle, see <b>Figure 1</b> .		4	4.5	V
	Input Sink Current			V <sub>(pin 3)</sub> = 0.7 V	0.3	0.7		mA

**Remark** The TYP. values are values at T<sub>A</sub> = 25°C, except for the characteristics of temperature.

Block	Characteristics	Symbol	Conditions	MIN.	TYP.	MAX.	Unit	
Output Section	Collector Cut-off Current	$I_{CER}$	$V_{CE} = 40\text{ V}, V_{CC} = 40\text{ V},$ Common Emitter			100	μA	
	Emitter Cut-off Current		$V_{CC} = V_C = 40\text{ V}, V_E = 0\text{ V},$ Emitter Follower			-100	μA	
	Collector Saturation Voltage	Common Emitter	$V_{CE(sat)}$	$I_C = 200\text{ mA}, V_E = 0\text{ V}$		0.95	1.3	V
		Emitter Follower	$V_{CE(ON)}$	$I_E = -200\text{ mA}, V_C = 15\text{ V}$		1.6	2.5	V
	Output Voltage Rise Time	Common Emitter	$t_{r1}$	$V_{CC} = 15\text{ V}, R_L = 150\ \Omega,$ $I_C \cong 100\text{ mA}, T_A = 25^\circ\text{C},$ see <b>Figure 1.</b>		100	200	ns
	Output Voltage Fall Time		$t_{f1}$			70	200	ns
	Output Voltage Rise Time	Emitter Follower	$t_{r2}$	$V_C = 15\text{ V}, R_L = 150\ \Omega,$ $I_E \cong 100\text{ mA}, T_A = 25^\circ\text{C},$ see <b>Figure 1.</b>		100	200	ns
	Output Voltage Fall Time		$t_{f2}$			70	200	ns
Total Device	Standby Current	$I_{CC(S.B)}$	$V_{CC} = 15\text{ V},$ all other pins open.		8	12.5	mA	
	Bias Current	$I_{CC(BI)}$	$V_{(pin\ 4)} = 2\text{ V},$ see <b>Figure 1.</b>		10		mA	

**Remark** The TYP. values are values at  $T_A = 25^\circ\text{C}$ , except for the characteristics of temperature.

**Notes 1.** The short circuit output current flows for no more than 1 second. Repeat operation is possible if the internal heat accumulation is not within a harmful range.


**2.** Standard deviation is a measure of the statistical distribution about the mean as derived from the formula ;

$$\sigma = \sqrt{\frac{\sum_{n=1}^N (X_n - \bar{X})^2}{N - 1}}$$

Calculation expression of frequency  $f_{osc}$  is as follows ;

$$f_{osc} \cong \frac{1}{0.817 R_T \cdot C_T + 1.42 \cdot 10^{-6}} \text{ (Hz)} \quad [R_T] = \Omega, [C_T] = F$$


Figure1. Test Circuit



**Note** Recommend film capacitor.

★ **Caution** When the emitter follower is output, connect C<sub>1</sub> and C<sub>2</sub> to V<sub>cc</sub> and E<sub>1</sub> and E<sub>2</sub> to GND via R<sub>L</sub>.

Figure2. Voltage Waveform









**Connection of Output Control Pin (Pin No.13)**


Output Control Input (Pin No.13)	Operation Mode
At Ref Out	Normal push-pull operation
Grounded	Single-ended or parallel output

TYPICAL PERFORMANCE CHARACTERISTICS


★ (Unless otherwise specified,  $T_A = 25^\circ\text{C}$ ,  $V_{CC} = 15\text{ V}$ , Reference)




DUTY CYCLE vs. DEAD-TIME CONTROL INPUT VOLTAGE




OPEN-LOOP VOLTAGE GAIN vs. FREQUENCY



COLLECTOR SATURATION VOLTAGE vs. OUTPUT CURRENT




STANDBY AND BIAS CURRENT vs. SUPPLY VOLTAGE











BASIC APPLICATION CIRCUIT




★ Remark  $f_{osc} \cong 40 \text{ kHz}$ ,  $C_5 = 1000 \text{ pF}$  (Recommend film capacitor)

CONNECTION DIAGRAM


Operation Mode	Output Control Input (Pin No.13)	Output Mode	Output Voltage Waveform
Push-pull operation	At Ref-out (JP1 Wired)	Open collector ( $R_9, R_{10} 0\Omega$ )	C <sub>1</sub>  C <sub>2</sub> 
		Emitter follower ( $R_{11}, R_{12} 0\Omega$ )	E <sub>1</sub>  E <sub>2</sub> 
Single-ended or parallel output	Grounded (JP2 Wired)	Open collector ( $R_9, R_{10} 0\Omega$ )	C <sub>1</sub> , C <sub>2</sub> 
		Emitter follower ( $R_{11}, R_{12} 0\Omega$ )	E <sub>1</sub> , E <sub>2</sub> 

Printed Pattern (Example of μPC494C) (Pattern side, Actual size)




TYPICAL EXAMPLE OF APPLICATION CIRCUITS

1) Forward Type




2) Push-pull Type


(Isolated)



(Non Isolated)




3) Step-down Chopper



**Remark** The dotted line indicates the connection in case of large current.


SYNCHRONIZED OPERATION

If synchronized operation is needed, master-slave circuit can be used. This circuit is shown below. Initially,  $R_T$  terminal of slave IC is connected to pin 14(Ref Out) and internal oscillator is stopped.



★ PACKAGE DRAWINGS (Unit : mm)

16-PIN PLASTIC DIP (7.62mm(300))




NOTES

1. Each lead centerline is located within 0.25 mm of its true position (T.P.) at maximum material condition.
2. Item "K" to center of leads when formed parallel.




ITEM	MILLIMETERS
A	20.32 MAX.
B	1.27 MAX.
C	2.54 (T.P.)
D	0.50±0.10
F	1.1 MIN.
G	3.5±0.3
H	0.51 MIN.
I	4.31 MAX.
J	5.08 MAX.
K	7.62 (T.P.)
L	6.5
M	0.25 <sup>+0.10</sup> <sub>-0.05</sub>
N	0.25
P	1.1 MIN.
R	0-15°

P16C-100-300B-2

16-PIN PLASTIC SOP (9.53 mm (375))



detail of lead end




NOTE

Each lead centerline is located within 0.12 mm of its true position (T.P.) at maximum material condition.




ITEM	MILLIMETERS
A	10.0±0.2
B	0.78 MAX.
C	1.27 (T.P.)
D	0.42 <sup>+0.08</sup> <sub>-0.07</sub>
E	0.125±0.075
F	2.77 MAX.
G	2.47±0.1
H	10.3±0.3
I	7.2
J	1.6
K	0.17 <sup>+0.08</sup> <sub>-0.07</sub>
L	0.8±0.2
M	0.12
N	0.15
P	3 <sup>+7°</sup> <sub>-3°</sub>

P16GM-50-375B-6

16-PIN PLASTIC SOP (7.62 mm (300))



detail of lead end



NOTE

Each lead centerline is located within 0.12 mm of its true position (T.P.) at maximum material condition.

ITEM	MILLIMETERS
A	10.2±0.2
B	0.78 MAX.
C	1.27 (T.P.)
D	0.42 <sup>+0.08</sup> <sub>-0.07</sub>
E	0.1±0.1
F	1.65±0.15
G	1.55
H	7.7±0.3
I	5.6±0.2
J	1.1±0.2
K	0.22 <sup>+0.08</sup> <sub>-0.07</sub>
L	0.6±0.2
M	0.12
N	0.10
P	3° <sup>+7°</sup> <sub>-3°</sub>

P16GM-50-300B-6

★ **RECOMMENDED SOLDERING CONDITIONS**

When soldering this product, it is highly recommended to observe the conditions as shown below. If other soldering processes are used, or if the soldering is performed under different conditions, please make sure to consult with our sales offices.

For more details, refer to our document "SEMICONDUCTOR DEVICE MOUNTING TECHNOLOGY MANUAL"(C10535E).

**Type of Through-hole Device**

**μPC494C: 16-pin plastic DIP (7.62 mm (300))**

Process	Conditions
Wave Soldering (only to leads)	Solder temperature: 260°C or below, Flow time: 10 seconds or less.
Partial Heating Method	Pin temperature: 300°C or below, Heat time: 3 seconds or less (per each lead).

**Caution** For through-hole device, the wave soldering process must be applied only to leads, and make sure that the package body does not get jet soldered.

**Type of Surface Mount Device**

**μPC494G: 16-pin plastic SOP (9.53 mm (375))**

**μPC494GS: 16-pin plastic SOP (7.62 mm (300))**

Process	Conditions	Symbol
Infrared Ray Reflow	Peak temperature: 230°C or below (Package surface temperature), Reflow time: 30 seconds or less (at 210°C or higher), Maximum number of reflow processes: 1 time.	IR30-00-1
Vapor Phase Soldering	Peak temperature: 215°C or below (Package surface temperature), Reflow time: 40 seconds or less (at 200°C or higher), Maximum number of reflow processes: 1 time.	VP15-00-1
Wave Soldering	Solder temperature: 260°C or below, Flow time: 10 seconds or less, Maximum number of flow processes: 1 time, Pre-heating temperature: 120°C or below (Package surface temperature).	WS60-00-1
Partial Heating Method	Pin temperature: 300°C or below, Heat time: 3 seconds or less (Per each side of the device).	—

**Caution** Apply only one kind of soldering condition to a device, except for "partial heating method", or the device will be damaged by heat stress.



[MEMO]

[MEMO]

[MEMO]

- **The information in this document is current as of November, 2000. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
  - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
  - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
  - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
  - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
  - NEC semiconductor products are classified into the following three quality grades:  
"Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
    - "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
    - "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
    - "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation and also includes its majority-owned subsidiaries.  
(2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).