



PL302ST Series 3mm LED Right Angle Single Holder

Features

- *Right Angle PCB Indicator
- *1 Red LED used
- *Stand-off prevents Flux entrapment
- *Housing Material Black Nylon UL94V-2
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	90mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL302ST-1R24	Red	GaP	700	650	55°	2.1	3.0	1.3	3.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.5\text{mm}$ unless otherwise specified.

