


PNP SILICON PLANAR EPITAXIAL TRANSISTORS

**PN2907
PN2907A**

**TO-92
Plastic Package**



Complementary Silicon Transistors for Switching and Linear Applications.

ABSOLUTE MAXIMUM RATINGS(Ta=25 ° C unless specified otherwise)

DESCRIPTION	SYMBOL	PN2907	PN2907A	UNITS
Collector Emitter Voltage	V_{CEO}	40	60	V
Collector Base Voltage	V_{CBO}	60	60	V
Emitter Base Voltage	V_{EBO}	5	5	V
Collector Current Continuous	I_C	600		mA
Power Dissipation@ Ta=25 ° C	P_D	625		mW
Derate Above 25 ° C		5.0		mW/ ° C
Power Dissipation@ Tc=25 ° C	P_D	1.5		W
Derate Above 25 ° C		12		mW/ ° C
Operating And Storage Junction Temperature Range	T_j, T_{stg}	-55 to +150		° C

THERMAL RESISTANCE

Junction to ambient	$R_{th(j-a)}$	200		° C/W
Junction to case	$R_{th(j-c)}$	83.3		° C/W


ELECTRICAL CHARACTERISTICS (Ta=25 ° C Unless Specified Otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	PN2907	PN2907A	UNITS
Collector Emitter Voltage	BV_{CEO}	$I_C=10mA, I_B=0$	>40	>60	V
Collector Base Voltage	BV_{CBO}	$I_C=10\mu A, I_E=0$	>60	>60	V
Emitter Base Voltage	BV_{EBO}	$I_E=10\mu A, I_C=0$	>5	>5	V
Collector Cut off Current	I_{CBO}	$V_{CB}=50V, I_E=0$	<20	<10	nA
		Ta= 150 ° C			
		$V_{CB}=50V, I_E=0$	<20	<10	μA
	I_{CEX}	$V_{CE}=30V, V_{EB}=0.5V$	<50	<50	nA
	I_{CEO}	$V_{CE}=10V, I_B=0$	<10	<10	nA
Emitter Cut off Current	I_{EBO}	$V_{EB}=3V, I_C=0$	<10	<10	nA
Base Cut off Current	I_{BEX}	$V_{CE}=30V, V_{EB}=0.5V$	<50	<50	nA
DC Current Gain	h_{FE}	$V_{CE}=10V, I_C=0.1mA$	>35	>75	
		$V_{CE}=10V, I_C=1mA$	>50	>100	
		$V_{CE}=10V, I_C=10mA$	>75	>100	
		$V_{CE}=10V^*, I_C=150mA$	100-300	100-300	
		$V_{CE}=10V^*, I_C=500mA$	>30	>50	

PNP SILICON PLANAR EPITAXIAL TRANSISTORS

**PN2907
PN2907A**

**TO-92
Plastic Package**






ELECTRICAL CHARACTERISTICS (Ta=25 ° C Unless Specified Otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	PN2907	PN2907A	UNITS
Collector Emitter Saturation Voltage	$V_{CE(sat)}$ *	$I_C=150mA, I_B=15mA$	<0.4	<0.4	V
		$I_C=500mA, I_B= 50mA$	<1.6	<1.6	V
Base Emitter Saturation Voltage	$V_{BE(sat)}$ *	$I_C=150mA, I_B=15mA$	<1.3	<1.3	V
		$I_C=500mA, I_B= 50mA$	<2.6	<2.6	V
DYNAMIC CHARACTERISTICS					
Transition Frequency	f_T	$I_C=50mA, V_{CE}=20V$ $f=100MHz$	>200	>200	MHz
Output Capacitance	C_{ob}	$I_E=0, V_{CB}=10V, f=1MHz$	<8	<8	pF
Input Capacitance	C_{ib}	$I_C=0, V_{EB}=2V, f=1MHz$	<30	<30	pF
SWITCHING CHARACTERISTICS					
Delay Time	t_d		<10	<10	ns
Rise Time	t_r	$I_C =150mA, I_{B1}= 15mA$	<40	<40	ns
Turn on Time	t_{on}	$V_{CC} =30V$	<50	<50	ns
Storage Time	t_s		<80	<80	ns
Fall Time	t_f	$I_C =150mA, I_{B1}=15mA$	<30	<30	ns
Turn off Time	t_f	$I_{B2}=15mA, V_{CC} =6V$	<110	<110	ns

***Pulse Condition: = Width \leq 300us, Duty Cycle \leq 1%.**



TO-92 Plastic Package

TO-92 Transistors on Tape and Ammo Pack



DIM	MIN.	MAX.
A	4.32	5.33
B	4.45	5.20
C	3.18	4.19
D	0.41	0.55
E	0.35	0.50
F	5 DEG	
G	1.14	1.40
H	1.14	1.53
K	12.70	—
L	1.982	2.082

All dimensions in mm.



ITEM	SYMBOL	SPECIFICATION				REMARKS
		MIN.	NOM.	MAX.	TOL.	
BODY WIDTH	A1	4.0		4.8		
BODY HEIGHT	A	4.8		5.2		
BODY THICKNESS	T	3.9		4.2		
PITCH OF COMPONENT	P	12.7			%%P1	
FEED HOLE PITCH	Po	12.7			%%P0.3	CUMULATIVE PITCH ERROR 1.0 mm/20 PITCH
FEED HOLE CENTRE TO COMPONENT CENTRE	P2	6.35			%%P0.4 +0.6 -0.2	TO BE MEASURED AT BOTTOM OF CLINCH
DISTANCE BETWEEN OUTER LEADS	F	5.08				
COMPONENT ALIGNMENT SIDE VIEW	Δh	0		1.0		AT TOP OF BODY
COMPONENT ALIGNMENT FRONT VIEW	Δh1	0		1.3		AT TOP OF BODY
TAPE WIDTH	W	18			%%P0.5	
HOLD-DOWN TAPE WIDTH	Wo	6			%%P0.2	
HOLE POSITION	W1	9			+0.7 -0.5	
HOLD-DOWN TAPE POSITION	W2	0.5			%%P0.2	
LEAD WIRE CLINCH HEIGHT	Ho	16			%%P0.5	
COMPONENT HEIGHT	H1			23.25		
LENGTH OF SNIPPED LEADS	L			11.0		
FEED HOLE DIAMETER	Do	4			%%P0.2	
TOTAL TAPE THICKNESS	t			1.2		t1 0.3 - 0.6
LEAD - TO - LEAD DISTANCE	F1, F2	2.54			+0.4, -0.1	
STAND OFF	H2	0.45		1.45		
CLINCH HEIGHT	H3			3.0		
LEAD PARALLELISM	C1 - C2			0.22		
PULL - OUT FORCE	(P)	6N				

NOTES

1. MAXIMUM ALIGNMENT DEVIATION BETWEEN LEADS NOT TO BE GREATER THAN 0.2 mm.
2. MAXIMUM NON-CUMULATIVE VARIATION BETWEEN TAPE FEED HOLES SHALL NOT EXCEED 1 mm IN 20 PITCHES.
3. HOLDDOWN TAPE NOT TO EXCEED BEYOND THE EDGE(S) OF CARRIER TAPE AND THERE SHALL BE NO EXPOSURE OF ADHESIVE.
4. NO MORE THAN 3 CONSECUTIVE MISSING COMPONENTS IS PERMITTED.
5. A TAPE TRAILER, HAVING AT LEAST THREE FEED HOLES IS REQUIRED AFTER THE LAST COMPONENT.
6. SPLICES SHALL NOT INTERFERE WITH THE SPROCKET FEED HOLES.

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-92 Bulk	1K/polybag	200 gm/1K pcs	3" x 7.5" x 7.5"	5K	17" x 15" x 13.5"	80K	23 kgs
TO-92 T&A	2K/ammo box	645 gm/2K pcs	12.5" x 8" x 1.8"	2K	17" x 15" x 13.5"	32K	12.5 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119

email@cdil.com www.cdilsemi.com