

**Application**


- Low-loss SAW component
- Low amplitude ripple
- Sharp rejections at both out-bands
- Usable passband 1.5 MHz

**Features**

- RoHS compatible
- Package size 11.0x4.5x4.1mm<sup>3</sup>
- Package Code F11-SMD
- Electrostatic Sensitive Device(ESD)



**Package Dimensions (Unit: mm)**



**Pin Configuration**


Pin No.	Description
1	Input
4	Output
2,3	Case Ground

**Marking Description**

RF	R	Trademark & Manufacturer
	F	SAW Filter
1010	Part Number	
●	Pin 1	
YYWW	Year Code & Week Code	

\*Fig: If the products produced in 06<sup>th</sup> week of 2015, The year code & week code is 1506.

**Test Circuit (Bottom View)**



**Performance****Maximum Rating**

Item		Value	Unit
DC Voltage	V <sub>DC</sub>	3	V
Operation Temperature	T	-40 ~ +85	°C
Storage Temperature	T <sub>stg</sub>	-55 ~ +125	°C
RF Power Dissipation	P	15	dBm

**Electronic Characteristics**

Test Temperature: 25°C ± 2°C


Terminating source impedance: 300Ω

Terminating load impedance: 300Ω


Item		Minimum	Typical	Maximum	Unit
Center Frequency	f <sub>c</sub>		110.592		MHz
Insertion Loss(min)	IL		3.5	4.5	dB
Insertion Loss	109.85-111.35MHz IL		4.8	5.5	dB
Amplitude Ripple (p-p)	109.85-111.35MHz Δα		1.2	1.8	dB
Group Delay Ripple	109.85-111.35MHz		500	800	ns
Absolute Attenuation	α				
	DC-100.000 MHz	45.0	50.0		dB
	105.416-107.144MHz	40.0	45.0		dB
	107.144-108.872MHz	35.0	40.0		dB
	112.328-114.056MHz	25.0	28.0		dB
	114.056-115.784MHz	35.0	40.0		dB
	150.000-800.000MHz	50.0	55.0		dB
Input VSWR	109.85-111.35MHz		2.0:1	2.5:1	/
Output VSWR	109.85-111.35MHz		2.0:1	2.5:1	/

Frequency Characteristics


Frequency Response




Frequency Response (wideband)




Delay Ripple & S11 VSWR




Phase Linearity & S22 VSWR



S11 Smith Chart




S22 Smith Chart



Reliability (The SAW components shall remain electrical performance after tests)

No.	Test item	Test condition
1	Temperature Storage	(1) Temperature: $85^{\circ}\text{C}\pm 2^{\circ}\text{C}$ , Duration: 250h, Recovery time: $2\text{h}\pm 0.5\text{h}$ (2) Temperature: $-55^{\circ}\text{C}\pm 3^{\circ}\text{C}$ , Duration: 250h, Recovery time: $2\text{h}\pm 0.5\text{h}$
2	Humidity Test	Conditions: $60^{\circ}\text{C}\pm 2^{\circ}\text{C}$ , 90~95% RH                          Duration: 250h
3	Thermal Shock	Heat cycle conditions: TA= $-55^{\circ}\text{C}\pm 3^{\circ}\text{C}$ , TB= $85^{\circ}\text{C}\pm 2^{\circ}\text{C}$ , t1=t2=30min, Switch time: $\leq 3\text{min}$ , Cycle time: 100 times, Recovery time: $2\text{h}\pm 0.5\text{h}$ .
4	Vibration Fatigue	Frequency of vibration: 10~55Hz                          Amplitude: 1.5mm Directions: X,Y and Z                          Duration: 2h
5	Drop Test	Cycle time: 10 times                          Height: 1.0m
6	Solder Ability Test	Temperature: $245^{\circ}\text{C}\pm 5^{\circ}\text{C}$ Duration: 3.0s--5.0s Depth: DIP--2/3, SMD--1/5
7	Resistance to Soldering Heat	(1) Thickness of PCB: 1mm, Solder condition: $260^{\circ}\text{C}\pm 5^{\circ}\text{C}$ , Duration: $10\pm 1\text{s}$ (2) Temperature of Soldering Iron: $350^{\circ}\text{C}\pm 10^{\circ}\text{C}$ , Duration: 3~4s, Recovery time: $2 \pm 0.5\text{h}$

Recommended Reflow Soldering Diagram



Reflow cycles: 3 cycles max.

**Notes**

1. As a result of the particularity of inner structure of SAW products, it easy to be breakdown by electrostatic, so we should pay attention to **ESD protect** in the test.
2. **Static voltage** between signal load and ground may cause deterioration and destruction of the component. Please avoid static voltage.
3. **Ultrasonic cleaning** may cause deterioration and destruction of the component. Please avoid ultrasonic cleaning.
4. Only leads of component may **be soldered**. Please avoid soldering another part of component.
5. There is a close relationship between the device's performance and **matching network**. The specifications of this device are based on the test circuit shown above. L and C values may change depending on board layout. Values shown are intended as a guide only.