


## Features

- 500W Peak Pulse Surge reverse capability on 10/1000 $\mu$ s waveform
- Excellent clamping capability
- Low incremental surge resistance
- Fast response time : typically less than 1.0 ns from 0 volts to BV



## Mechanical Data

- Case : DO-15 Molded plastic
- Epoxy : UL94V-O rate flame retardant
- Lead : Axial lead solderable per MIL-STD-202, method 208 guaranteed
- Polarity : Color band denotes cathode end
- Mounting position : Any
- Weight : 0.34 gram

DO-15		
Dim	Min	Max
A	25.40	—
B	5.50	7.62
C	0.686	0.889
D	2.60	3.60
All Dimensions in mm		

## Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

Rating	Symbol	Value	Unit
Peak Pulse Power Dissipation on 10/1000 $\mu$ s waveform (Note 1, Figure 1)	PPPM	Minimum 500	Watts
Steady State Power Dissipation at T <sub>L</sub> = 75 °C Lead Lengths 0.375", (9.5mm)	P <sub>D</sub>	1.0	Watts
Peak Forward Surge Current on 10/1000 $\mu$ s Waveform (Fig. 3, Note 1)	IFSM	See Table 1.	Amps.
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	- 65 to + 175	°C

### Note :

(1) Non-repetitive Current pulse, per Fig. 5 and derated above T<sub>a</sub> = 25 °C per Fig. 2



TYPE NUMBER	Breakdown Voltage @ $I_t$		Reverse Stand-off Voltage	Maximum Reverse Leakage @ $V_{RWM}$	Maximum Clamping Voltage @ $I_{RSM}=5A$	Maximum Reverse Current	Maximum Junction Capacitance @ 0 Volt	Working Inverse Blocking Voltage	Max. Inverse Blocking Current @ $V_{WIB}$	Peak Inverse Blocking Voltage
	$V_{BR}$ (V)	$I_t$								
	Min.	(mA)	$V_{RWM}$ (V)	$I_R$ ( $\mu A$ )	$V_{RSM}$ (V)	$I_{RSM}$ (A)	$V_{WIB}$ (V)	$I_{IB}$ (mA)	$V_{PIB}$ (V)	
SAC5.0	7.6	1.0	5.0	300	10.0	44	50	75	1.0	100
SAC6.0	7.9	1.0	6.0	300	11.2	41	50	75	1.0	100
SAC7.0	8.3	1.0	7.0	300	12.6	38	50	75	1.0	100
SAC8.0	8.9	1.0	8.0	100	13.4	36	50	75	1.0	100
SAC8.5	9.4	1.0	8.5	50	14.0	34	50	75	1.0	100
SAC10	11.1	1.0	10	5.0	16.3	29	50	75	1.0	100
SAC12	13.3	1.0	12	5.0	19.0	25	50	75	1.0	100
SAC15	16.7	1.0	15	5.0	23.6	20	50	75	1.0	100
SAC18	20.0	1.0	18	5.0	28.8	15	50	75	1.0	100
SAC22	24.4	1.0	22	5.0	35.4	14	50	75	1.0	100
SAC26	28.9	1.0	26	5.0	42.3	11.1	50	75	1.0	100
SAC30	33.3	1.0	30	5.0	48.6	10	50	75	1.0	100
SAC36	40.0	1.0	36	5.0	60.0	8.6	50	75	1.0	100
SAC45	50.0	1.0	45	5.0	77.0	6.8	50	150	1.0	200
SAC50	55.5	1.0	50	5.0	88.0	5.8	50	150	1.0	200

FIG.1 - PEAK PULSE POWER RATING CURVE




FIG.2 - PULSE DERATING CURVE




FIG.3 - PULSE WAVEFORM

