



SD57045

RF POWER TRANSISTORS The *LdmoST* FAMILY



ADVANCE DATA

N-CHANNEL ENHANCEMENT-MODE LATERAL MOSFETs

- v EXCELLENT THERMAL STABILITY
- v COMMON SOURCE CONFIGURATION
- v P_{OUT} = 45 W PEP with 13 dB gain @ 945 MHz
- v BeO FREE PACKAGE

DESCRIPTION

The SD57045 is a common source N-Channel Enhancement-Mode lateral Field-Effect RF power transistor designed for broadband commercial and industrial applications at frequencies up to 1.0 GHz. The SD57045 is designed for high gain and broadband performance operating in common source mode at 28V. It is ideal for base stations applications requiring high linearity.



ABSOLUTE MAXIMUM RATINGS (T_{case} = 25 °C)

| Symbol | Parameter | Value | Unit |
|----------------------|--|------------|------|
| V _{(BR)DSS} | Drain Source Voltage | 65 | V |
| V _{DGR} | Drain-Gate Voltage (R _{GS} = 1 MΩ) | 65 | V |
| V _{GS} | Gate-Source Voltage | ± 20 | V |
| I _D | Drain Current | 5 | A |
| P _{DISS} | Power Dissipation (@ T _c = 70 °C) | 93 | W |
| T _j | Max. Operating Junction Temperature | 200 | °C |
| T _{STG} | Storage Temperature | -65 to 200 | °C |

THERMAL DATA (T_{case} = 70 °C)

| | | | |
|----------------------|----------------------------------|------|------|
| R _{th(j-c)} | Junction-Case Thermal Resistance | 1.4 | °C/W |
| R _{th(c-s)} | Case-Heatsink Thermal Resistance | 0.45 | °C/W |

* Determined using a flat aluminum or copper heatsink with thermal compound applied (Dow Corning 340 or equivalent).

ELECTRICAL SPECIFICATION ($T_{case} = 25\text{ }^{\circ}\text{C}$)

STATIC

| Symbol | Parameter | | Min. | Typ. | Max. | Unit |
|---------------|----------------|------------------------|------|------|------|---------------|
| $V_{(BR)DSS}$ | $V_{GS} = 0V$ | $I_{DS} = 1\text{ mA}$ | 65 | | | V |
| I_{DSS} | $V_{GS} = 0V$ | $V_{DS} = 28\text{ V}$ | | | 1 | μA |
| I_{GSS} | $V_{GS} = 20V$ | $V_{DS} = 0\text{ V}$ | | | 1 | μA |
| $V_{GS(Q)}$ | $V_{DS} = 28V$ | $I_D = 250\text{ mA}$ | 2.5 | | 5.0 | V |
| $V_{DS(ON)}$ | $V_{GS} = 10V$ | $I_D = 3\text{ A}$ | | 0.7 | 0.9 | V |
| G_{FS} | $V_{DS} = 10V$ | $I_D = 5\text{ A}$ | 2.0 | 2.7 | | mho |
| C_{ISS} | $V_{GS} = 0V$ | $V_{DS} = 28\text{ V}$ | | 80 | | pF |
| C_{OSS} | $V_{GS} = 0V$ | $V_{DS} = 28\text{ V}$ | | 40 | | pF |
| C_{RSS} | $V_{GS} = 0V$ | $V_{DS} = 28\text{ V}$ | | 3.2 | | pF |


REF. 7133620B

DYNAMIC

| Symbol | Parameter | | Min. | Typ. | Max. | Unit |
|---------------|--|---|------|------|------|------|
| P_{OUT} | $f = 945\text{ MHz}$ | $V_{DD} = 28V$ $I_{DQ} = 250\text{ mA}$ | 45 | | | W |
| IMD_3 | $V_{DD} = 28\text{ V}$ | $P_{out} = 45\text{ W PEP}$ $I_{DQ} = 250\text{ mA}$ | | -32 | -28 | dBc |
| G_{PS} | $V_{DD} = 28\text{ V}$ | $P_{out} = 45\text{ W PEP}$ $I_{DQ} = 250\text{ mA}$ | 13 | 15 | | dB |
| η_D | $V_{DD} = 28\text{ V}$ | $P_{out} = 45\text{ W PEP}$ $I_{DQ} = 250\text{ mA}$ | 33 | 40 | | % |
| Load Mismatch | $f = 945\text{ MHz}$ ALL PHASE ANGLES | $V_{DD} = 28\text{ V}$ $P_{out} = 45\text{ W}$ $I_{DQ} = 250\text{ mA}$ | 10:1 | | | VSWR |

Note: $f_1 = 945.0\text{ MHz}$
 $f_2 = 945.1\text{ MHz}$


IMPEDANCE DATA




| FREQ. | $Z_{IN} (\Omega)$ | $Z_{DL} (\Omega)$ |
|---------|-------------------|-------------------|
| 925 MHz | $1.27 + j 0.82$ | $2.22 - j 1.63$ |
| 930 MHz | $1.21 + j 0.79$ | $2.24 - j 1.61$ |
| 945 MHz | $1.04 + j 0.71$ | $2.30 - j 1.52$ |
| 960 MHz | $0.93 + j 0.43$ | $2.37 - j 1.37$ |
| 965 MHz | $0.91 + j 0.41$ | $2.43 - j 1.36$ |

TYPICAL PERFORMANCE


Capacitance vs Drain-Source Voltage




Gate-Source Voltage vs Case Temperature




Drain Current vs Gate Voltage



DC Maximum Safe Operating Area




Maximum Thermal Resistance vs Case Temperature




TYPICAL PERFORMANCE (CW)


Output Power and Power Gain vs Input Power




Power Gain vs Output Power




Efficiency vs Output Power




Broadband Power Performance



Output Power vs. Drain Voltage




Output Power vs. Gate Bias Voltage




TYPICAL PERFORMANCE (PEP)


Output Power and Power Gain vs Input Power




Efficiency vs Output Power




Intermodulation Distortion vs. Output Power




Intermodulation Distortion vs. Output Power



Class A Third Order Intercept Point



945 MHz Test Circuit Schematic




945 MHz Test Circuit Component Part List


| COMPONENT | PART NO | VENDOR | DESCRIPTION |
|-----------|--------------------|------------------|---|
| C19 | SME63VB221M10X20L | UNITED CHEMI-CON | 220µF/63V ALUMINUM ELECTROLYTIC RADIAL LEAD CAPACITOR |
| C18 | C1812X7R501-104KNE | VENKEL | 0.1µF/500V SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C17 | ATC100B101KW500X | ATC | 100pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C16 | ATC100B470KW500X | ATC | 47pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C15 | SKR100M1JD11 | MALLORY | 10µF/50V ALUMINUM ELECTROLYTIC RADIAL LEAD CAPACITOR |
| C14 | C1812X7R501-104KNE | VENKEL | 0.1µF/500V SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C13 | ATC700B102MW50X | ATC | 1000pF ATC 700B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C12 | ATC100B470KW500X | ATC | 47pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C11 | ATC100B470KW500X | ATC | 47pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C10 | ATC100B3R0KW500X | ATC | 3.0pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C9 | 27291PC | JOHANSON | 0.8-8.0pF GIGA TRIM VARIABLE CAPACITOR |
| C8 | ATC100B6R2KW500X | ATC | 6.2pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C7 | ATC100B100KW500X | ATC | 10pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C6 | ATC100B100KW500X | ATC | 10pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C5 | ATC100B100KW500X | ATC | 10pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C4 | ATC100B100KW500X | ATC | 10pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C3 | ATC100B3R0CW500X | ATC | 3pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| C2 | 27291PC | JOHANSON | 0.8-8.0pF GIGA TRIM VARIABLE CAPACITOR |
| C1 | ATC100B470KW500X | ATC | 47pF ATC 100B SURFACE MOUNT CERAMIC CHIP CAPACITOR |
| R3 | CR2010-2W-475JT | VENKEL | 120 OHM, 2W SURFACE MOUNT CHIP RESISTOR |
| R2 | CR2512-1W-183JT | VENKEL | 4.7M OHM 1W SURFACE MOUNT CHIP RESISTOR |
| R1 | CR2512-1W-121JT | VENKEL | 18K OHM, 1W SURFACE MOUNT CHIP RESISTOR |
| FB2 | 2743021447 | FAIR-RITE CORP. | SHIELD BEAD SURFACE MOUNT EMI |
| FB1 | 2743019447 | FAIR-RITE CORP. | SHIELD BEAD SURFACE MOUNT EMI |
| L2 | 8051 | BELDEN | INDUCTOR, 5TURNS AIR WOUND #22AWG, ID=0.059[1.49], NYLON COATED MAGNET WIRE |
| L1 | 8051 | BELDEN | INDUCTOR, 5TURNS AIR WOUND #22AWG, ID=0.059[1.49], NYLON COATED MAGNET WIRE |
| PCB | G0300M1026 | ROGERS CORP. | WOVEN FIBERGLASS REINFORCED PTFE 0.080" THK, εr=2.55, 2 Oz EDCu BOTH SIDE |

SC14640

945 MHz Test Circuit Photomaster



945 MHz Production Test Fixture



COMMON SOURCE S-PARAMETERS

(V_{DS} = 13.5 V, I_{DS} = 1.5 A)

| FREQ (MHz) | S ₁₁ | ∠S ₁₁ | S ₂₁ | ∠S ₂₁ | S ₁₂ | ∠S ₁₂ | S ₂₂ | ∠S ₂₂ |
|---------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|
| 50 | 0.902 | -168 | 14.591 | 88 | 0.015 | -4 | 0.781 | -170 |
| 60 | 0.902 | -169 | 13.845 | 88 | 0.015 | -4 | 0.781 | -170 |
| 70 | 0.902 | -168 | 13.069 | 87 | 0.014 | -5 | 0.781 | -171 |
| 80 | 0.902 | -170 | 12.266 | 86 | 0.014 | -5 | 0.781 | -171 |
| 90 | 0.902 | -170 | 11.436 | 86 | 0.014 | -5 | 0.782 | -171 |
| 100 | 0.903 | -171 | 10.587 | 84 | 0.014 | -6 | 0.782 | -172 |
| 150 | 0.905 | -173 | 6.604 | 78 | 0.014 | -9 | 0.788 | -173 |
| 200 | 0.910 | -174 | 4.670 | 71 | 0.013 | -11 | 0.799 | -173 |
| 250 | 0.916 | -174 | 3.588 | 66 | 0.013 | -12 | 0.812 | -173 |
| 300 | 0.921 | -174 | 2.884 | 61 | 0.012 | -11 | 0.825 | -173 |
| 350 | 0.927 | -175 | 2.379 | 56 | 0.011 | -13 | 0.839 | -173 |
| 400 | 0.933 | -175 | 2.005 | 52 | 0.011 | -14 | 0.853 | -173 |
| 450 | 0.939 | -175 | 1.719 | 48 | 0.010 | -14 | 0.866 | -173 |
| 500 | 0.944 | -175 | 1.494 | 45 | 0.010 | -15 | 0.878 | -173 |
| 550 | 0.950 | -175 | 1.317 | 42 | 0.009 | -14 | 0.889 | -173 |
| 600 | 0.954 | -175 | 1.169 | 40 | 0.008 | -12 | 0.899 | -173 |
| 650 | 0.957 | -175 | 1.051 | 38 | 0.007 | -10 | 0.908 | -174 |
| 700 | 0.960 | -175 | 0.942 | 36 | 0.007 | -5 | 0.916 | -174 |
| 750 | 0.963 | -175 | 0.853 | 34 | 0.006 | -1 | 0.923 | -174 |
| 800 | 0.966 | -175 | 0.770 | 32 | 0.005 | 7 | 0.930 | -174 |
| 850 | 0.968 | -176 | 0.696 | 31 | 0.005 | 16 | 0.935 | -174 |
| 900 | 0.970 | -176 | 0.630 | 29 | 0.005 | 28 | 0.940 | -174 |
| 950 | 0.972 | -176 | 0.568 | 28 | 0.005 | 40 | 0.944 | -174 |
| 1000 | 0.973 | -176 | 0.515 | 27 | 0.005 | 50 | 0.948 | -174 |
| 1050 | 0.974 | -176 | 0.465 | 26 | 0.006 | 59 | 0.950 | -174 |
| 1100 | 0.926 | -177 | 0.422 | 25 | 0.006 | 66 | 0.950 | -174 |
| 1150 | 0.977 | -177 | 0.301 | 25 | 0.007 | 74 | 0.949 | -175 |
| 1200 | 0.979 | -177 | 0.348 | 24 | 0.008 | 79 | 0.946 | -176 |
| 1250 | 0.980 | -177 | 0.317 | 24 | 0.009 | 83 | 0.941 | -177 |
| 1300 | 0.982 | -177 | 0.292 | 24 | 0.010 | 84 | 0.934 | -178 |
| 1350 | 0.984 | -177 | 0.267 | 24 | 0.011 | 85 | 0.923 | 180 |
| 1400 | 0.986 | -177 | 0.248 | 24 | 0.012 | 86 | 0.910 | 177 |
| 1450 | 0.989 | -177 | 0.231 | 24 | 0.013 | 87 | 0.892 | 175 |
| 1500 | 0.990 | -177 | 0.223 | 25 | 0.013 | 88 | 0.898 | 172 |


COMMON SOURCE S-PARAMETERS

(V_{DS} = 28 V, I_{DS} = 1.5 A)

| FREQ (MHz) | S ₁₁ | ∠S ₁₁ | S ₂₁ | ∠S ₂₁ | S ₁₂ | ∠S ₁₂ | S ₂₂ | ∠S ₂₂ |
|---------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|
| 50 | 0.867 | -158 | 20.011 | 91 | 0.013 | 2 | 0.675 | -163 |
| 60 | 0.870 | -159 | 18.979 | 90 | 0.013 | 1 | 0.676 | -164 |
| 70 | 0.873 | -160 | 17.907 | 89 | 0.013 | -0 | 0.677 | -164 |
| 80 | 0.876 | -162 | 16.794 | 88 | 0.013 | -1 | 0.679 | -165 |
| 90 | 0.880 | -163 | 15.649 | 87 | 0.013 | -2 | 0.681 | -165 |
| 100 | 0.884 | -164 | 14.478 | 86 | 0.013 | -3 | 0.683 | -165 |
| 150 | 0.904 | -169 | 8.997 | 77 | 0.012 | -9 | 0.700 | -167 |
| 200 | 0.915 | -171 | 6.310 | 70 | 0.012 | -14 | 0.722 | -167 |
| 250 | 0.920 | -172 | 4.797 | 62 | 0.011 | -18 | 0.748 | -167 |
| 300 | 0.927 | -173 | 3.813 | 56 | 0.010 | -21 | 0.774 | -167 |
| 350 | 0.933 | -173 | 3.106 | 51 | 0.009 | -22 | 0.799 | -167 |
| 400 | 0.940 | -173 | 2.589 | 47 | 0.009 | -23 | 0.823 | -168 |
| 450 | 0.947 | -174 | 2.194 | 43 | 0.008 | -23 | 0.843 | -168 |
| 500 | 0.953 | -174 | 1.890 | 40 | 0.007 | -23 | 0.862 | -168 |
| 550 | 0.958 | -174 | 1.652 | 37 | 0.006 | -21 | 0.877 | -169 |
| 600 | 0.963 | -174 | 1.456 | 34 | 0.006 | -17 | 0.891 | -169 |
| 650 | 0.966 | -174 | 1.299 | 32 | 0.005 | -12 | 0.904 | -169 |
| 700 | 0.968 | -175 | 1.157 | 30 | 0.004 | -4 | 0.914 | -170 |
| 750 | 0.971 | -175 | 1.039 | 28 | 0.004 | 6 | 0.923 | -170 |
| 800 | 0.974 | -175 | 0.932 | 26 | 0.004 | 18 | 0.932 | -170 |
| 850 | 0.976 | -175 | 0.838 | 25 | 0.004 | 31 | 0.940 | -172 |
| 900 | 0.977 | -176 | 0.755 | 23 | 0.004 | 42 | 0.946 | -170 |
| 950 | 0.979 | -176 | 0.678 | 22 | 0.004 | 54 | 0.951 | -170 |
| 1000 | 0.980 | -176 | 0.613 | 21 | 0.005 | 61 | 0.955 | -171 |
| 1050 | 0.981 | -176 | 0.550 | 20 | 0.006 | 69 | 0.957 | -171 |
| 1100 | 0.982 | -177 | 0.498 | 19 | 0.006 | 74 | 0.958 | -171 |
| 1150 | 0.983 | -177 | 0.449 | 19 | 0.007 | 28 | 0.957 | -172 |
| 1200 | 0.985 | -177 | 0.410 | 19 | 0.008 | 80 | 0.954 | -173 |
| 1250 | 0.985 | -177 | 0.373 | 18 | 0.009 | 83 | 0.949 | -174 |
| 1300 | 0.986 | -177 | 0.344 | 18 | 0.010 | 86 | 0.940 | -175 |
| 1350 | 0.987 | -177 | 0.314 | 18 | 0.010 | 88 | 0.929 | -177 |
| 1400 | 0.989 | -177 | 0.292 | 19 | 0.011 | 90 | 0.913 | -180 |
| 1450 | 0.991 | -177 | 0.273 | 19 | 0.012 | 93 | 0.896 | -177 |
| 1500 | 0.992 | -177 | 0.263 | 19 | 0.013 | 94 | 0.884 | -175 |

M243 (.230 x .360 WIDE 2/L N/HERM W/FLG) MECHANICAL DATA

| DIM. | mm | | | inch | | |
|------|-------|-------|-------|-------|-------|-------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| A | 5.21 | | 5.72 | 0.205 | | 0.225 |
| B | 5.46 | | 6.48 | 0.215 | | 0.255 |
| C | 5.59 | | 6.10 | 0.220 | | 0.240 |
| D | | 14.27 | | | 0.562 | |
| E | 20.07 | | 20.57 | 0.790 | | 0.810 |
| F | 8.89 | | 9.40 | 0.350 | | 0.370 |
| G | 0.10 | | 0.15 | 0.004 | | 0.006 |
| H | 3.18 | | 4.45 | 0.125 | | 0.175 |
| I | 1.83 | | 2.24 | 0.072 | | 0.088 |
| J | 1.27 | | 1.78 | 0.050 | | 0.070 |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 2000 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco -
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>

