



Solid State Devices, Inc.
 14701 Firestone Blvd. * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SER30KB60 / SER30KE60 Series

ELECTRICAL CHARACTERISTICS		Symbol	Typical	Maximum	Unit
Instantaneous Forward Voltage Drop ($I_F = 5 \text{ A}$, 300 μsec Pulse)	$T_A = -55^\circ\text{C}$	V_{F1a}	1070	-	mV_{DC}
	$T_A = 25^\circ\text{C}$	V_{F1b}	950	-	
	$T_A = 100^\circ\text{C}$	V_{F1c}	760	-	
	$T_A = 125^\circ\text{C}$	V_{F1d}	710	-	
	$T_A = 150^\circ\text{C}$	V_{F1e}	650	-	
Instantaneous Forward Voltage Drop ($I_F = 10 \text{ A}_{\text{DC}}$, 300 μsec Pulse)	$T_A = -55^\circ\text{C}$	V_{F2a}	1150	-	mV_{DC}
	$T_A = 25^\circ\text{C}$	V_{F2b}	1050	1150	
	$T_A = 100^\circ\text{C}$	V_{F2c}	860	-	
	$T_A = 125^\circ\text{C}$	V_{F2d}	810	975	
	$T_A = 150^\circ\text{C}$	V_{F2e}	750	-	
Instantaneous Forward Voltage Drop ($I_F = 20 \text{ A}_{\text{DC}}$, 300 μsec Pulse)	$T_A = -55^\circ\text{C}$	V_{F3a}	1260	-	mV_{DC}
	$T_A = 25^\circ\text{C}$	V_{F3b}	1170	-	
	$T_A = 100^\circ\text{C}$	V_{F3c}	1000	-	
	$T_A = 125^\circ\text{C}$	V_{F3d}	950	-	
	$T_A = 150^\circ\text{C}$	V_{F3e}	880	-	
Instantaneous Forward Voltage Drop ($I_F = 30 \text{ A}_{\text{DC}}$, 300 μsec Pulse)	$T_A = -55^\circ\text{C}$	V_{F4a}	1340	-	mV_{DC}
	$T_A = 25^\circ\text{C}$	V_{F4b}	1260	1400	
	$T_A = 100^\circ\text{C}$	V_{F4c}	1100	-	
	$T_A = 125^\circ\text{C}$	V_{F4d}	1050	1250	
	$T_A = 150^\circ\text{C}$	V_{F4e}	990	-	
Instantaneous Forward Voltage Drop ($I_F = 50 \text{ A}_{\text{DC}}$, 300 μsec Pulse)	$T_A = -55^\circ\text{C}$	V_{F5a}	1480	-	mV_{DC}
	$T_A = 25^\circ\text{C}$	V_{F5b}	1400	-	
	$T_A = 100^\circ\text{C}$	V_{F5c}	1240	-	
	$T_A = 125^\circ\text{C}$	V_{F5d}	1190	-	
	$T_A = 150^\circ\text{C}$	V_{F5e}	1150	-	
Reverse Leakage Current (Rated V_R , 300 μsec pulse minimum)	$T_A = 25^\circ\text{C}$	I_{R1}	0.1	10	μA
	$T_A = 100^\circ\text{C}$	I_{R2}	6	-	
	$T_A = 125^\circ\text{C}$	I_{R3}	25	500	
	$T_A = 150^\circ\text{C}$	I_{R4}	80	-	
Junction Capacitance ($T_A = 25^\circ\text{C}$, $f = 1 \text{ MHz}$)	$V_R = 5 \text{ V}$	C_J	190	-	pF
	$V_R = 10 \text{ V}$		140	250	
Reverse Recovery	$I_F = 0.5 \text{ A}$, $I_R = 1 \text{ A}$, $I_{rr} = 0.25 \text{ A}$	t_{rr1}	32	35	ns
	$I_F = 1 \text{ A}$, $I_R = 1 \text{ A}$, $I_{rr} = 0.1 \text{ A}$	t_{rr2}	75	-	ns
	$I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 25^\circ\text{C}$	t_{rr3}	46	-	ns
	$I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 25^\circ\text{C}$	I_{RM3}	1.8	-	A
	$I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 100^\circ\text{C}$	t_{rr4}	115	-	ns
	$I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 100^\circ\text{C}$	I_{RM4}	3.8	-	A
	$I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A/us}$, $T_A = 25^\circ\text{C}$	t_{rr5}	45	-	ns
	$I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A/us}$, $T_A = 25^\circ\text{C}$	I_{RM5}	3.7	-	A
Forward Recovery	$I_F = 1 \text{ A}$	t_{fr}	60	-	ns
		V_{fr}	880	-	mV

NOTES:

- 1/ For ordering information, price, operating curves, and availability – contact factory.
- 2/ Screening based on MIL-PRF-19500. Screening flows available on request.

NOTE: All specifications are subject to change without notification.
 SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0128D

DOC