

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free

**FEATURES**

- High Current Capability
- Extremely Low Thermal Resistance
- For Surface Mount Application
- Higher Temp Soldering : 250°C for 10 Seconds at Terminals
- Low Reverse Current



**MECHANICAL DATA**

- Case: Molded Plastic
- Epoxy: UL 94V-0 Rate Flame Retardant
- Lead: Axial Leads, Solderable per MIL-STD-202 method 208 Guaranteed
- Polarity: Color Band Denotes Cathode End
- Mounting Position: Any

**PACKAGE INFORMATION**

Package	MPQ	LeaderSize
SMB	3K	13' inch

**SMB**



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	1.91	2.20	E	-	0.203
B	4.06	4.70	F	5.08	5.59
C	3.30	3.94	G	0.76	1.52
D	2.13	2.44	H	0.15	0.305

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load. For capacitive load, de-rate current by 20%.)


Parameter	Symbol	Rating	Unit
Peak Repetitive Peak reverse voltage	$V_{RRM}$	200	V
Working Peak Reverse Voltage	$V_{RWM}$	200	V
Maximum DC Blocking Voltage	$V_R$	200	V
Average Forward Current @ $T_J=25^\circ\text{C}$	$I_{F(AV)}$	2	A
Peak Forward Current @ 8.3 ms Half Sine	$I_{FSM}$	60	A
Maximum Instantaneous Forward Voltage	$V_F$	$I_{FM} = 2.0A, T_A=25^\circ\text{C}$	0.85
		$I_{FM} = 2.0A, T_A=75^\circ\text{C}$	0.75
		$I_{FM} = 2.0A, T_A=125^\circ\text{C}$	0.68
Maximum DC Reverse Current At Rated DC Blocking Voltage	$I_R$	$T_J=25^\circ\text{C}$	5
		$T_J=100^\circ\text{C}$	50
Typical Junction Capacitance <sup>1</sup>	$C_J$	40	pF
Typical Thermal Resistance <sup>2</sup>	$R_{\theta JA}$	50	°C / W
Typical Thermal Resistance <sup>3</sup>	$R_{\theta JC}$	25	°C / W
Voltage Rate of Change (Rated $V_R$ )	dv/dt	1000	V / $\mu\text{s}$
Operating Temperature Range	$T_J$	-50~150	°C
Storage temperature	$T_{STG}$	-65~150	°C

Notes:


1. Measured at 1MHz and applied reverse voltage of 5.0V D.C.
2. Thermal Resistance Junction to Ambient.
3. Thermal Resistance Junction to Case.

**RATINGS AND CHARACTERISTIC CURVES**


Typical Forward Current Derating Curve




Typical Reverse Characteristic



Typical Junction Capacitance



Typical Forward Characteristic



Maximum Non- Repetitive Forward Surge Current

