



DESCRIPTION

The SM220AF~SM2200AF are available in SMAF package.

ORDERING INFORMATION

Package Type	Part Number
SMAF	SM220AF
	SM240AF
	SM260AF
	SM280AF
	SM2100AF
	SM2120AF
	SM2150AF
	SM2200AF
Note	SPQ: 3,000pcs/Reel
AiT provides all RoHS Compliant Products	

FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SMAF package

MECHANICAL DATA

Case: SMAF

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 27mg 0.00086oz

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitivederate by 20 %

Parameter	Symbol	SM	SM	SM	SM	SM	SM	SM	SM	Unit
		220AF	240AF	260AF	280AF	2100AF	2120AF	2150AF	2200AF	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS Voltage	V_{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	2.0								A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	50				40				A
Max Instantaneous Forward Voltage at 2A	V_F	0.55		0.70		0.85		0.95		V
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	$T_A=25^{\circ}C$	0.5			0.3				mA
		$T_A=100^{\circ}C$	5			3				
Typical Junction Capacitance ^{NOTE1}	C_j	220			80				pF	
Operating Junction Temperature Range	T_J	-55 to +125								°C
Storage Temperature Range	T_{STG}	-55 to +150								°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4V D.C



TYPICAL PERFORMANCE CHARACTERISTICS

Figure. 1 Forward Current Derating Curve




Figure. 2 Typical Reverse Characteristics




Figure. 3 Typical Forward Characteristic




Figure. 4 Typical Junction Capacitance






Figure. 5 Maximum Non-Repetitive Peak Forward Surge Current






PACKAGE INFORMATION

Dimension in SMAF Package (Unit: mm)



The recommended mounting pad size



Unit: $\frac{\text{mm}}{\text{(mil)}}$

UNIT		A	C	D	E	e	g	HE	\angle
mm	Min	1.1	0.20	3.7	2.7	1.6	1.2	4.9	7°
	Max	0.9	0.12	3.3	2.4	1.3	0.8	4.4	
mil	Min	43	7.9	146	106	63	47	193	
	Max	35	4.7	130	94	51	31	173	



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.