


## Micropower, SC-70, 100mA CMOS LDO Regulator

### FEATURES

- Tiny 5-pin SC-70 Package
- Guaranteed 100 mA Output
- 2.5% Output Voltage Accuracy
- Low Dropout Voltage: 250 mV at 100mA
- Low Quiescent Current: 65  $\mu$ A
- Low Ground Current: 135  $\mu$ A @  $I_L = 100$ mA
- Low Shutdown Current: 1  $\mu$ A MAX
- Current Limit: 190mA
- Thermal Shutdown: 168°C
- Good Load and Line Regulation
- Fast Transient Response:  $T_{ON}/T_{OFF}=80\mu$ s
- Low Temperature Coefficient
- Unconditionally Stable with 1  $\mu$ F Ceramic
- Fixed Outputs: 1.8V, 2.5V, 2.7V, 2.85V, 3.0V, 3.3V, 5V
- 100mA Replacement for 80mA MIC5213



\*connect to GND for enhanced thermal performance


### APPLICATIONS

- Digital Cordless Phones
- Cellular Phones
- PDAs
- Digital Still Cameras
- MP3 Players
- Battery-Powered Equipment
- Medical Devices
- Data Cable

### DESCRIPTION

The SP6213 is a 100mA CMOS linear voltage regulator offered in an SC-70 package that reduces board space requirements by 50% over a SOT-23 package. The SP6213 features low dropout voltage (250mV at 100mA ), low ground current (135 $\mu$ A at full load) and low, 65 $\mu$ A quiescent current. Designed specifically for hand-held, battery powered devices, the device includes an enable/shutdown pin. Regulator ground current increases only slightly in dropout to extend battery life. The SP6213 is offered in an industry standard 5-pin SC-70 package. SP6213 is available in 1.8V, 2.5V, 2.7V, 2.85V, 3.0V, 3.3V and 5.0V fixed output voltages.

### FUNCTIONAL DIAGRAM



Supply Input Voltage ( $V_{IN}$ ).....-2V to 7V  
 Output Voltage ( $V_{OUT}$ ).....-0.6 to ( $V_{IN} + 1V$ )  
 Enable Input Voltage ( $V_{EN}$ ).....-2V to 7V  
 Power Dissipation ( $P_D$ ).....Internally Limited, Note 3  
 Lead Temperature (soldering 5s).....260°C  
 Storage Temperature.....-65°C to +150°C

## ABSOLUTE MAXIMUM RATINGS (Note 1)

(Note 1) These are stress ratings only and functional operation of the device at these ratings or any other above those indicated in the operation sections of the specifications below is not implied. Exposure to absolute maximum rating conditions for extended periods of time may affect reliability.

## OPERATING RATINGS (Note 2)

Input Voltage ( $V_{IN}$ ) ..... +2.5V to +6V  
 Enable Input Voltage ( $V_{EN}$ ) ..... 0V to +6V  
 Junction Temperature ( $T_J$ ) ..... -40°C to +125°C

Thermal Resistance ..... (Note 3)  
 SC-70-5 ( $\theta_{JA}$ ) ..... 330°C/W

## ELECTRICAL SPECIFICATIONS

$V_{IN} = V_{OUT} + 0.5V$ ,  $I_L = 100\mu A$ ,  $C_{IN} = 1\mu F$ ,  $C_{OUT} = 1\mu F$ ,  $T_J = 25^\circ C$ , unless otherwise noted. The ♦ denotes the specifications which apply over the full operating temperature range, unless otherwise specified.

| PARAMETER   | MIN        | TYP                  | MAX                  | UNITS         | ♦ | CONDITIONS  |
|---|------------|----------------------|----------------------|---------------|---|---|
| Output Voltage Accuracy, ( $V_{OUT}$ )  | -2.5<br>-4 |                      | 2.5<br>4             | %             | ♦ | Variation from specified $V_{OUT}$  |
| Output Voltage Temperature Coefficient, Note 4, ( $\Delta V_{OUT}/\Delta T$ ) |            | 60                   |                      | ppm/<br>° C   |   |   |
| Minimum Supply Voltage  |            | 2.50<br>2.55<br>2.75 | 2.70<br>2.85<br>3.00 | V             |   | $I_{OUT} = 100\mu A$<br>$I_{OUT} = 50mA$<br>$I_{OUT} = 100mA$                   |
| Line Regulation, ( $\Delta V_{OUT}/V_{IN}$ )                                  |            | 0.05                 | 0.2                  | %/V           | ♦ | $V_{IN} = (V_{OUT} + 0.5V)$ to 6V   |
| SP6213-1.8V Line Regulation   |            | 0.05                 | 0.2                  | %/V           | ♦ | $V_{IN} = 2.8V$ to 6V   |
| Load Regulation, Note 5, ( $\Delta V_{OUT}$ )                                 |            | 0.4                  | 0.8                  | %             | ♦ | $I_L = 0.1mA$ to 100mA, $V_{IN} = V_{OUT} + 1V$                                 |
| SP6213-1.8V Load Regulation   |            | 0.4                  | 0.8                  | %             | ♦ | $I_L = 0.1mA$ to 100mA, $V_{IN} = 3.0V$   |
| Dropout Voltage, Note 6, ( $V_{IN} - V_{OUT}$ )                               |            | 0.25                 | 4                    | mV            | ♦ | $I_L = 100\mu A$  |
|   |            | 130                  | 250                  | mV            | ♦ | $I_L = 50mA$  |
|   |            | 250                  | 500                  | mV            | ♦ | $I_L = 100mA$   |
| Quiescent Current, ( $I_{GND}$ )  |            | 0.01<br>65           | 1<br>125             | $\mu A$       | ♦ | $V_{EN} \leq 0.4V$ (Shutdown)<br>$V_{EN} \geq 1.6V$ (Operating), $I_L = 0\mu A$ |
|   |            | 65                   | 125                  | $\mu A$       | ♦ | $V_{EN} \geq 1.6V$ , $I_L = 100\mu A$   |
| Ground Pin Current, Note 7, ( $I_{GND}$ )                                     |            | 100                  | 175                  | $\mu A$       | ♦ | $V_{EN} \geq 1.6V$ , $I_L = 50mA$   |
|   |            | 135                  | 250                  | $\mu A$       | ♦ | $V_{EN} \geq 1.6V$ , $I_L = 100mA$  |
|   |            | 74<br>40             |                      |               |   | Frequency = 100Hz, $I_L = 10mA$<br>Frequency = 400kHz, $I_L = 10mA$             |
| Power Supply Rejection Ratio, (PSRR)  |            | 74<br>40             |                      | dB            |   |   |
| Current Limit, ( $I_{CL}$ )   | 120        | 190                  | 350                  | mA            | ♦ |   |
| Thermal Limit   |            | 168<br>153           |                      | ° C           |   | Turns On<br>Turns Off   |
| Thermal Regulation, ( $\Delta V_{OUT}/\Delta P_D$ ), Note 8                   |            | 0.05                 |                      | %/W           |   |   |
| Output Noise ( $e_{NO}$ )   |            | 250                  |                      | $\mu V_{rms}$ |   | $I_L = 50mA$ , $C_L = 1\mu F$ , 10Hz to 100kHz                                  |

## ELECTRICAL SPECIFICATIONS: Continued

$V_{IN} = V_{OUT} + 0.5V$ ,  $I_L = 100\mu A$ ,  $C_{IN} = 1\mu F$ ,  $C_{OUT} = 1\mu F$ ,  $T_J = 25^\circ C$ , unless otherwise noted. The ♦ denotes the specifications which apply over the full operating temperature range, unless otherwise specified.

| PARAMETER  | MIN | TYP  | MAX | UNITS   | ♦ | CONDITIONS                                |
|--|-----|------|-----|---------|---|---|
| <b>ENABLE INPUT</b>                              |     |      |     |         |   |   |
| Enable Input Logic-Low Voltage, ( $V_{IL}$ )     |     |      | 0.4 | V       | ♦ | Regulator Shutdown                        |
| Enable Input Logic-High Voltage, ( $V_{IH}$ )    | 1.6 |      |     | V       | ♦ | Regulator Enabled                         |
| Enable Input Current, ( $I_{IL}$ ), ( $I_{IH}$ ) |     | 0.01 | 1   | $\mu A$ | ♦ | $V_{IL} \leq 0.4V$                        |
|  |     | 0.01 | 1   | $\mu A$ | ♦ | $V_{IH} \geq 1.6V$                        |
| Turn on Time ( $T_{ON}$ )                        |     | 80   | 165 | $\mu s$ |   | $I_{OUT} = 50mA$                          |
| Turn off Time ( $T_{OFF}$ )                      |     | 80   | 175 | $\mu s$ |   | $I_{OUT} = 100\mu A$<br>$I_{OUT} = 100mA$ |
|  |     | 30   | 35  |         |   |   |

**Note 1.** Exceeding the absolute maximum rating may damage the device.

**Note 2.** The device is not guaranteed to function outside its operating rating.

**Note 3.** The maximum allowable power dissipation at any  $T_A$  (ambient temperature) is  $P_{D(MAX)} = (T_{J(MAX)} - T_A) / \theta_{JA}$ . Exceeding the maximum allowable power dissipation will result in excessive die temperature, and the regulator will go into thermal shutdown. The  $\theta_{JA}$  of the SP6213 (SC-70-5) is  $330^\circ C/W$  mounted on a PC board with minimum copper area (see "Thermal Considerations" section for further details).

**Note 4.** Output voltage temperature coefficient is defined as the worst case voltage change divided by the total temperature range.

**Note 5.** Load Regulation is measured at constant junction temperature using low duty cycle pulse testing. Parts are tested for load regulation in the load range. Changes in output voltage due to heating effects are covered by the thermal regulation specification.

**Note 6.** Dropout Voltage is defined as the input to output differential at which the output voltage drops 2% below its nominal value measured at 0.5V differential. Not applicable to output voltages less than 2.7V.

**Note 7.** Ground pin current is the regulator quiescent current. The total current drawn from the supply is the sum of the load current plus the ground pin current.

**Note 8.** Thermal regulation is defined as the change in output voltage at a time "t" after a change in power dissipation is applied, excluding load or line regulation effects. Specifications are for a 100mA load pulse at  $V_{IN} = 6V$  for  $t = 10ms$ .

**Note 9.** Devices are ESD sensitive. Handling precautions are recommended.

| PIN NUMBER | PIN NAME         | DESCRIPTION (FUNCTION)                                      |
|------------|------------------|---|
| 3          | GND              | Ground Connection   |
| 4          | V <sub>OUT</sub> | Regulator Output  |
| 5          | V <sub>IN</sub>  | Supply Input  |
| 1          | EN               | Enable / Shutdown (Logic high=enable; logic low = shutdown) |
| 2          | NC               | No Connection   |

## THEORY OF OPERATION

### General Overview

#### Enable/Shutdown Operation

The SP6213 is turned off by pulling the EN pin low and turned on by pulling it high. If this enable/shutdown feature is not required, EN should be tied to V<sub>IN</sub> to keep the regulator output on at all times.

#### Input Capacitor

A small capacitor of about 1μF is required from V<sub>IN</sub> to GND if e.g. a battery is used as the input. Any good quality ceramic or tantalum capacitor may be used at the input.

#### Output Capacitor

An output capacitor is required between V<sub>OUT</sub> and GND to prevent oscillation. The minimum size of the output capacitor is a 0.47 μF ceramic. The given datasheet values relate to an IC with a ceramic output capacitor of 1μF. Larger values make the IC more stable which means an improvement of the regulator's transient response. For a lower output current, the output capacitance can be chosen smaller in order to have the same output stability.

#### No Load Stability

The SP6213 will remain stable and in regulation with no external load (other than the internal voltage driver) unlike many other voltage regulators. This is especially important in CMOS RAM keep-alive applications.

#### Thermal Considerations

The SP6213 is designed to provide 100 mA of continuous current in a very tiny package. Maximum power dissipation can be calculated based on

the output current and the voltage drop across the part. To determine the maximum power dissipation of the package, use the junction-to-ambient thermal resistance of the device and the following basic equation:

$$P_D = (T_{J(max)} - T_A) / \Theta_{JA}$$

T<sub>J(max)</sub> is the maximum junction temperature of the die and is 125°C. T<sub>A</sub> is the ambient operating. Θ<sub>JA</sub> is the junction-to-ambient thermal resistance for the regulator and is layout dependent. The actual power dissipation of the regulator circuit can be determined using one simple equation:

$$P_D = (V_{IN} - V_{OUT}) * I_{OUT} + V_{IN} * I_{GND}$$

Substituting P<sub>D(max)</sub> for P<sub>D</sub> and solving for the operating conditions that are critical to the application will give the maximum operating conditions for the regulator circuit. For example, if we are operating the SP6213 at 3.0V output at room temperature, with a minimum footprint layout, we can determine the maximum input voltage for a set output current.

$$P_{D(max)} = [(125^\circ\text{C} - 25^\circ\text{C}) / (330^\circ\text{C}/\text{W})] = 303 \text{ mW}$$


To prevent the device from entering thermal shutdown, maximum power dissipation can not be exceeded. Using the output voltage of 3.0V and an output current of 100 mA, the maximum input voltage can be determined. Ground pin current can be taken from the electrical spec's- table (0.135 mA at 100 mA). The maximum input voltage is determined as follows:

$$303 \text{ mW} = (V_{IN} - 3.0\text{V}) * 100 \text{ mA} + V_{IN} * 0.135 \text{ mA}$$


After calculations, we find that the maximum input voltage of a 3.0V application at 100mA of output current in an SC-70-5 package is 6.02V.

# TYPICAL CHARACTERISTICS


27°C,  $V_{IN}=4V$ ,  $I_L = 0.1mA$ ,  $C_{IN} = C_{OUT} = 1\mu F$  unless otherwise specified.




Output Voltage vs. Temperature ( $I_{OUT} = 0.1mA$ )




Output Voltage vs. Temperature ( $I_{OUT} = 10mA$ )




Output Voltage vs. Temperature ( $I_{OUT} = 50mA$ )




Output Voltage vs. Temperature ( $I_{OUT} = 100mA$ )




Quiescent Current vs. Temperature ( $I_{OUT} = 0A$ )



Dropout Voltage vs. Temperature




Output Voltage vs. Output Current




Output Voltage vs. Input Voltage

# TYPICAL CHARACTERISTICS: Continued


27°C,  $V_{IN}=4V$ ,  $I_L = 0.1mA$ ,  $C_{IN} = C_{OUT} = 1\mu F$  unless otherwise specified.




**Quiescent Current vs. Input Voltage**




**Ground Current vs. Output Current**




**Ground Current vs. Input Voltage**




**Dropout Voltage vs. Output Current**




**Turn-on Characteristic ( $V_{IN} = 4V$ ,  $I_{OUT} = 100\mu A$ )**



**Turn-on Characteristic ( $V_{IN} = 4V$ ,  $I_{OUT} = 100mA$ )**




**Turn-on Characteristic ( $V_{IN} = 7V$ ,  $I_{OUT} = 100\mu A$ )**




**Turn on Time ( $V_{IN} = 7V$ ,  $I_{OUT} = 100mA$ )**


27°C,  $V_{IN}=4V$ ,  $I_L = 0.1mA$ ,  $C_{IN} = C_{OUT} = 1\mu F$  unless otherwise specified.




Turn off Time ( $V_{IN}=4V$ ,  $I_{OUT}=100\mu A$ )




Turn off Time ( $V_{IN} = 4V$ ,  $I_{OUT} = 100mA$ )




Turn off Time ( $V_{IN} = 7V$ ,  $I_{OUT} = 100\mu A$ )




Turn off Time ( $V_{IN} = 7V$ ,  $I_{OUT} = 100mA$ )




( $V_{IN} = 4V$ ,  $I_{OUT} = 100\mu A$ )



In-Rush Current ( $V_{IN} = 4V$ ,  $I_{OUT} = 100mA$ )




Load Transient Response ( $V_{IN} = 4V$ )




Load Transient Response ( $V_{IN} = 4V$ )


27°C,  $V_{IN}=4V$ ,  $I_L = 0.1mA$ ,  $C_{IN} = C_{OUT} = 1\mu F$  unless otherwise specified.




Load Transient Response ( $V_{IN} = 7V$ )




Load Transient Response ( $V_{IN} = 7V$ )




Line Transient Response ( $V_{IN}=4V$ ,  $I_{OUT}=100\mu A$ )




Line Transient Response ( $V_{IN}=4V$ ,  $I_{OUT}=10mA$ )



Line Transient Response ( $V_{IN}=7V$ ,  $I_{OUT}=100\mu A$ )






Line Transient Response ( $V_{IN}=7V$ ,  $I_{OUT}=10\mu A$ )



Power Supply Rejection Ratio,  $V_o=3V$





NOTE:

1. All dimensions are in inches/(millimeters)
2. Dimensions are inclusive of plating
3. Dimensions are exclusive of mold flash & metal burr
4. All specifications comply to EIAJ SC70

| SYMBOL | MIN                 | MAX          |
|--------|---------------------|--------------|
| e      | 0.026BSC/(0.65 BSC) |              |
| D      | 0.071/(1.80)        | 0.067/(2.20) |
| b      | 0.006/(0.15)        | 0.012/(0.30) |
| E      | 0.045/(1.15)        | 0.053/(1.35) |
| HE     | 0.071/(1.80)        | 0.094/(2.40) |
| Q1     | 0.004/(0.10)        | 0.016/(0.40) |
| A2     | 0.031/(0.80)        | 0.039/(1.00) |
| A1     | 0.000/(0.00)        | 0.004/(0.10) |
| A      | 0.031/(0.80)        | 0.043/(1.10) |
| c      | 0.004/(0.10)        | 0.007/(0.18) |
| L      | 0.004/(0.10)        | 0.012/(0.30) |

5 PIN SC-70

| <b>Model</b>         | <b>TOP MARK</b> | <b>Temperature Range</b> | <b>Package Type</b>       |
|----------------------|-----------------|--------------------------|---------------------------|
| SP6213EC5-1.8 .....  | W00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-2.5 .....  | F00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-2.7 .....  | E00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-2.85 ..... | D00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-3.0 .....  | A00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-3.3 .....  | C00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |
| SP6213EC5-5.0 .....  | B00 .....       | -40°C to +125°C .....    | Tape & Reel ..... SC-70-5 |


**ANALOG EXCELLENCE**
**Sipex Corporation**

**Headquarters and  
Sales Office**  
233 South Hillview Drive  
Milpitas, CA 95035  
TEL: (408) 934-7500  
FAX: (408) 935-7600

**Sales Office**  
22 Linnell Circle  
Billerica, MA 01821  
TEL: (978) 667-8700  
FAX: (978) 670-9001  
e-mail: sales@sipex.com

Sipex Corporation reserves the right to make changes to any products described herein. Sipex does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others.