

SR320 THRU SR3200
SCHOTTKY BARRIER RECTIFIER



VOLTAGE

20 THRU 200Volts

CURRENT

3.0 Ampers

DO-27/DO-201AD


Unit:(mm)

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Metal silicon junction,majority carrier conduction
- ◆ Low power loss,high efficiency
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:
250°C/10 seconds,0.375"(9.5mm) lead length,
5 lbs. (2.3kg) tension

MECHANICAL DATA

Case: JEDEC DO-27 molded plastic body
Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight: 0.04 ounce, 1.10 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (TA=25°C(UNLESS OTHERWISE NOTED))

Single phase half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

	SYMBOLS	SR 320	SR 330	SR 340	SR 350	SR 360	SR 370	SR 380	SR 390	SR 3100	SR 3150	SR 3200	UNITS	
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	70	80	90	100	150	200	VOLTS	
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	49	56	63	70	105	140	VOLTS	
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	70	80	90	100	150	200	VOLTS	
Maximum average forward rectified current 0.375"(9.5mm) lead length(see fig.1)	$I_{(AV)}$	3.0											Amps	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	80.0											Amps	
Maximum instantaneous forward voltage at 3.0A	V_F	0.55		0.70		0.85			0.95			Volts		
Maximum DC reverse current at rated DC blocking voltage	I_R	0.5					0.2			2.0				mA
Typical junction capacitance (NOTE 1)	C_J	250			160									pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	40.0											°C/W	
Operating junction temperature range	T_J	-65 to +125					-65 to +150							°C
Storage temperature range	T_{STG}	-65 to +150											°C	

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. Thermal resistance from junction to ambient at 0.375"(9.5mm)lead length,P.C.B. mounted

SR320 THRU SR3200
SCHOTTKY BARRIER RECTIFIER



RATING AND CHARACTERISTIC CURVES




Fig-FORWARD CURRENT DE-RATING CURVE




Fig.2-TYPICAL INSTANTANEOUS FORWARD




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL JUNCTION CAPACITANCE




Fig.5- MAXIMUM NON - REPETITIVE SURGE CURRENT




FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



SR320 THRU SR3200
SCHOTTKY BARRIER RECTIFIER



ORDER INFORMATION

- Packing information
T/R - 1.25K per BOX