

# Distinctive Characteristics


Top or side actuation permits flexible board design.

Compact dimensions and low profile allow high density mounting and close stacking of PC boards.

Crisp actuation positively indicates circuit status.

Double molded thermoset base and thermo-plastic housing prevent loosening of terminals due to high soldering temperatures.


Award-winning STC mechanism with benefits unavailable in conventional mechanisms: smoother, positive detent actuation, increased contact stability, and unparalleled logic-level reliability. (Additional STC details in Terms and Acronyms in the Supplement section.)



Insert molded terminals lock out flux, solvents, and other contaminants.

Inch or metric terminal spacing for standard PC board grid (.100" x .100" or 2.0mm x 2.0mm).

Actual Size



# General Specifications

## Electrical Capacity (Resistive Load)

- Power Level (code 2):** 0.1A @ 30V DC
- Logic Level (code 4):** 0.4VA maximum @ 28V AC/DC maximum  
(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)  
Note: Find additional explanation of operating range in Supplement section.

## Other Ratings

- Contact Resistance:** 20 milliohms maximum for power level; 40 milliohms maximum for logic level
- Insulation Resistance:** 100 megohms minimum @ 500V DC
- Dielectric Strength:** 500V AC minimum 1 minute minimum
- Mechanical Life:** 10,000 operations minimum
- Electrical Life:** 10,000 operations minimum
- Contact Timing:** Shorting (make-before-break)
- Total Travel:** .079" (2.0mm)

## Materials & Finishes

- Actuator:** Polyamide
- Upper Case:** Polyester for 3-On models; polyacetal for all other models
- Lower Case:** Glass fiber reinforced polyester for 3-On models;  
glass fiber reinforced polybutylene terephthalate (thermoplastic) for other models
- Movable Contactor:** Phosphor bronze with silver plating (code 2) or  
phosphor bronze with gold plating (code 4)
- Interior Base:** Phenolic resin (thermoset)
- Terminals:** Brass with silver plating over copper plating or brass with gold plating

## Environmental Data

- Operating Temp Range:** -15°C through +60°C (+5°F through +140°F)
- Humidity:** 90 ~ 95% humidity for 96 hours @ 40°C (104°F)
- Vibration:** 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
- Shock:** 50G (490m/s<sup>2</sup>) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

## PCB Processing

- Soldering:** Wave Soldering: See Profile B in Supplement section.  
Manual Solder: See Profile B in Supplement section.
- Cleaning:** Hand clean locally using alcohol based solution.

## Standards & Certifications

- UL Recognition or CSA Certification:** The SS series devices have not been tested for UL recognition and CSA certification. These switches are designed for use in a low-voltage, low-current circuit. When used as intended in a low-voltage, low-current circuit, the results do not produce hazardous energy.

## TYPICAL SWITCH ORDERING EXAMPLE

**SS**

**12S**

**D**

**P**

**2**

**POLES & CIRCUITS**

<b>12S</b>	SPDT	ON	NONE	ON
<b>*14M</b>	SP3T	ON	ON	ON
<b>22S</b>	DPDT	ON	NONE	ON

See Poles & Circuits chart below.

\* 14M Circuit with silver contacts only.

**CONTACT MATERIAL & RATINGS**

<b>2</b>	Silver Rated 0.1A @ 30V DC
<b>*4</b>	Gold Rated 0.4VA maximum @ 28V AC/DC maximum

\* Gold not available with SS14M.

**TERMINAL SPACING**

<b>B</b>	Metric 2.0mm x 2.0mm
<b>D</b>	Inch .100" x .100"


**ACTUATION**

<b>P</b>	Top Actuated
<b>H</b>	Side Actuated

### DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

#### SS12SDP2

Top Actuated






Silver Contacts Rated 0.1A @ 30V DC

SPDT ON-NONE-ON Circuit



Terminals with .100" Spacing

### POLES & CIRCUITS



		Slide Position			Connected Terminals			Throw & Schematics
Pole	Model	Right	Center	Left	Right	Center	Left	
SP	<b>SS12S</b>	ON	NONE	ON	2-1	OPEN	2-3	SPDT 
SP	<b>SS14M</b>	ON	ON	ON	3-4	3-2	3-1	SP3T  Make-Before-Break ON-OFF-ON circuit can be created by not connecting terminal 2.
DP	<b>SS22S</b>	ON	NONE	ON	2-1 5-4	OPEN	2-3 5-6	DPDT 

## TERMINAL SPACING



### B Metric 2.0mm x 2.0mm with Black Base



On-None-On Single Pole Models





On-None-On Double Pole Models





3-On Models



### D Inch .100" x .100" with Gray Base



On-None-On Single Pole Models




On-None-On Double Pole Models




3-On Models

## ACTUATION

### P Top Actuated



### H Side Actuated



## CONTACT MATERIALS & RATINGS

**2** Silver over Phosphor Bronze

Power Level

0.1A @ 30V DC

**4** Gold over Silver/Phosphor Bronze

Logic Level


0.4VA max @ 28V AC/DC max

Complete explanation of operating range in Supplement section.

## TYPICAL SWITCH DIMENSIONS

### Top Actuated


### Single & Double Pole



SS12SDP2

### Side Actuated


### Single & Double Pole



SS12SDH2

### 3-On Circuit • Top Actuated


### Single Pole



SS14MDP2

### 3-On Circuit • Side Actuated

### Single Pole



SS14MDH2