



STK4703 SERIES	thick film hybrid IC	CIRCUIT DRAWING No.6026
2-CHANNEL 10 TO 50W MIN AF POWER AMP.(DUAL-SUPPLY)		 4029

Features


- AF Output Power

STK4773: 10Wmin.	STK4793: 15Wmin.	STK4803: 20Wmin.
STK4813: 20Wmin.	STK4833: 25Wmin.	STK4843: 30Wmin.
STK4853: 30Wmin.	STK4863: 35Wmin.	STK4873: 35Wmin.
STK4893: 40Wmin.	STK4913: 50Wmin.	
- Contains emitter follower circuit for upgrading.
- Case temperature 125°C is guaranteed, thereby enabling great reduction of heat sink.
- By attaching muting circuit externally, pop noise at the time of power ON/OFF can be rejected.

STK5320 SERIES	thick film hybrid IC	CIRCUIT DRAWING No.6028
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4036 4037 4039


Features

- | | | | | |
|-----------|------------------|------------------|------------------|------------------|
| | STK5321 | STK5322 | STK5324 | STK5325 |
| Output 1: | 9.5±0.1V (1.6A) | 9.5±0.1V (1.6A) | 12.0±0.1V (1.6A) | 12.0±0.1V (1.6A) |
| Output 2: | 12.0±0.3V (2.5A) | 15.0±0.3V (2.5A) | 12.0±0.3V (2.5A) | 14.0±0.3V (2.5A) |
-
- | | | | | |
|-----------|------------------|------------------|--|--|
| | STK5326 | STK5327 | | |
| Output 1: | 12.0±0.1V (1.6A) | 15.0±0.3V (2.5A) | | |
| Output 2: | 13.0±0.3V (2.5A) | 13.5±0.3V (1.6A) | | |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
 - Provides cutoff function to cut off output voltage by external signal.
 - Output voltages of 2 outputs are set.
 - Small size and excellent cost performance.
 - Package Number: 4036 (STK5324)
4037 (STK5325, 5326, 5327)
4039 (STK5321, 5322)

STK5346	thick film hybrid IC	CIRCUIT DRAWING No.6027
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4038

Features

- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.

STK5352,5353	thick film hybrid IC	CIRCUIT DRAWING No.6029
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4064

Features

- | | | | | |
|-----------|------------------|------------------|--|--|
| | STK5352 | STK5353 | | |
| Output 1: | 6.0±0.1V (0.5A) | 5.1±0.1V (0.5A) | | |
| Output 2: | 12.0±0.1V (1.5A) | 12.0±0.1V (1.5A) | | |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology)
 - Contains power supply for microcomputer.
 - Output voltages of 2 outputs are set.
 - Small size and excellent cost performance