

SWS1000L-24



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	SWS-L
<b>Status</b>	Production
<b>Feature</b>	for Medical instruments
<b>Option</b>	
<b>Option Lineup</b>	
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 350V
Efficiency	86% Typ.
Rated Output Voltage[DC]	24V
Output Voltage Range[DC]	19.2 to 28.8V
Maximum Output Current	44A
Maximum Average Current	
Maximum Peak Current	51A
Maximum Output Power	1056W
Maximum Average Power	
Maximum Peak Power	1224W

### Cases Shape & Size

Case'□ shape	Unit
Width(W)	150mm Nom.
Height(H)	61mm Nom.
Depth(D)	240mm Nom.
Weight	2300g Typ.

### Other

Operating Temp. Range	-20 to 74°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	UL60601-1
	EN60601-1
	EN50178
	CSA-C22.2 No.601.1-M90

Safety Standard(Conformed)

Den-an  
EN61010-1

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.