


Product Description

Stanford Microdevices' SXL-208 amplifier is a high efficiency GaAs Heterojunction Bipolar Transistor (HBT) MMICs housed in low-cost surface-mountable plastic package. These HBT MMICs are fabricated using molecular beam epitaxial growth technology which produces reliable and consistent performance from wafer to wafer and lot to lot.

These amplifiers are specially designed for use as driver devices for infrastructure equipment in the 800-970 MHz cellular, ISM and narrowband PCS.

Its high linearity make it an ideal choice for multi-carrier as well as digital applications.

Output Third Order Intercept Point vs. Frequency



Electrical Specifications at Ta = 25C

| Symbol | Parameters; Test Conditions: $Z_0 = 50 \text{ Ohms}$, $f = 800\text{-}970 \text{ MHz}$ | | Units | Min. | Typ. | Max. |
|-----------|--|--|------------|------|----------------|------|
| P_{1dB} | Output Power at 1dB Compression | $f = 820\text{-}880 \text{ MHz}$ $f = 800\text{-}970 \text{ MHz}$ | dBm dBm | 30.0 | 30.5 30.0 | |
| S_{21} | Power Gain | $f = 800\text{-}970 \text{ MHz}$ | dB | | 18.0 | |
| PAE | Power Added Efficiency | $f = 820\text{-}880 \text{ MHz}$ $f = 800\text{-}970 \text{ MHz}$ | % % | | 44 40 | |
| VSWR | Input VSWR | $f = 820\text{-}880 \text{ MHz}$ $f = 800\text{-}970 \text{ MHz}$ | - | | 1.5:1 2.0:1 | |
| VSWR | Output VSWR | $f = 820\text{-}880 \text{ MHz}$ $f = 800\text{-}970 \text{ MHz}$ | - | | 1.5:1 2.5:1 | |
| IP_3 | Third Order Intercept Point | $f = 820\text{-}880 \text{ MHz}$ $f = 800\text{-}970 \text{ MHz}$ | dBm dBm | 43 | 46 45 | |
| I_d | Device Current | $V_c = +5V$ | mA | | 460 | |

Preliminary

SXL-208




**800-970 MHz 50 Ohm
Power MMIC Amplifier**

Product Features


- Patented High Reliability GaAs HBT Technology
- High 3rd Order Intercept : +46dBm Typ. at 900 MHz
- High Gain : 18dB Typ. at 900 MHz
- Surface-Mountable Power Plastic Package

Applications


- Multi-Carrier Systems
- Basestation Applications

SXL-208 800-970 MHz Power MMIC Amplifier
Typical Performance at 25° C (Vc = 5.0V, Ic=460mA)
Output Power and Efficiency vs. Frequency

Gain and Isolation vs. Frequency

Input & Output Return Loss vs. Frequency


Third Order Intercept Point vs. Output Tone Power



Tone Power= +14dBm, IP3 = +46dBm



Tone Power= +17dBm, IP3 = +46dBm

Absolute Maximum Ratings

| Parameter | Absolute Maximum |
|-----------------------|------------------|
| Device Voltage | 7V |
| Device Current | 700mA |
| Power Dissipation | 5000mW |
| RF Input Power | 100mW |
| Junction Temperature | +175C |
| Operating Temperature | -45C to +85C |
| Storage Temperature | -65C to +175C |

Notes:

1. Operation of this device above any one of these parameters may cause permanent damage.


Part Number Ordering Information

| Part Number | Devices Per Reel | Reel Size |
|-------------|------------------|-----------|
| SXL-208-TR1 | 500 | 7" |
| SXL-208-TR2 | 1000 | 13" |
| SXL-208-BLK | 100/TRAY | - |

**MTTF vs. Temperature
@ Id = 460mA**

| Lead Temperature | Junction Temperature | MTTF (hrs) |
|------------------|----------------------|-------------|
| +25C | +103C | >10,000,000 |
| +60C | +138C | 1,000,000 |
| +85C | +163C | 100,000 |

Thermal Resistance (Lead-Junction): 60° C/W



**SXL-208 Evaluation Board
(P/N SXL-208EB)**

**Application Schematic and Bias Circuit
for 900 MHz Operation**

