


## Rectifier Diode SXXHN/HR14





Symbol	Characteristics	Conditions	$T_J(^{\circ}\text{C})$	Value	Unit
<b>BLOCKING PARAMETERS</b>					
$V_{RRM}$	Repetitive peak reverse voltage		180	200-1500	V
$I_{RRM}$	Repetitive peak reverse current	$V = V_{RRM}$	180	2	mA
<b>CONDUCTING PARAMETERS</b>					
$I_{F(AV)}$	Average on-state current	180 sine, 50Hz, $T_C = 130^{\circ}\text{C}$		12	A
$I_{RMS}$	RMS on-state current			19	A
$I_{FSM}$	Non repetitive peak surge on-state current	Sine wave, 10mS without reverse voltage	180	250	A
$I^2t$	Permissible surge energy			310	A <sup>2</sup> S
$V_{FM}$	Peak on-state voltage drop	On-state current = 38A	180	1.50	V
$V_0$	Typical forward conduction Threshold voltage		180	0.70	V
$r_0$	Typical forward slope resistance		180	16.50	m $\Omega$
<b>THERMAL &amp; MECHANICAL PARAMETERS</b>					
$R_{TH(J-C)}$	Thermal impedance, 180 <sup>o</sup> conduction, Sine	Junction to case		4.50	<sup>o</sup> C/W
$R_{TH(C-HK)}$	Thermal impedance	Case to heatsink		0.60	<sup>o</sup> C/W
$T_J$	Maximum Permissible junction temperature			180	<sup>o</sup> C
$T_{STG}$	Storage temperature range			-40 – 180	<sup>o</sup> C
F	Mounting Torque			2	NM
W	Weight			10	gms




# HIND RECTIFIERS LTD

# Rectifier Diode SXXHN/HR14




All dimensions in mm


## On State Power Loss




**HIND RECTIFIERS LTD**




## Maximum Permissible Case Temp




## Max non repetitive Surge Current







Transient Thermal Impedance Junction to Case



On State Characteristics



## Rectifier Diode SXXHN/HR14



### Ordering Information: -

<b>S</b>	<b>XX</b>	<b>HN / HR</b>	<b>14</b>
Hirect make Rectifier Diode	$V_{RRM} = XX * 100$ e.g. $12 * 100 = 1200V$	HN – Normal Polarity HR – Reverse Polarity	$I_{F(AV)} = 14A$

Hind Rectifiers Ltd reserves the right to change the specifications without notice.

This datasheet specifies technical information for semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

#### Hind Rectifiers Ltd

Lake Road

Bhandup (West)

Mumbai – 400 078

Tel: - +91 22 2596 8027/28/29/31

Fax: - +91 22 2596 4114

Fax: - +91 22 2596 4114

E-mail: - [marketing@hirect.com](mailto:marketing@hirect.com)

Website: - [www.hirect.com](http://www.hirect.com)

June-2008



# HIND RECTIFIERS LTD

5 of 5