



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

TIP47

Features


- Halogen free available upon request by adding suffix "-HF"
- Mounting Torque: 5 in-lbs Maximum
- Lead Free Finish/RoHS Compliant(Note 1)("P" Suffix designates RoHS Compliant. See ordering information)
- Silicon Power NPN transistors in TO-220 package.
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CBO}	Collector-Base Voltage	350	V
V_{CEO}	Collector-Emitter Voltage	250	V
V_{EBO}	Emitter-Base Voltage	5.0	V
I_C	Collector Current	1.0	A
I_{CM}	Collector Current Peak	2.0	A
I_B	Base Current	0.6	A
P_D	Collector power dissipation($T_C=25^\circ\text{C}$)	40	W
	Collector power dissipation($T_A=25^\circ\text{C}$)	2	
T_J	Junction Temperature	-65 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-65 to +150	$^\circ\text{C}$
R_{thjc}	Thermal Resistance, Junction to Case	3.125	$^\circ\text{C}/\text{W}$
R_{thja}	Thermal Resistance, Junction to Ambient	62.5	$^\circ\text{C}/\text{W}$

NPN Silicon Power Transistors

TO-220



Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage $I_C=30\text{mA}; I_B=0$	250	---	Vdc
$V_{CE(Sat)}$	Collector-Emitter Saturation Voltage $I_C=1\text{A}; I_B=0.2\text{A}$	1.0	---	Vdc
$V_{BE(ON)}$	Base-Emitter On Voltage $I_C=1\text{A}; V_{CE}=10\text{V}$	1.5	---	Vdc
I_{CES}	Collector Cutoff Current ($V_{CE}=350\text{Vdc}, V_{BE}=0$)	---	1.0	mAdc
I_{EBO}	Emitter Cutoff Current ($V_{EB}=5.0\text{Vdc}, I_C=0$)	---	1.0	mAdc
I_{CEO}	Collector Cutoff Current ($V_{CE}=150\text{Vdc}; I_B=0$)	---	1.0	mAdc
h_{FE-1}	DC Current Gain ($I_C=0.3\text{Adc}, V_{CE}=10\text{Vdc}$)	30	150	
h_{FE-2}	DC Current Gain ($I_C=1.0\text{Adc}, V_{CE}=10\text{Vdc}$)	10		
f_T	Current Gain-Bandwidth Product ($I_C=0.1\text{Adc}; V_{CE}=10\text{Vdc}$)	10		MHz

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	∅
G	.190	.110	2.29	2.79	
H	---	.250	---	6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
T	.230	.270	5.84	6.86	
U	-----	.050	-----	1.27	
V	.045	-----	1.15	-----	



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com